


**New York State Department of Environmental Conservation**  
**Division of Water**  
**Bureau of Water Permits, 4th Floor**  
625 Broadway, Albany, New York 12233-3505  
**Phone:** (518) 402-8111 ▪ **Fax:** (518) 402-9029  
**Website:** www.dec.state.ny.us



*Eqw to 401*  
*This is 402*  
*518 auto*  
*Fred.*

**- NOIT SUBMISSION REQUIRED FOR CONTINUED PERMIT AUTHORIZATION -**

1/29/2007

US ARMY CORPS OF ENGINEERS, USAED, BUFF.  
JUDITH LEITHNER  
CELRB-ED-EE, 1776 NIAGARA STREET  
BUFFALO NY 14207-3199

Re: Renewal of SPDES General Permit for Industrial Stormwater for the following facility:

**NIAGARA FALLS STORAGE SITE**  
**1397 PLETCHER RD**  
**YOUNGSTOWN NY 14174-**  
**Permit ID No.: NYR00B156**

Dear Permittee:

This is to inform you that the New York State Department of Environmental Conservation (NYSDEC) has renewed and modified the existing State Pollutant Discharge Elimination System (SPDES) General Permit for Stormwater Discharges Associated with Industrial Activity. The revised general permit is the SPDES Multi-Sector General Permit (MSGP) for Stormwater Discharges Associated with Industrial Activity (GP-0-06-002). This new permit will be effective from March 28, 2007, to March 27, 2012, and will authorize both new and existing discharges of stormwater to waters of the United States from industrial activities as defined in 40 CFR Part 122.26(b)(14)(i-ix and xi) as well as miscellaneous discharges authorized under state permitting authority.

Copies of the new Multi-Sector General Permit and Fact Sheet are enclosed for your information.

Facilities will need to submit a new Notice of Intent or Termination (NOIT) form to obtain coverage under the MSGP. The NOIT form is located in Appendix B of the enclosed permit. An Adobe Acrobat version of the NOIT form will be available on our website at <http://www.dec.state.ny.us/website/dow/mainpage.htm> which can be completed on your computer or filled in by hand. There is no application fee, but there is an annual regulatory fee which the Department will bill at a later time (normally in September).

Facilities with coverage under the existing SPDES General Permit for Stormwater Discharges Associated with Industrial Activity (GP-98-03) will be allowed up to 90 days from the effective date of the new MSGP (by June 26, 2007) to submit their NOIT form. Additionally, these facilities will be allowed up to 150 days from the effective date of the new MSGP (by August 25, 2007) to update their Stormwater Pollution Prevention Plan (SWPPP) to meet any new requirements.

The completed NOIT must be returned to:


Industrial Stormwater General Permit Coordinator  
NYS DEC, Division of Water  
Bureau of Water Permits  
625 Broadway  
Albany, NY 12233-3505

If you have any questions, please contact Bruce Terbush at (518) 402-8235 or Toni Cioffi at (518) 402-8109.

Enclosure

SUPP\_008459

**New York State Department of Environmental Conservation**  
**SPDES Multi-Sector General Permit**  
**for Stormwater Discharges Associated with Industrial Activity**  
**(GP-0-06-002)**  
**Fact Sheet - January 2007**



The New York State Department of Environmental Conservation (NYSDEC) issued the SPDES Multi-Sector General Permit for Stormwater Discharges Associated with Industrial Activity (GP-0-06-002) on December 27, 2006. The permit will be effective on March 28, 2007. This permit replaces the SPDES General Permit for Stormwater Discharges Associated with Industrial Activity (GP-98-03) and has been revised to more closely reflect the USEPA's Multi-Sector General Permit for Stormwater Discharges Associated with Industrial Activity.

The SPDES Multi-Sector General Permit for Stormwater Discharges Associated with Industrial Activity (GP-0-06-002) is a 5 year permit that covers new and existing discharges of stormwater to waters of the United States from industrial activities as defined in 40 CFR Part 122.26(b)(14)(i-ix and xi).

The Clean Water Act provides that stormwater discharges associated with industrial activity from a point source (including discharges through a municipal separate storm sewer system) to waters of the United States are unlawful, unless authorized by a National Pollutant Discharge Elimination System (NPDES) permit. In New York, EPA has approved the state program which is enacted through the administration of the State Pollutant Discharge Elimination System (SPDES) program. Facilities must obtain permit coverage through either an individual industrial SPDES permit which address the stormwater discharges, obtain coverage under the SPDES Multi-Sector General Permit for Stormwater Discharges Associated with Industrial Activity or provide certification using the No Exposure Exclusion that industrial activities are not exposed to stormwater.

There are several major changes in this general permit compared to the previous general permit. The permit format has changed to include general requirements applicable to all facilities with permit coverage (Parts I through VII) and industry specific requirements (Part VIII) that have been tailored to address 31 different industrial activities. These industry specific requirements account for the increased size of the permit, but it is important to note that combining the general requirements in Parts I-VII and applicable industry specific requirements Part VIII will result in a general permit that is approximately the same size as the existing general permit (GP-98-03). It is also important to note that requirements are no longer based solely on the facility's primary Standard Industrial Code (SIC) or narrative description. If a facility has more than one industrial activity occurring on-site, those industrial activities are considered to be co-located and a facility must comply with the requirements for each specific industrial activity that is applicable at the facility. Other significant changes under this permit include:

- an expanded Notice of Intent or Termination (NOIT) form to provide the necessary level of information;
- a requirement to perform and document quarterly visual examinations of stormwater discharges;
- a requirement to perform and document annual dry weather flow inspections at stormwater discharge outfalls;
- a requirement that all facilities must complete, certify and submit an annual certification report;
- stormwater monitoring parameters for specific industrial facilities have been revised;
- benchmark monitoring cut-off concentrations have been added as guidance for comparison with sample results to identify potential stormwater contamination;

- the sampling frequency for analytical testing has been revised to once per year;
- sampling requirements have been revised to only require grab samples;
- additional monitoring requirements have been added for several EPA Point Source Categorical industries subject to effluent limitation guidelines for stormwater discharges (similar to coal pile run-off);
- a requirement that all analytical testing must be reported on specific forms and be submitted to the Department once per year with the annual certification form;
- permit authorization will begin 30 calendar days from receipt of the NOIT (no longer 2 days from postmark);
- revisions to requirements for facilities subject to EPCRA Section 313 reporting;
- new requirements for facilities with secondary containment areas for storage and transfer areas;
- a revised Best Management Practice (BMP) that salt piles will require enclosure or covers regardless of whether there is a discharge to surface or groundwater;
- a new sampling waiver referred to as the Alternative Certification of "Not Present" or "No Exposure";
- sectors AD and AE have been added to allow for permit coverage of stormwater discharges from industrial activities designated by the Department as needing a stormwater permit where coverage under a general permit would be more suitable than requiring an individual industrial SPDES permit; and
- in response to the types of industrial operations being conducted at mining and landfill facilities, sectors J, L & M can be used to authorize stormwater discharges from construction activities.

This general permit will expire on March 27, 2012.

## How to Get Copies


Copies of the general permit are available on the DEC website at:

<http://www.dec.state.ny.us/website/dow/mainpage.htm> or by calling the NYSDEC, Bureau of Water Permits, General Permits Section at (518) 402-8109. Copies of the Notice of Intent or Termination (NOIT) form or Annual Certification Report form are included in the appendices of the permit or on the DEC website.

## Who to Contact with Questions:

Questions regarding the content of the general permit can be directed to the following individual:

Bruce Terbush  
 NYSDEC, Division of Water  
 625 Broadway - 4<sup>th</sup> Floor  
 Albany, NY 12233-3505  
 (518) 402-8235  
 E-mail: [brterbus@gw.dec.state.ny.us](mailto:brterbus@gw.dec.state.ny.us)



**NEW YORK STATE DEPARTMENT OF ENVIRONMENTAL CONSERVATION**  
**SPDES MULTI-SECTOR GENERAL PERMIT**  
**FOR STORMWATER DISCHARGES ASSOCIATED WITH INDUSTRIAL ACTIVITY**

Permit No. GP-0-06-002

Issued Pursuant to Article 17, Titles 7, 8 and Article 70  
of the Environmental Conservation Law

Effective Date: March 28, 2007

Expiration Date: March 27, 2012

William R. Adriance  
Chief Permit Administrator

Address: NYSDEC, 625 Broadway  
Albany, NY 12233-1750

William R. Adriance  
Authorized Signature

Date: 12/27/2006



## PREFACE

The Clean Water Act (CWA)<sup>(1)</sup> provides that stormwater discharges associated with industrial activity from a point source<sup>(2)</sup> (including discharges through a municipal separate storm sewer system) to waters of the United States<sup>(3)</sup> are unlawful, unless authorized by a National Pollutant Discharge Elimination System (NPDES) permit. In New York, EPA has approved the state program which is enacted through the administration of the State Pollutant Discharge Elimination System (SPDES) program.

A discharger who is subject to the stormwater SPDES regulations may be eligible to obtain coverage under a general permit by submitting a Notice of Intent or Termination (NOIT) form to the address provided on the form. Blank NOIT forms are available by calling (518) 402-8109 or can be downloaded from the NYSDEC website at: [www.dec.state.ny.us/website/dow/mainpage.htm](http://www.dec.state.ny.us/website/dow/mainpage.htm). There are no application fee(s), but there is an annual regulatory fee which the Department will bill at a later time (normally towards the end of each summer).

There are several major changes from the previous permit that will affect permittees. Please be sure to review and understand the requirements that apply to your facility. The permit format has changed to include general requirements applicable to all facilities with permit coverage (Parts I through VII) and industry specific requirements in Part VIII which address 31 different industrial activities. These industry specific requirements account for the increased size of the permit, but it is important to note that combining the general requirements in Parts I-VII and applicable industry specific requirements in Part VIII will result in a general permit that is approximately the same size as the existing general permit (GP-98-03). It is also important to

<sup>1</sup> Also known as the Federal Water Pollution Control Act or Federal Water Pollution Control Act Amendments of 1972 (Pub.L. 92-500, as amended Pub. L. 92-217, Pub. L. 95-576, Pub. L. 96-483 and Pub. L. 97-117, 33 U.S.C. 1251 et seq.)

<sup>2</sup> "Point Source" means any discernible, confined, and discrete conveyance, including but not limited to, any pipe, ditch, channel, tunnel, conduit, well, discrete fissure, container, rolling stock, concentrated animal feeding operation, landfill leachate collection system, vessel or other floating craft from which pollutants are or may be discharged.

<sup>3</sup> "Waters of the United States" means:

- (a) All waters which are currently used, were used in the past, or may be susceptible to use in interstate or foreign commerce, including all waters which are subject to the ebb and flow of the tide;
- (b) All interstate waters, including interstate "wetlands";
- (c) All other waters such as interstate lakes, rivers, streams (including intermittent streams), mudflats, sandflats, wetlands, sloughs, prairie potholes, wet meadows, playa lakes, or natural ponds the use, degradation, or destruction of which would affect or could affect interstate or foreign commerce including any such waters:
  - (1) Which are or could be used by interstate or foreign travelers for recreational or other purposes; or
  - (2) From which fish or shellfish are or could be taken and sold in interstate or foreign commerce; or
  - (3) Which are used or could be used for industrial purposes by industries in interstate commerce;
- (d) All impoundments of waters otherwise defined as waters of the United States under this definition;
- (e) Tributaries of waters identified in paragraphs (a) through (d) of this definition;
- (f) The territorial sea; and
- (g) Wetlands adjacent to waters (other than waters that are themselves wetlands) identified in paragraphs (a) through (f) of this definition.

note that requirements are no longer based only on the primary Standard Industrial Code (SIC) or narrative description. If more than one industrial activity occurs at the facility, those industrial activities are considered to be co-located and the facility must comply with all of the applicable industrial requirements for those activities. Other significant changes under this permit include:

- an expanded Notice of Intent or Termination (NOIT) form to provide the necessary level of information;
- a requirement to perform quarterly visual inspections of stormwater discharges;
- a requirement to perform annual dry weather flow inspections at stormwater discharge outfalls;
- a requirement that all facilities must submit an annual certification report form;
- stormwater monitoring parameters for specific industrial facilities have been revised;
- sampling guidelines (referred to as benchmark monitoring cut-off concentrations) have been added to the monitoring requirements;
- the sampling frequency for analytical testing has been revised to once per year;
- sampling requirements have been revised to require only grab samples;
- additional monitoring requirements for several EPA Point Source Categorical industries subject to effluent limitation guidelines for stormwater discharges (similar to coal pile run-off);
- a requirement that all analytical testing must be reported on specific forms and be submitted to the Department once per year with the annual certification form;
- permit authorization will begin 30 calendar days from receipt of the NOIT (not 2 days from postmark);
- revisions to requirements for facilities subject to EPCRA Section 313 reporting;
- new requirements for facilities with secondary containment areas for storage and transfer areas;
- a revised Best Management Practice (BMP) that salt piles will require enclosure or covers regardless of whether there is a demonstrated discharge to surface or groundwater;

- a new sampling waiver referred to as the Alternative Certification of “Not Present” or “No Exposure”; and
- sectors AD and AE have been added to allow for permit coverage of stormwater discharges from industrial activities designated by the Department as needing a stormwater permit where coverage under a general permit would be more suitable than requiring an individual industrial SPDES permit.
- In response to the types of industrial operations being conducted at mining and landfill facilities, sectors J, L and M can be used to authorize stormwater discharges from construction activities.

Copies of the Notice of Intent or Termination and Annual Certification Report are included in the appendices of the permit.

Coverage under this general permit is available effective March 28, 2007 and will expire on March 27, 2012.

**SPDES Multi-Sector General Permit  
for Stormwater Discharges Associated with Industrial Activity  
except Construction Activity**

**Table of Contents**

**Part I. COVERAGE UNDER THIS PERMIT (Page 1)**

- A. Permit Area (Page 1)
- B. Maintaining Water Quality (Page 1)
- C. Eligibility (Page 2)
- D. Activities Which are Ineligible for Coverage under this General Permit (Page 7)
- E. How to Obtain Authorization Under this Permit (Page 7)
- F. Deadlines for Notification (Page 8)
- G. Interim Permit Coverage for Facilities Covered Under GP-98-03 (Page 8)
- H. Conditional Exclusion for No Exposure (Page 9)

**Part II. SPECIAL CONDITIONS (Page 10)**

- A. New Stormwater Discharges (Page 10)
- B. Releases of Hazardous Substances or Petroleum (Page 10)
- C. Impaired Waters (303(d) and TMDL) (Page 11)

**Part III. STORMWATER POLLUTION PREVENTION PLANS (Page 11)**

- A. Stormwater Pollution Plan Requirements (Page 11)
- B. Deadlines for SWPPP Preparation and Compliance (Page 12)
- C. Contents of the Plan (Page 12)
- D. Maintenance (Page 18)
- E. Non-stormwater Discharges (Page 18)
- F. Documentation of Permit Eligibility Related to Endangered Species (Page 19)
- G. Documentation of Permit Eligibility Related to Historic Places (Page 20)
- H. Copy of Permit Requirements (Page 20)
- I. Comprehensive Site Compliance Evaluation (Page 20)
- J. Signature and Plan Review (Page 22)
- K. Keeping SWPPPs Current (Page 22)
- L. Special Pollution Prevention Plan Requirements (Page 23)

**Part IV. MONITORING AND REPORTING REQUIREMENTS (Page 26)**

- A. Monitoring Requirements (Page 26)
- B. Reporting Monitoring Results and Annual Certification Reporting (Page 35)
- C. Retention of Monitoring Records (Page 36)

**Part V. STANDARD PERMIT CONDITIONS (Page 37)**

- A. Duty to Comply (Page 37)
- B. Continuation of the Expired General Permit (Page 38)
- C. Penalties for Violations of Permit Conditions (Page 38)
- D. Need to Halt or Reduce Activity Not a Defense (Page 38)
- E. Duty to Mitigate (Page 38)
- F. Duty to Provide Information (Page 38)
- G. Other Information (Page 38)
- H. Signatory Requirements (Page 38)
- I. Penalties for Falsification of Reports (Page 40)
- J. Penalties for Falsification of Monitoring Systems (Page 40)
- K. Oil and Hazardous Substance Liability (Page 40)
- L. Property Rights (Page 40)
- M. Severability (Page 40)
- N. Requiring an Individual Permit or an Alternative General Permit (Page 407)
- O. State/Environmental Laws (Page 41)
- P. Proper Operation and Maintenance (Page 41)
- Q. Inspection and Entry (Page 41)
- R. Permit Actions (Page 41)
- S. Definitions (Page 41)

**Part VI. REOPENER CLAUSE (Page 42)**

**Part VII. TERMINATION OF COVERAGE (Page 42)**

- A. Notice of Intent or Termination (NOIT) Form (Page 42)
- B. Addresses (Page 43)

**Part VIII. SECTOR SPECIFIC PERMIT REQUIREMENTS (Page 43)**

- A. Timber Products (Page VIII.A-1)
- B. Paper and Allied Products Manufacturing (Page VIII.B-1)
- C. Chemical and Allied Products Manufacturing (Page VIII.C-1)
- D. Asphalt Paving and Roofing Materials and Lubricant Manufacturers (Page VIII.D-1)
- E. Glass, Clay, Cement, Concrete, and Gypsum Products (Page VIII.E-1)
- F. Primary Metals (Page VIII.F-1)
- G. Metal Mining (Ore Mining and Dressing) (Page VIII.G-1)
- H. [Reserved]
- I. Oil and Gas Extraction and Refining (Page VIII.I-1)
- J. Mineral Mining and Dressing (Page VIII.J-1)
- K. Hazardous Waste Treatment, Storage, or Disposal Facilities (Page VIII.K-1)
- L. Landfills, Land Application Sites and Non-Compliant Landfills (Page VIII.L-1)
- M. Automobile Salvage Yards (Page VIII.M-1)
- N. Scrap Recycling and Waste Recycling Facilities (Page VIII.N-1)
- O. Steam Electric Generating Facilities (Page VIII.O-1)
- P. Land Transportation and Warehousing (Page VIII.P-1)
- Q. Water Transportation (Page VIII.Q-1)

**Part VIII. SECTOR SPECIFIC PERMIT REQUIREMENTS (continued)**

- R. Ship and Boat Building or Repair Yards (Page VIII.R-1)
- S. Air Transportation (Page VIII.S-1)
- T. Treatment Works (Page VIII.T-1)
- U. Food and Kindred Products (Page VIII.U-1)
- V. Textile Mills, Apparel, and Other Fabric Products (Page VIII.V-1)
- W. Furniture and Fixtures (Page VIII.W-1)
- X. Printing and Publishing (Page VIII.X-1)
- Y. Rubber, Miscellaneous Plastic Products, and Misc. Manufacturing (Page VIII.Y-1)
- Z. Leather Tanning and Finishing (Page VIII.Z-1)
- AA. Fabricated Metal Products (Page VIII.AA-1)
- AB. Transportation Equipment, Industrial or Commercial Machinery (Page VIII.AB-1)
- AC. Electronic, Electrical Equipment and Components, Photographic and Optical Goods (Page VIII.AC-1)
- AD. Non-classified Facilities/Stormwater Discharges Designated by the Department as Requiring Permit Coverage (Page VIII.AD-1)
- AE. Non-classified Facilities/Stormwater Discharges Designated by the Department as Requiring Permit Coverage for Department of Public Works and Highway Maintenance Facilities (Page VIII.AE-1)

**Appendix A - Definitions**

**Appendix B - Notice of Intent or Termination**

**Appendix C - Annual Certification Report**

**Appendix D - Example Quarterly Visual Monitoring Form**

**Appendix E - Discharge Monitoring Report**

**Appendix F - Additional Information for New Discharges**

**Appendix G - List of DEC Regional Offices**

## **Part I. COVERAGE UNDER THIS PERMIT**

**A. Permit Area** - This permit is intended to provide SPDES Permit coverage to facilities with stormwater discharges to waters of the United States from a point source that conduct industrial activities identified within 40 CFR Part 122.26(b)(14)(i) through (ix) and (xi), as well as other miscellaneous industrial activities designated by the Department on a case by case basis. This Permit covers all areas of New York State where New York State implements Section 402 of the CWA. Except as in compliance with this general permit or with a duly authorized individual permit from DEC, stormwater "discharges associated with industrial activity"<sup>(4)</sup> by any person shall be unlawful.

### **B. Maintaining Water Quality**

1. Under the terms and conditions of this permit, the permittee must develop and implement a Stormwater Pollution Prevention Plan (SWPPP) which identifies specific best management practices (BMPs) to be selected, installed, implemented and maintained at the facility to minimize the presence of pollutants in the stormwater discharges.
2. It shall be a violation of this general permit and the Environmental Conservation Law ("ECL") for any discharge authorized by this general permit to either cause or contribute to a violation of water quality standards as contained in Parts 700-705 of Title 6 of the Official Compilation of Codes, Rules and Regulations of the State of New York including, but not limited to:
  - a. There shall be no increase in turbidity that will cause a substantial visible contrast to natural conditions;
  - b. There shall be no suspended, colloidal and settleable solids from sewage, industrial wastes or other wastes that will cause deposition or impair the waters for their best usages; and
  - c. There shall be no residue from oil and floating substances attributable to sewage, industrial wastes or other wastes, nor visible oil film nor globules or grease.
3. If there is evidence indicating that the stormwater discharges authorized by this permit are causing, have the reasonable potential to cause, or are contributing to an excursion above an applicable water quality standard, the permittee must take appropriate corrective action and notify DEC of corrective actions taken. The Department may require the permittee to conduct follow-up monitoring or provide additional information, may require the permittee to include and implement appropriate controls in the SWPPP to correct the problem, may require the permittee to obtain an individual permit and/or may take appropriate enforcement action.

<sup>4</sup> A "discharge associated with industrial activity" covered under this general permit, includes those defined in 40 CFR Section 122.26(b)(14)(i) through (ix) and (xi).

C. **Eligibility** - The Permittee must maintain permit eligibility to discharge under this permit. Any discharges that are not compliant with the eligibility conditions of this permit are not authorized by the permit and the Permittee must either apply for a separate permit to cover those ineligible discharges or take steps necessary to make the discharge eligible for coverage.

1. **Facilities Covered** - Permit eligibility is limited to the discharge of stormwater associated with industrial activities defined in 40 CFR 122.26(b)(14)(i-ix and xi) which identifies categories of industrial activity based on Standard Industrial Classification (SIC) codes; industrial activity codes; or non-classified discharges covered under sectors AD and AE of this general permit which have been designated by the Department (via written notification) as needing a stormwater permit and determined to be suitable for coverage under this permit. These industrial activities have been organized into specific industrial sectors A through AE that are summarized in Table I-1. Reference to "sectors" in this permit (e.g., sector specific monitoring requirements, etc.) refer to these sectors.

a. **Co-located industrial activity** - If more than one industrial activity occurs at the facility which is described in Table I-1, those industrial activities are considered to be co-located. Stormwater discharges from co-located industrial activities are authorized by this permit, provided that the permittee complies with any and all additional sector specific requirements from Part VIII applicable to each industrial activity at the facility.

b. **Industrial sector determination** - If a permittee can provide adequate justification to the Department, and the Department agrees, the permittee may utilize another industrial sector which better reflects the industrial activities occurring at the facility than the industrial sector associated with the facility's SIC code. The Department reserves its right to classify such facilities in Sector AD instead.

c. **Municipally owned facilities** - An industrial facility that is owned and operated by a municipality covered by the Phase II Municipal Separate Storm Sewer (MS4) General Permit may not need coverage under a separate MSGP permit provided that the Phase II MS4 permit has implemented an O&M plan and the facility is operated in accordance with the six minimum stormwater control measures required by the Phase II permit.

2. **Discharges Covered** - Subject to compliance with terms and conditions of this permit, the following stormwater discharges are authorized:

a. Stormwater associated with industrial activity to waters of the United States, except ineligible stormwater discharges identified under Part I.D or under the sector specific requirements of Part VIII;



b. Stormwater discharges associated with industrial activity that are mixed with stormwater discharges from construction activities<sup>5</sup>, a different SPDES general permit or an individual SPDES permit provided that all discharges are in compliance with the terms and conditions of the various permits;

c. Stormwater discharges associated with industrial activity which are authorized by this permit may be combined with other sources of stormwater which are not classified as associated with industrial activity pursuant to 40 CFR 122.26(b)(14), provided that the discharge is in compliance with this permit and the discharges have not been designated by the Department as requiring an individual SPDES Permit;

d. Discharge subject to effluent guidelines listed in Tables IV-2 or IV-3 that also meet all other eligibility requirements of the permit;

e. Discharges designated by the Department as needing a stormwater permit and determined to be suitable for coverage under sectors AD & AE of this general permit; and

f. Non-stormwater discharges explicitly listed in Part I.C.3.

**3. Non-Stormwater Discharges** - The following non-stormwater discharges may be authorized by this permit provided that the non-stormwater component of the discharge is in compliance with Part III.E:

a. Discharges from fire fighting activities;

b. Fire hydrant flushings;

c. Potable water sources including waterline flushings;

d. Uncontaminated air conditioning or compressor condensate, and other uncontaminated condensate such as condensate from the surface of pressurized gas cylinders stored outside;

e. Irrigation drainage;

f. Landscape watering provided that all pesticides<sup>6</sup> and fertilizers have been applied in accordance with manufacturer's instructions;

<sup>5</sup> See definition of "discharges associated with industrial activity" for the construction category, 40 CFR Section 122.26(b)(14)(x).

<sup>6</sup> All pesticide, herbicide and fungicide products used at the facility must be registered with New York State and applied in accordance with the label directions. Any use contrary to the legal label is considered a violation of Federal and State Pesticide Law. Certification of pesticide applicators may be required. (See <http://www.dec.state.ny.us/website/dshn/pesticide/appman.htm>)

**TABLE I-1**  
**SECTORS OF INDUSTRIAL ACTIVITY COVERED BY THIS PERMIT**

SIC Code or Activity Code	Activity Represented
<b>Sector A: Timber Products</b>	
2411 .....	Log Storage and Handling (Wet deck storage areas are only authorized if no chemical additives are used in the spray water or applied to the logs).
2421 .....	General Sawmills and Planning Mills.
2426 .....	Hardwood Dimension and Flooring Mills.
2429 .....	Special Product Sawmills, Not Elsewhere Classified.
2431-2439 (except 2434 - see Sector W) .....	Millwork, Veneer, Plywood, and Structural Wood.
2441, 2448, 2449 .....	Wood Containers.
2451, 2452 .....	Wood Buildings and Mobile Homes.
2491 .....	Wood Preserving.
2493 .....	Reconstituted Wood Products.
2499 .....	Wood Products, Not Elsewhere Classified.
<b>Sector B: Paper and Allied Products</b>	
2611 .....	Pulp Mills.
2621 .....	Paper Mills.
2631 .....	Paperboard Mills.
2652-2657 .....	Paperboard Containers and Boxes.
2671-2679 .....	Converted Paper and Paperboard Products, Except Containers and Boxes.
<b>Sector C: Chemical and Allied Products</b>	
2812-2819 .....	Industrial Inorganic Chemicals.
2821-2824 .....	Plastics Materials and Synthetic Resins, Synthetic Rubber, Cellulosic and Other Manmade Fibers Except Glass.
2833-2836 .....	Medicinal Chemicals and Botanical Products; Pharmaceutical Preparations; In Vitro and In Vivo Diagnostic Substances; Biological Products, Except Diagnostic Substances.
2841-2844 .....	Soaps, Detergents, and Cleaning Preparations; Perfumes, Cosmetics, and Other Toilet Preparations.
2851 .....	Paints, Varnishes, Lacquers, Enamels, and Allied Products.
2861-2869 .....	Industrial Organic Chemicals.
2873-2879 .....	Agricultural Chemicals.
2891-2899 .....	Miscellaneous Chemical Products.
3952 (limited to list) .....	Inks and Paints, Including China Painting Enamels, India Ink, Drawing Ink, Platinum Paints for Burnt Wood or Leather Work, Paints for China Painting, Artist's Paints and Artist's Watercolors.
<b>Sector D: Asphalt Paving and Roofing Materials and Lubricants</b>	
2951, 2952 .....	Asphalt Paving and Roofing Materials.
2992, 2999 .....	Miscellaneous Products of Petroleum and Coal.
<b>Sector E: Glass Clay, Cement, Concrete, and Gypsum Products</b>	
3211 .....	Flat Glass.
3221, 3229 .....	Glass and Glassware, Pressed or Blown.
3231 .....	Glass Products Made of Purchased Glass.
3241 .....	Hydraulic Cement.
3251-3259 .....	Structural Clay Products.
3261-3269 .....	Pottery and Related Products.
3271-3275 .....	Concrete, Gypsum and Plaster Products.
3281 .....	Cut Stone and Stone Products.
3291-3299 .....	Abrasive, Asbestos, and Miscellaneous Non-metallic Mineral Products.
<b>Sector F: Primary Metals</b>	
3312-3317 .....	Steel Works, Blast Furnaces, and Rolling and Finishing Mills.
3321-3325 .....	Iron and Steel Foundries.
3331-3339 .....	Primary Smelting and Refining of Nonferrous Metals.
3341 .....	Secondary Smelting and Refining of Nonferrous Metals.
3351-3357 .....	Rolling, Drawing, and Extruding of Nonferrous Metals.
3363-3369 .....	Nonferrous Foundries (Castings).
3398, 3399 .....	Miscellaneous Primary Metal Products.

<b>Sector G: Metal Mining (Ore Mining and Dressing)</b>	
1011 .....	Iron Ores.
1021 .....	Copper Ores.
1031 .....	Lead and Zinc Ores.
1041, 1044 .....	Gold and Silver Ores.
1061 .....	Ferroalloy Ores, Except Vanadium.
1081 .....	Metal Mining Services.
1094, 1099 .....	Miscellaneous Metal Ores.
<b>Sector I: [Reserved]</b>	
<b>Sector I: Oil and Gas Extraction and Refining</b>	
1311 .....	Crude Petroleum and Natural Gas.
1321 .....	Natural Gas Liquids.
1381-1389 .....	Oil and Gas Field Services.
2911 .....	Petroleum Refineries.
<b>Sector J: Mineral Mining and Dressing</b>	
1411 .....	Dimension Stone.
1422-1429 .....	Crushed and Broken Stone, Including Rip Rap.
1442, 1446 .....	Sand and Gravel
1455, 1459 .....	Clay, Ceramic, and Refractory Materials.
1474-1479 .....	Chemical and Fertilizer Mineral Mining.
1481 .....	Nonmetallic Minerals Services, Except Fuels.
1499 .....	Miscellaneous Nonmetallic Minerals, Except Fuels.
<b>Sector K: Hazardous Waste Treatment, Storage, or Disposal Facilities</b>	
HZ .....	Hazardous Waste Treatment Storage or Disposal.
<b>Sector L: Landfills and Land Application Sites</b>	
LF .....	Landfills, Land Application Sites, and Non-Compliant Landfills.
<b>Sector M: Automobile Salvage Yards</b>	
5015 .....	Automobile Salvage Yards.
<b>Sector N: Scrap Recycling Facilities</b>	
5093 .....	Scrap Recycling Facilities.
4499 (limited to list) .....	Dismantling Ships, Marine Salvaging, and Marine Wrecking - Ships For Scrap
<b>Sector O: Steam Electric Generating Facilities</b>	
SE .....	Steam Electric Generating Facilities.
<b>Sector P: Land Transportation and Warehousing</b>	
4011, 4013 .....	Railroad Transportation.
4111-4173 .....	Local and Highway Passenger Transportation.
4212-4231 .....	Motor Freight Transportation and Warehousing.
4311 .....	United States Postal Service.
5171 .....	Petroleum Bulk Stations and Terminals.
<b>Sector Q: Water Transportation</b>	
4412-4499 (except 4499 facilities as specified in Sector N)	Water Transportation.
<b>Sector R: Ship and Boat Building or Repairing Yards</b>	
3731, 3732 .....	Ship and Boat Building or Repairing Yards.
<b>Sector S: Air Transportation</b>	
4512-4581 .....	Air Transportation Facilities.
<b>Sector T: Treatment Works</b>	
TW .....	Treatment Works.
<b>Sector U: Food and Kindred Products</b>	
2011-2015 .....	Meat Products.
2021-2026 .....	Dairy Products.
2032-2038 .....	Canned, Frozen and Preserved Fruits, Vegetables and Food Specialties.
2041-2048 .....	Grain Mill Products.
2051-2053 .....	Bakery Products.
2061-2068 .....	Sugar and Confectionery Products.
2074-2079 .....	Fats and Oils.
2082-2087 .....	Beverages.
2091-2099 .....	Miscellaneous Food Preparations and Kindred Products.
2111-2141 .....	Tobacco Products.

<b>Sector V: Textile Mills, Apparel, and Other Fabric Product Manufacturing, Leather and Leather Products</b>	
2211-2299 .....	Textile Mill Products.
2311-2399 .....	Apparel and Other Finished Products Made From Fabrics and Similar Materials.
3131-3199 (except 3111 - see ..... Sector Z)	Leather and Leather Products, except Leather Tanning and Finishing.
<b>Sector W: Furniture and Fixtures</b>	
2434 .....	Wood Kitchen Cabinets.
2511-2599 .....	Furniture and Fixtures.
<b>Sector X: Printing and Publishing</b>	
2711-2796 .....	Printing, Publishing, and Allied Industries.
<b>Sector Y: Rubber, Miscellaneous Plastic Products, and Miscellaneous Manufacturing Industries.</b>	
3011 .....	Tires and Inner Tubes.
3021 .....	Rubber and Plastics Footwear.
3052, 3053 .....	Gaskets, Packing, and Sealing Devices and Rubber and Plastics Hose and Belting.
3061, 3069 .....	Fabricated Rubber Products, Not Elsewhere Classified.
3081-3089 .....	Miscellaneous Plastics Products.
3931 .....	Musical Instruments.
3942-3949 .....	Dolls, Toys, Games and Sporting and Athletic Goods.
3951-3955 (except 3952 facilities .. as specified in Sector C).	Pens, Pencils, and Other Artists' Materials.
3961, 3965 .....	Costume Jewelry, Costume Novelties, Buttons, and Miscellaneous Notions, Except Precious Metal.
3991-3999 .....	Miscellaneous Manufacturing Industries.
<b>Sector Z: Leather Tanning and Finishing</b>	
3111 .....	Leather Tanning, Currying and Finishing.
<b>Sector AA: Fabricated Metal Products</b>	
3411-3499 .....	Fabricated Metal Products, Except Machinery and Transportation Equipment.
3911-3915 .....	Jewelry, Silverware, and Plated Ware.
<b>Sector AB: Transportation Equipment, Industrial or Commercial Machinery</b>	
3511-3599 (except 3571-3579 - .... see Sector AC)	Industrial and Commercial Machinery (Except Computer and Office Equipment).
3711-3799 (except 3731, 3732 - ... see Sector R)	Transportation Equipment (Except Ship and Boat Building and Repairing).
<b>Sector AC: Electronic, Electrical, Photographic, and Optical Goods</b>	
3571-3579 .....	Computer and Office Equipment.
3612-3699 .....	Electronic, Electrical Equipment and Components, Except Computer Equipment.
3812-3873 .....	Measuring, Analyzing and Controlling Instrument; Photographic and Optical Goods.
<b>Sectors AD &amp; AE: Non-Classified Facilities/Stormwater Discharges Designated By the Department As Requiring Permits</b>	
N/A.....	Other Stormwater Discharges Designated By the Department As Needing a Permit or Any Facility Discharging Stormwater Associated With Industrial Activity Not Described By Any of Sectors A-AC. Note: Facilities may not elect to be covered under Sector AD & AE. Only the Department may assign a facility to Sector AD & AE.

g. Routine external building washdown which does not use detergents;

h. Pavement wash waters where detergents are not used and where spills or leaks of toxic or hazardous materials have not occurred (unless all spilled material has been removed);

i. Uncontaminated ground water or spring water;

k. Foundation or footing drains where flows are not contaminated with process

materials such as solvents; and

1. Incidental windblown mist from cooling towers that collect on rooftops or adjacent portions of the facility, but not intentional discharges from cooling tower (e.g.; "piped" cooling tower blowdown or drains).

**D. Activities Which are Ineligible for Coverage under this General Permit** - The following discharges from industrial activity are not authorized by this permit:

1. Discharges from industrial activity that are mixed with sources of non-stormwater other than those expressly authorized under either this permit or a different SPDES permit.
2. Discharges from industrial activity that are subject to an existing SPDES individual or general permit located at a facility where a SPDES permit has been terminated or denied; or which are issued an individual or alternative general permit;
3. Discharges from industrial activity which are subject to an existing effluent limitation guideline addressing stormwater which are not included in Table IV-2 or IV-3 (or a combination of stormwater and process water);
4. Discharges from industrial activity from construction activities, except stormwater discharges from portions of a construction site that can be classified as an industrial activity under 40 CFR 122.26(b)(14)(i) through (ix) or (xi) (including stormwater discharges from mobile asphalt plants and mobile concrete plants);
5. Discharges from industrial activity that adversely affect a listed or proposed to be listed endangered or threatened species or its critical habitat;
6. Discharges from industrial activity that adversely affect a property that is listed or is eligible for listing on the National Register of Historic Places; and
7. Discharges occurring on federal lands from industrial activity from either inactive mining, inactive landfills, or inactive oil and gas operations where an owner or operator cannot be identified.

**E. How to Obtain Authorization Under this Permit**

1. **Eligibility** - A discharger of stormwater associated with industrial activity may be authorized under this permit only if the discharge from the facility meets the eligibility requirements in Part I.C. of this permit.
2. **Stormwater Pollution Prevention Plan** - A discharger of stormwater associated with industrial activity may be authorized under this permit only if the owner or operator has developed and implemented a Stormwater Pollution Prevention Plan (SWPPP) according to the requirements in Part III. and applicable sections of Part VIII. of this permit.

3. **Notice of Intent or Termination** - A discharger of stormwater associated with industrial activity may be authorized under this permit only if the owner or operator has submitted a complete Notice of Intent or Termination (NOIT) form approved and provided by the Department <sup>(7)</sup> (or photocopy thereof) to:

Industrial Stormwater General Permit Coordinator  
NYSDEC, Bureau of Water Permits  
625 Broadway  
Albany, New York 12233-3505

- a. Unless notified by the Department to the contrary, owner or operators<sup>(8)</sup> who submit an NOIT in accordance with the requirements of this permit are authorized to discharge storm water under the terms and conditions of this permit 30 calendar days after the date that the NOIT is received. An exception to this is for transfers of ownership for which permits are effective once the conditions of I.F.3 and VII are met.
- b. The Department may deny coverage under this permit and require submittal of an application for an individual SPDES permit based on a review of the NOIT or other information pursuant to Part V.N.

**F. Deadlines for Notification**

1. Owners or operators of existing facilities that have permit coverage under GP-98-03 shall submit a complete NOIT in accordance with I.G.
2. Owners or operators of facilities who intend to obtain coverage under this general permit shall submit a complete NOIT in accordance with the requirements of this Part at least 30 calendar days prior to the commencement of the industrial activity at the facility;
3. Where the owner or operator of a facility with stormwater discharge associated with industrial activity which is covered by this permit changes, both the previous and new owners or operators of the facility must submit NOITs in accordance with Part VII. (Termination of Coverage); and

**G. Interim Permit Coverage for Facilities Covered Under GP-98-03** - Facilities that have coverage under the SPDES General Permit for Stormwater Discharges Associated with Industrial Activity (GP-98-03) may be eligible for continued permit coverage on an interim basis as follows:

<sup>7</sup> A copy of the NOIT form is provided in Appendix B of this permit.

<sup>8</sup> For the purposes of this permit, the term "owner or operator" means owner or operator of any facility or activity subject to regulation under 6 NYCRR Part 750. In accordance with 6 NYCRR Part 750-1.6(a) When a facility or activity is owned by one person but is operated by another person, it is the operator's duty to obtain a permit.

1. For facilities with coverage under the SPDES General Permit for Stormwater Discharges Associated with Industrial Activities (GP-98-03) as of the date this permit becomes effective, authorization will be automatically continued on an interim basis for up to one hundred twenty (120) calendar days. Please note that submission of a completed NOIT is necessary within ninety (90) calendar days from the date this permit becomes effective as authorization will occur 30 calendar days after receipt of a completed NOIT. Interim coverage will terminate once a complete NOIT has been submitted and coverage is granted;

2. If a facility is covered by the SPDES General Permit for Stormwater Discharges Associated with Industrial Activity (GP-98-03), but cannot meet (or the facility cannot immediately determine if they meet) the eligibility requirements of this permit, the permittee may be granted interim authorization until eligibility is determined by DEC or an individual SPDES Permit or alternative permit is issued under the following schedule. Upon submission of the NOIT, the applicant shall notify the Department that eligibility for coverage has not yet been determined. Within 90 days from receipt of the NOIT, the Department shall notify the applicant whether application for an individual permit, or coverage under an alternate SPDES permit, is necessary. The applicant must submit an application for an individual permit or an alternate SPDES permit.

3. Interim Coverage Permit Requirements - To obtain interim coverage status, a facility must:

- a. Submit a complete NOIT within ninety (90) calendar days from the date this permit becomes effective;
- b. Comply with the terms and conditions of the SPDES General Permit for Stormwater Discharges Associated with Industrial Activity (GP-98-03); and
- c. Update the facility's SWPPP to comply with the requirements of this permit within 150 days after the effective date of this permit.

#### **H. Conditional Exclusion for No Exposure**

1. Facilities may qualify for a "Conditional Exclusion for No Exposure" where industrial activities and materials are completely sheltered from exposure to rain, snow, snowmelt and/or runoff. Facilities qualifying for this exclusion are not required to obtain a general permit for stormwater discharges associated with industrial activity. This exclusion is available on a facility-wide basis only and is not applicable to individual outfalls. To obtain the conditional no exposure exclusion, the owner or operator must submit a certification to the Department attesting to the condition of "no exposure". This certification must be completed and submitted once every 5 years and is non-transferable. Facilities must maintain the condition of no exposure. If changes at a facility result in

industrial activities or materials becoming exposed, the no exposure exclusion ceases to apply. Owners or operators who certified that their facilities qualify for the conditional no exposure exclusion may, nonetheless, be required by the Department to obtain permit coverage, based on a determination that stormwater discharges are likely to have an adverse impact on water quality. More information regarding the Conditional Exclusion for No Exposure is available at:

<http://www.dec.state.ny.us/website/dow/noexpexplanation.html>

## **Part II. SPECIAL CONDITIONS**

**A. New Stormwater Discharges** - New stormwater discharges associated with industrial activity which require any other Uniform Procedures Act permits (Environmental Conservation Law, 6 NYCRR Part 621) cannot be covered under this permit until the other required permits are obtained (see Appendix F). Upon satisfying the State Environmental Quality Review Act (SEQRA) requirements and obtaining the necessary permits, the applicant may submit a NOIT to obtain coverage under this general permit (see Appendix F). In order to facilitate the Department's review of a multi-permitted project, an applicant should submit, at a minimum, a copy of the SWPPP which contains the information specified in Appendix F. This information will assist the Department in determining whether or not coverage under this general permit or another SPDES permit is the more appropriate option.

### **B. Releases of Hazardous Substances or Petroleum**

1. This permit does not authorize the discharge of hazardous substances (as listed in 6 NYCRR Part 597) or petroleum. The discharge of hazardous substances or petroleum in the stormwater discharge(s) from the facility shall be prevented or minimized in accordance with the stormwater pollution prevention plan for the facility. Any spill of petroleum must be reported in accordance with 6 NYCRR Part 613.8. Any spill of a hazardous substance must be reported in accordance with 6 NYCRR Part 595.3.

Notification must be reported to the DEC hotline (1-800- 457-7362) within two hours of the release. Additional notifications may be required for Federal level notification through the National Response Center (NRC) at 1-800-424-8802.

2. Where a release enters a municipal separate storm sewer system (MS4), the permittee shall also notify the owner of the MS4 within 2 hours of the time at which facility staff becomes aware of the release; and

3. Following any release incident, the permittee must evaluate the facility's stormwater pollution prevention plan to identify measures preventing reoccurrence and to improve the emergency response to such releases. The plan must be modified where appropriate.



### **C. Impaired Waters (303(d) and TMDL)**<sup>9</sup>

1. **303(d) Listed Waters** - If stormwater discharges to a 303(d) listed water, the Permittee must, by modification and application of its SWPPP, ensure no increase of the listed pollutant of concern to the 303(d) listed water. The 303(d) list is updated approximately every two years and is available on the Department's website at: [www.dec.state.ny.us/website/dow/303dcalm.pdf](http://www.dec.state.ny.us/website/dow/303dcalm.pdf).

2. **Total Maximum Daily Load (TMDL) Strategy** - If a TMDL has been approved by EPA for any waterbody or watershed into which the facility discharges, the Permittee must, within two calendar months of notification from the Department, review the applicable TMDL to see if the facility meets the requirements for control of stormwater discharges. If a facility is not meeting the TMDL stormwater allocations for the pollutant of concern it must, within 8 months of the above noted notification from the Department, modify its SWPPP to ensure that reduction of the pollutant of concern specified in the TMDL is achieved. The Department may grant additional time beyond the 8 months after notification to comply with the storm water TMDL reductions if the permittee demonstrates to the satisfaction of Department that this additional time is necessary.

### **Part III. STORMWATER POLLUTION PREVENTION PLANS**

**A. Stormwater Pollution Prevention Plan Requirements** - A stormwater pollution prevention plan (SWPPP) shall be developed and implemented by the owner or operator for each facility covered by this permit. SWPPPs shall be prepared in accordance with good engineering practices and in accordance with the factors outlined in 40 CFR 125.3(d)(2) or (3) as appropriate. This plan does not necessarily have to be developed or certified by a licensed Professional Engineer. The SWPPP shall identify potential sources of pollution which may reasonably be expected to affect the quality of stormwater discharges associated with industrial activity from the facility. In addition, the plan shall describe and ensure the implementation of practices which are to be used to reduce the pollutants in stormwater discharges associated with industrial activity at the facility and to assure compliance with the terms and conditions of this permit. Facilities must implement the provisions of the SWPPP required under this Part as a condition of this permit.

The SWPPP requirements of this general permit may be fulfilled by incorporating by reference other plans or documents such as an Erosion and Sediment Control (ESC) plan, a Mined Land Use Plan, a spill prevention control and countermeasure (SPCC) plan developed

<sup>9</sup> Section 303(d) of the federal Clean Water Act requires the Department to periodically to prepare a list of all surface waters in the state for which beneficial uses of the water – such as for drinking, recreation, aquatic habitat, and industrial use – are impaired by pollutants. These are water quality-limited estuaries, lakes, and streams that fall short of state surface water quality standards, and are not expected to improve within the next two years.

Waters placed on the 303(d) list require the preparation of Total Maximum Daily Loads (TMDLs), a key tool in the work to clean up polluted waters. TMDLs identify the maximum amount of a pollutant to be allowed to be released into a waterbody so as not to impair uses of the water. TMDLs allocate that amount among various sources. In addition, even before a TMDL is completed, the inclusion of a water on the 303(d) list can reduce the amount of pollutants allowed to be released under permits issued by the Department.

for the facility or best management practices (BMP) programs otherwise required for the facility provided that the incorporated plan meets or exceeds the plan requirements of Part III.C (Contents of the Plan). All plans incorporated by reference into the SWPPP become enforceable under this permit; however, this enforcement is limited only to those aspects of these other plans that are specifically referenced to provide information or practices required for the SWPPP.

EPA has developed guidance documents entitled, Stormwater Management for Industrial Activities: Developing Pollution Prevention Plans and Best Management Practices and Stormwater Management for Industrial Activities: Summary Guidance on Developing Pollution Prevention Plans and Best Management Practices to assist facilities in developing SWPPPs. These guidance documents are available at EPA's website at the following address: <http://cfpub.epa.gov/npdes/stormwater/swppp-msgp.cfm>

**B. Deadlines for Preparation and Compliance**

1. The SWPPP shall be prepared and provide for compliance with the terms of this permit on or before the date of submission of an NOIT to be covered under this permit (except as provided in Part I.G.3.c.); and
2. Upon showing of good cause, the Department may establish a later date in writing for preparing and compliance with the SWPPP for a stormwater discharge associated with industrial activity that submits an NOIT in accordance with Part I.F.

**C. Contents of the Plan** - The contents of the SWPPP shall comply with the requirements listed below and those in the appropriate sectors of Part VIII. These requirements are cumulative. If a facility has co-located activities that are covered in more than one sector of Part VIII, that facility's SWPPP must comply with the requirements listed in all applicable sectors. The following requirements are applicable to all SWPPPs developed under this general permit. The plan shall include, at a minimum, the following items:

1. **Pollution Prevention Team** - The plan shall identify the staff individuals (by name or title) that comprise the facility's stormwater pollution prevention team. The pollution prevention team is responsible for assisting the facility or plant manager in developing, implementing, maintaining, and revising the facility's SWPPP. Responsibilities of each staff individual on the team must be listed. The activities and responsibilities of the team shall address all aspects of the facility's SWPPP.
2. **Site Description** - The SWPPP shall include the following:
  - a. **Activities at the facility** - A description of the nature of the industrial activity(ies) at the facility.
  - b. **General location map** - A general location map (e.g., USGS quadrangle or other map) with enough detail to identify the location of the facility and the receiving waters within one mile of the facility.

c. Site map - A site map identifying the following:

- (1) Directions of stormwater flow (e.g., use arrows to show which ways stormwater will flow);
- (2) Locations of all existing structural BMPs;
- (3) Locations of all surface water bodies;
- (4) Locations of potential pollutant sources identified under Part III.C.3 and where significant materials are exposed to precipitation;
- (5) Locations where major spills or leaks identified under Part III.C.4 have occurred;
- (6) Locations of the following activities where such activities are exposed to precipitation: fueling stations; vehicle and equipment maintenance and/or cleaning areas; loading/unloading areas; locations used for the treatment, storage or disposal of wastes; and liquid storage tanks;
- (7) Locations of stormwater outfalls and an approximate outline of the area draining to each outfall or sufficient density of flow arrows to show the drainage area outline;
- (8) Location and description of non-stormwater discharges, including but not limited to those listed in Part I.C.3;
- (9) Locations of stormwater flows with significant potential for causing erosion;
- (10) Locations of the following activities where such activities are exposed to precipitation: processing and storage areas; access roads, rail cars and tracks; the location of transfer of substance in bulk; and machinery; and
- (11) Location and source of runoff from adjacent property containing significant quantities of pollutants of concern to the facility (the permittee may include an evaluation of how the quality of the stormwater running onto the facility impacts the facility's stormwater discharges).

d. Receiving waters - The name of the nearest receiving water(s), including intermittent streams and the areal extent and description of wetlands (mapped and federally regulated wetlands) that may receive discharges from the facility.

e. Municipal separate storm sewer systems - If stormwater is discharged to a municipal separate storm sewer systems (MS4), the SWPPP must identify the MS4 operator and the receiving water to which the MS4 discharges.

f. Other SPDES permitted discharges - The SWPPP must describe any discharges that are currently covered by another SPDES permit at the facility (e.g., process wastewater, sanitary wastewater, non-contact cooling water, etc.).

g. Impervious surface estimate - Provide an estimate of the percent imperviousness of your site:

$$\frac{(\text{Area of Roofs} + \text{Area of Paved and Other Impervious Surfaces})}{\text{Total Area of Facility}} \times 100$$

3. **Summary of Potential Pollutant Sources** - The plan shall identify each separate area at the facility where industrial materials or activities are exposed to stormwater. Industrial materials or activities include, but are not limited to material handling equipment or activities, industrial machinery, raw materials, intermediate products, byproducts, final products, or waste products. Material handling activities include the storage, loading and unloading, transportation, or conveyance of any raw material, intermediate product, final product or waste product. For each separate area identified, the description must include:

a. Activities in area - A list of the activities (e.g., material storage, equipment fueling and cleaning, cutting steel beams); and

b. Pollutants - A list of the associated pollutant(s) or pollutant parameter(s) (e.g., crankcase oil, iron, biochemical oxygen demand, pH, etc.) for each activity. The pollutant list must include all significant materials that have been handled, treated, stored or disposed in a manner to allow exposure to stormwater between the time of three years before being covered under this permit and the present.

c. Potential for presence in stormwater - For each area of the facility that generates stormwater discharges associated with industrial activity with a reasonable potential to contaminate stormwater, a prediction of the direction of flow, and an identification of the types of pollutants which are likely to be present in stormwater discharges associated with industrial activity. Factors to consider include the toxicity of chemicals; quantity of chemicals used, produced or discharged; the likelihood of contact with stormwater; and history of reportable leaks or spills of toxic or hazardous pollutants.

4. **Spills and Releases** - The SWPPP must clearly identify areas where potential spills or releases can contribute to pollutants in stormwater discharges and their accompanying drainage points. For areas that are exposed to precipitation or that otherwise drain to a stormwater conveyance at the facility to be covered under this permit, the plan must include a list of reportable spills or releases<sup>(10)</sup> of petroleum and hazardous substances or other pollutants that may adversely effect water quality that occurred during the three-year period prior to the date of the submission of a NOIT. The list must be updated if

<sup>10</sup> This may also include releases of petroleum or hazardous substances that are not in excess of reporting quantities but which may still cause or contribute to significant water quality impairment. For example, the reportable quantity for ammonia is listed to be 100 pounds and releases well below this threshold will cause water quality impairment and must be addressed.

reportable spills or releases occur in exposed areas of the facility during the term of the permit. This permit does not relieve the Permittee of any reporting or other requirements related to spills or other releases of petroleum or hazardous substances.

5. **Sampling Data** - The plan must include a summary of existing stormwater discharge sampling data taken at the facility, and must also include a summary of all stormwater sampling data collected during the term of this permit.

6. **Stormwater Controls** - The SWPPP shall include a description of stormwater management controls appropriate for the facility. The description of controls shall address the following minimum components:

a. **Description of existing and planned BMPs** - The plan shall describe the type and location of existing nonstructural and structural best management practices (BMPs) selected for each of the areas where industrial materials or activities are exposed to stormwater. All the areas identified in Part III.C.3 (summary of potential pollutant sources) should have a BMP(s) identified for the areas discharges. For areas where BMPs are not currently in place, include a description of appropriate BMPs that will be used to control pollutants in stormwater discharges. Selection of BMPs should take into consideration:

- (1) The quantity and nature of the pollutants, and their potential to impact the water quality of receiving waters;
- (2) Opportunities to combine the dual purposes of water quality protection and local flood control benefits, including physical impacts of high flows on streams (e.g., bank erosion, impairment of aquatic habitat, etc.);
- (3) Opportunities to offset the impact of impervious areas of the facility on ground water recharge and base flows in local streams, taking into account the potential for ground water contamination.

b. **BMP types to be considered** - The permittee must consider the following types of structural, nonstructural and other BMPs for implementation at the facility. The SWPPP shall describe how each BMP is, or will be, implemented. If this requirement was fulfilled with the area-specific BMPs identified under Part III.C.6.a., then the previous description is sufficient. However, many of the following BMPs may be more generalized or non-site-specific and therefore not previously considered. If the permittee determines that any of these BMPs are not appropriate for the facility, an explanation of why they are not appropriate shall be included in the plan. The BMP examples listed below are not intended to be an exclusive list of BMPs that may be used. The permittee is encouraged to keep abreast of new BMPs or new applications of existing BMPs to find the most cost effective means of permit compliance for the

facility. If BMPs are being used or planned at the facility that are not listed here (e.g., replacing a chemical with a less toxic alternative, adopting a new or innovative BMP, etc.), descriptions of them shall be included in this section of the SWPPP.

(1) Nonstructural BMPs

(a) Good housekeeping - The permittee must keep all exposed areas of the facility in a clean, orderly manner where such exposed areas could contribute pollutants to stormwater discharges. Common problem areas include around trash containers, storage areas and loading docks. Measures must also include a schedule for regular pickup and disposal of garbage and waste materials; routine inspections for leaks and conditions of drums, tanks and containers.

(b) Minimizing exposure - Where practicable, industrial materials and activities should be protected by a storm-resistant shelter to prevent exposure to rain, snow, snowmelt, or runoff.

Note: Eliminating exposure at all industrial areas may make the facility eligible for the "Conditional Exclusion for No Exposure" provision, thereby eliminating the need to have a permit (See Part I.H.).

(c) Preventive maintenance - The permittee must have a preventive maintenance program that includes timely inspection and maintenance of stormwater management devices (e.g., cleaning oil/water separators, catch basins), as well as inspection, testing, maintenance and repairing of facility equipment and systems to avoid breakdowns or failures that could result in discharges of pollutants to surface waters.

(d) Spill prevention and response procedures - The plan must describe the procedures that will be followed for cleaning up spills or leaks. The procedures and necessary spill response equipment must be made available to those employees who may cause or detect a spill or leak. Where appropriate, the plan must include an explanation of existing or planned material handling procedures, storage requirements, secondary containment, and equipment (e.g., diversion valves), that are intended to minimize spills or leaks at the facility. Measures for cleaning up spills or leaks must be consistent with applicable petroleum bulk storage, chemical bulk storage or hazardous waste management regulations at 6 NYCRR Parts 595-599, 612-614 and 370-373.

(e) Routine facility inspections - In addition to or as part of the comprehensive site evaluation required under Part III.I, qualified facility personnel (trained in accordance with condition f below) must inspect all areas of the facility where industrial materials or activities are exposed to stormwater. The inspections must include an evaluation of the existing stormwater BMPs. The inspection frequency shall be specified in the plan based upon the frequency identified under the SWPPP requirements for your specific industrial sector. If an inspection frequency is not indicated under the industrial sector, one should be

established based upon a consideration of the level of industrial activity at the facility. Quarterly inspections are suggested as a minimum frequency for those that don't have a frequency set for the specific industrial sectors. Any deficiencies in the implementation of the SWPPP must be corrected as soon as practicable, but not later than within 14 days of the inspection for items that can be readily resolved. More complicated maintenance or repairs shall be performed in accordance with the timeframes described under Sections III.D - Maintenance or III.I.2 - Follow-up Actions. The results of the inspections must be documented in the SWPPP, along with any corrective actions that were taken in response to any deficiencies or opportunities for improvement that were identified.

(f) Employee training - The SWPPP must describe the stormwater employee training program for the facility. The description should include the topics to be covered, such as spill response, good housekeeping, material management practices, and must identify periodic dates for such training (e.g., annually, every six months during the months of July and January). Employee training must be provided for all employees who work in areas where industrial materials or activities are exposed to stormwater, and for employees who are responsible for implementing activities identified in the SWPPP (e.g., inspectors, sampling personnel, maintenance people). The training should inform employees of the components and goals of the SWPPP.

## (2) Structural BMPs

(a) Sediment and erosion control - The plan shall identify areas at the facility which, due to topography, land disturbance (e.g., construction) or other factors, have potential for significant soil erosion. The plan must identify structural, vegetative, and/or stabilization BMPs that will be implemented to limit erosion. The Department has developed a document entitled, New York Standards and Specifications for Erosion and Sediment Control to assist in the design and selection of appropriate controls. This document is available at: <http://www.dec.state.ny.us/website/dow/toolbox/techstan.html>

(b) Management of runoff - The plan shall describe the traditional stormwater management practices (permanent structural BMPs other than those that control the generation or source(s) of pollutants) that currently exist or that are planned for the facility. These types of BMPs are typically used to divert, infiltrate, reuse, or otherwise reduce pollutants in stormwater discharges from the site. The plan shall provide that all measures that the permittee determines to be reasonable and appropriate, or are required by a state or local authority, shall be implemented and maintained. Factors for the permittee to consider when selecting appropriate BMPs should include:

- (i) The industrial materials and activities that are exposed to stormwater, and the associated pollutant potential of those materials and activities; and

(ii) The beneficial and potential detrimental effects on surface water quality, ground water quality, receiving water base flow (dry weather stream flow), and physical integrity of receiving waters. Structural measures should be placed on upland soils, avoiding wetlands and floodplains, if possible. Structural BMPs may require a separate permit under section 404 of the CWA before installation begins.

(c) Example BMPs - BMPs that could be used include but are not limited to: stormwater detention structures (including wet ponds); stormwater retention structures; flow attenuation by use of open vegetated swales and natural depressions; infiltration of runoff on-site; and sequential systems (which combine several practices).

(d) Other Controls - No solid materials, including floating debris, may be discharged to waters of the United States, except as authorized by a permit issued under section 404 of the CWA. Off-site vehicle tracking of raw, final, or waste materials or sediments, and the generation of dust must be minimized. Tracking or blowing of raw, final, or waste materials from areas of no exposure to exposed areas must be minimized. Velocity dissipation devices (or equivalent measures) must be placed at discharge locations and along the length of any outfall channel if they are necessary to provide a nonerosive flow velocity from the structure to a water course.

D. Maintenance - All BMPs identified in the SWPPP must be maintained in effective operating condition. If site inspections required by Part III.C.6.b(1)(e) or Part III.I. identify BMPs that are not operating effectively, maintenance must be performed before the next anticipated storm event, or as necessary to maintain the continued effectiveness of stormwater controls. If maintenance prior to the next anticipated storm event is impracticable, maintenance must be scheduled and accomplished as soon as practicable, but not more than 12 weeks after completion of the routine facility inspection or the comprehensive site evaluation, unless permission for a later date is granted in writing by the Department. In the case of nonstructural BMPs, the effectiveness of the BMP must be maintained by appropriate means (e.g., spill response supplies available and personnel trained, etc.).

#### E. Non-stormwater Discharges

##### 1. Certification of Non-Stormwater Discharges

a. The SWPPP must include a certification that all discharges (i.e., outfalls) have been tested or evaluated for the presence of nonstormwater. The certification must be signed in accordance with Part V.H. of this permit, and include:

- (1) The date of any testing and/or evaluation;
- (2) Identification of potential significant sources of nonstormwater at the site;



(3) A description of the results of any test and/or evaluation for the presence of nonstormwater discharges;

(4) A description of the evaluation criteria or testing method used; and

(5) A list of the outfalls or on-site drainage points that were directly observed during the test.

b. A copy of the certification must be included in the SWPPP at the facility.

Nonstormwater discharges to waters of the United States which are not authorized by a SPDES permit are unlawful, and must be terminated.

## **2. Allowable Non-Stormwater Discharges**

a. The sources of nonstormwater listed in Part I.C.3. (allowable nonstormwater discharges) are allowable discharges under this permit provided the permittee includes the following information in the SWPPP:

(1) Identification of each allowable nonstormwater source (flows from fire fighting activities do not need to be identified);

(2) The location where the nonstormwater is likely to be discharged; and

(3) Descriptions of appropriate BMPs for each source.

b. If mist blown from cooling towers is included as one of the allowable nonstormwater discharges from the facility, the permittee must specifically evaluate the potential for the discharges to be contaminated by chemicals used in the cooling tower and must select and implement BMPs to control such discharges so that the levels of cooling tower chemicals in the discharges would not cause or contribute to a violation of an applicable water quality standard.

**F. Documentation of Permit Eligibility Related to Endangered Species** - For new facilities and facilities expanding the perimeter of operations (onto adjoining or additional parcels that will result in a 1 acre or greater ground disturbance), the SWPPP must include documentation supporting the determination of permit eligibility with regard to Part I.D.5. (Endangered Species), including:

1. Information on whether listed endangered or threatened species, or critical habitat, are found in proximity to the facility;

2. Whether such species may be affected by the facility's stormwater discharges or stormwater discharge-related activities;

3. Results of endangered species screening determinations; and

4. A description of measures necessary to protect listed endangered or threatened species, or critical habitat. If the permittee fails to describe and implement such measures, the stormwater discharge is ineligible for coverage under this permit.

5. Information regarding the presence of rare, threatened and endangered species may be obtained from the appropriate regional Division of Fish, Wildlife and Marine Resources office or from consultation with Information Services, New York Natural Heritage Program. Regional Division of Fish, Wildlife and Marine Resources contact information may be obtained at <http://www.dec.state.ny.us/website/about/abtrull3.html>. The New York Natural Heritage Program may be reached at 518-402-8935 or at [www.dec.state.ny.us/website/dfwmr/heritage/inforeq.htm](http://www.dec.state.ny.us/website/dfwmr/heritage/inforeq.htm).

**G. Documentation of Permit Eligibility Related to Historic Places** - For new facilities and facilities expanding the perimeter of operations (onto adjoining or additional parcels that will result in a 1 acre or greater ground disturbance), the SWPPP must include documentation supporting the determination of permit eligibility with regard to Part I.D.6. (Historic Places), including:

1. Information on whether the stormwater discharges or stormwater discharge-related activities would have an effect on a property that is listed or eligible for listing on the National Register of Historic Places;
2. Where effects may occur, any written agreements that the permittee has made with the State Historic Preservation Office to mitigate those effects;
3. Results of historic places screening determinations;
4. A description of measures necessary to avoid or minimize adverse impacts on places listed, or eligible for listing, on the National Register of Historic Places. If the permittee fails to describe and implement such measures, the stormwater discharge is ineligible for coverage under this permit; and
5. As a minimum, information regarding the location of places listed, or eligible for listing, on the National Register of Historic Places should be obtained by consulting with New York State Historic Preservation Office, Peebles Island Resource Center, P.O. Box 189, Waterford, NY 12188-0189, Phone: (518) 237-8643, or using the GIS online resources available at: <http://nysparks.state.ny.us/shpo/>

**H. Copy of Permit Requirements** - The permittee must maintain a copy of the permit on file at the facility along with a copy of the SWPPP.

**I. Comprehensive Site Compliance Evaluation** - The permittee shall conduct facility inspections (site compliance evaluations) at least once a year. The inspections must be done by qualified personnel who may be either facility employees or outside consultants hired by the facility. The inspectors must be familiar with the industrial activity, the BMPs, the SWPPP, and must possess the skills to assess conditions at the facility that could impact stormwater quality and assess the effectiveness of the BMPs that have been chosen to control

the quality of the stormwater discharges. If more frequent inspections are conducted, the SWPPP must specify the frequency of inspections.

1. **Scope of the Compliance Evaluation** - Inspections must include all areas where industrial materials or activities are exposed to stormwater, as identified in Part III.C.3., and areas where spills and leaks have occurred within the past three years. Inspectors should look for but not limited to:

- a. Industrial materials, residue or trash on the ground that could contaminate or be washed away in stormwater;
- b. Leaks or spills from industrial equipment, drums, barrels, tanks or similar containers;
- c. Unauthorized non-stormwater discharges or allowable non-stormwater discharges that are not certified in accordance with Part III.E.1.;
- d. Off-site tracking of industrial materials or sediment where vehicles enter or exit the site;
- e. Tracking or blowing of raw, final, or waste materials from areas of no exposure to exposed areas; and
- f. Evidence of, or the potential for, pollutants entering the drainage system. Results of both visual and any analytical monitoring done during the year must be taken into consideration during the evaluation. Stormwater BMPs identified in the SWPPP must be observed to ensure that they are operating correctly. Where discharge locations or points are accessible, they must be inspected to see whether BMPs are effective in preventing significant impacts to receiving waters. Where discharge locations are inaccessible, nearby downstream locations must be inspected if possible.

2. **Follow-up Actions** - Based on the results of the inspection, the SWPPP shall be modified as necessary (e.g., show additional controls on the map required by Part III.C.2(c); revise the description of controls required by Part III.C.6. to include additional or modified BMPs designed to correct problems identified). Revisions to the SWPPP shall be completed within 14 calendar days following the inspection, unless permission for a later date is granted in writing by the Department. If existing BMPs need to be modified or if additional BMPs are necessary, implementation must be completed before the next anticipated storm event, if practicable, but not more than 12 weeks after completion of the comprehensive site evaluation, unless permission for a later date is granted in writing by the Department. For structural BMPs that will take longer than 12 weeks to implement, the written notification to the Department must include a schedule for completing the proposed project.

3. **Compliance evaluation report** - A report summarizing the scope of the inspection, name(s) of personnel making the inspection, the date(s) of the inspection, and major observations relating to the implementation of the SWPPP, and actions taken shall be made and retained as part of the SWPPP for at least one (1) year from the date permit coverage expires or is terminated. Major observations should include: the location(s) of discharges of pollutants from the site; location(s) of BMPs that need to be maintained; location(s) of BMPs that failed to operate as designed or proved inadequate for a particular location; and location(s) where additional BMPs are needed that did not exist at the time of inspection. The reports must identify any incidents of noncompliance. Where a report does not identify any incidents of noncompliance, the report shall contain a certification that the facility is in compliance with the SWPPP and this permit. The report shall be signed in accordance with Part V.H.; and

4. **Credit as a Routine Facility Inspection** - Where compliance evaluation schedules overlap with routine inspections required under Part III.C.6.b(1)(e), the annual compliance evaluation may be used as one of the routine inspections.

**J. Signature and Plan Review**

1. **Signature/Location** - The SWPPP shall be signed in accordance with Part V.H. and retained on-site at the facility covered by this permit in accordance with Part III.J.2. For inactive facilities, the plan may be kept at the nearest office of the permittee.

2. **Availability** - The permittee must keep a copy of the SWPPP on-site or locally available to the Department for review at the time of an on-site inspection. The SWPPP must be made available upon request to the Department, local agency approving stormwater management plans, or the owner of a municipal separate storm sewer receiving discharge from the site. Also, in the interest of the public's right to know, the permittee must make a copy of the SWPPP available to the public upon written request. (Note: A facility may withhold justifiable portions of the SWPPP from public review that contain trade secrets, confidential commercial information or critical infrastructure information in accordance with 6 NYCRR Part 616.7).

3. **Required Modifications** - The Department may notify the permittee at any time that the plan does not meet one or more of the minimum requirements of this permit. The notification shall identify those provisions of the permit that are not being met, as well as the required modifications. The permittee shall make the required changes to the SWPPP within 30 days of receipt of such notification, unless permission for a later date is granted in writing by the Department, and shall submit a written certification to the Department that the requested changes have been made.

**K. Keeping SWPPPs Current** - The permittee shall amend the SWPPP whenever:

1. There is a change in design, construction, operation, or maintenance at the facility which may have an effect on the potential for the discharge of pollutants from the facility which has not otherwise been addressed in the SWPPP; or

2. During inspections, monitoring, or investigations by facility personnel or by local, state, or federal officials it is determined that the SWPPP is ineffective in eliminating or significantly minimizing pollutants from sources identified under Part III.C.3., or is otherwise not achieving the general objectives of controlling pollutants in discharges from the facility.

#### **L. Special Stormwater Pollution Prevention Plan Requirements**

1. Additional requirements for stormwater discharges associated with industrial activity that discharge into or through municipal separate storm sewer systems.

a. In addition to the applicable requirements of this permit, facilities covered by this permit must comply with applicable requirements in municipal stormwater management programs developed under SPDES permits issued for the discharge of the municipal separate storm sewer system that receives the facility's discharge, provided that the permittee has been notified of such conditions.

b. Permittees that discharge stormwater associated with industrial activity through a municipal separate storm sewer system, or a municipal system designated by the Department shall make their SWPPP available to the municipal operator of the system upon request.

2. **Additional requirements for stormwater discharges associated with industrial activity from facilities subject to EPCRA Section 313 reporting requirements<sup>(11)</sup> for Water Priority Chemicals** - Any potential pollutant sources for which the facility has reporting requirements under EPCRA 313 must be identified in the SWPPP in Part III.C.3. (Summary of Potential Pollutant Sources).

3. **Additional requirements for facilities with Secondary Containment at Storage and Transfer Areas** - Compliance must be maintained with all applicable regulations including, but not limited to, those involving releases, registration, handling and storage of petroleum, chemical bulk and hazardous waste storage facilities (6 NYCRR 595-599, 612-614 and 370-373). Stormwater discharges from handling and storage areas should be eliminated where practical. Where this is not feasible, the permittee shall comply with the following BMPs:

<sup>11</sup> Pursuant to Section 313 of Title III of the Emergency Planning and Community Right-to-Know Act (EPCRA) (also known as Title III of the Superfund Amendments and Reauthorization Act (SARA) of 1986), a facility is subject to the annual reporting provisions of Section 313 if it meets all three of the following criteria for a calendar year: it is included in SIC codes 20-39; it has 10 or more full-time employees; and it manufactures (including imports), processes or otherwise uses chemicals listed in 40 CFR 372.65 in amounts greater than the "threshold" quantities specified in 40 CFR 372.25. Section 313 water priority chemicals are defined as chemical or chemical categories that: 1) are listed at 40 CFR 372.65; 2) are manufactured, processed or otherwise used at or above threshold levels at a facility subject to EPCRA Section 313 reporting requirements; and 3) that meet at least one of the following criteria: (i) are listed in Appendix D of 40 CFR 122 on either Table II (organic priority pollutants), Table III (certain metals, cyanides and phenols) or Table V (certain toxic pollutants and hazardous substances); (ii) are listed as a hazardous substance pursuant to section 311(b)(2)(A) of the CWA at 40 CFR 116.4; or (iii) are pollutants for which EPA has established acute or chronic water quality criteria.

a. Loading/Unloading Areas - Loading and unloading areas shall be operated to minimize spills, leaks or the discharge of pollutants in stormwater. Protection such as roofs, overhangs or door skirts to enclose trailer ends at truck loading/unloading docks shall be provided as appropriate. Where this is not feasible, the permittee shall comply with the following BMPs:

(1) During deliveries, having station personnel familiar with spill prevention and response procedures present to ensure that any leaks/spills are immediately contained and cleaned up; and

(2) Use of spill and overflow protection (e.g., drip pans, drip diapers, and/or other containment devices placed beneath fuel oil connectors to contain potential spillage during deliveries or from leaks at the connectors).

b. Spill Cleanup - All spilled or leaked substances must be removed from secondary containment systems as soon as practical and for CBS storage areas within 24 hours of the owner or operator discovering the spill, unless authorization is received from the Department. This permit does not relieve the Permittee of any reporting or other requirement related to spills or other releases of petroleum or hazardous substances. [Also See Part II Special Condition B regarding releases of hazardous substances or petroleum.] The containment system must be thoroughly cleaned to remove any residual contamination which could cause contamination of stormwater and the resulting discharge of pollutants to waters of the State<sup>(12)</sup>. Following spill cleanup the affected area must be completely flushed with clean water three times and the water removed after each flushing for proper disposal in an on-site or off-site wastewater treatment plant designed to treat such water and permitted to discharge such wastewater. Alternately, the permittee may test the first batch of stormwater following the spill cleanup to determine discharge acceptability. If the water contains no pollutants it may be discharged, otherwise it must be disposed of as noted above. (See the Discharge Monitoring section below for the list of parameters to be sampled for.)

c. Discharge Operation - Stormwater must be removed before it compromises the required containment system capacity. Each discharge may only proceed with the prior approval of the facility representative responsible for ensuring SPDES permit compliance. Bulk storage secondary containment drainage systems must be locked in

<sup>12</sup> "Waters or waters of the state" shall be construed to include lakes, bays, sounds, ponds, impounding reservoirs, springs, wells, rivers, streams, creeks, estuaries, marshes, inlets, canals, the Atlantic ocean within the territorial seas of the state of New York and all other bodies of surface or underground water, natural or artificial, inland or coastal, fresh or salt, public or private (except those private waters that do not combine or effect a junction with natural surface or underground waters), which are wholly or partially within or bordering the state or within its jurisdiction. Waters of the state are further defined in Parts 800 to 941 of this Title.

Storm sewers are not waters of the state unless they are classified in Parts 800 to 941 of this Title. Nonetheless, a discharge to a storm sewer shall be regulated as a discharge at the point where the storm sewer discharges to waters of the state.

Waste treatment systems, including treatment ponds or lagoons designed to meet the requirements of the Act and Environmental Conservation Law (other than cooling ponds as defined in 40 CFR 423.11(m)(see section 750 - 1.24) which also meet the criteria of this definition are not waters of the state. This exclusion applies only to manmade bodies of water which neither were originally created in waters of the state (such as a disposal area in wetlands) nor resulted from impoundment of waters of the state.

a closed position except when the owner or operator is in the process of draining accumulated stormwater. Transfer area secondary containment drainage systems must be locked in a closed position during all transfers and must not be reopened unless the transfer area is clean of contaminants. Stormwater discharges from secondary containment systems should be avoided during periods of precipitation. A logbook shall be maintained on site noting the date, time and personnel supervising each discharge.

d. Discharge Screening. - Prior to each discharge<sup>(13)</sup> from a secondary containment system the stormwater must be screened for contamination. (Note: All stormwater must be inspected for visible evidence of contamination.) Additional screening methods shall be developed by the permittee as part of the overall BMP Plan (e.g., the use of volatile gas meters to detect the presence of gross levels of gasoline or volatile organic compounds). If the screening indicates contamination, the permittee must collect and analyze a representative sample<sup>(14)</sup> of the stormwater. If the water contains no pollutants, the stormwater may be discharged. Otherwise it must either be disposed of in an onsite or off-site wastewater treatment plant designed to treat and permitted to discharge such wastewater, or the Regional Water Manager can be contacted to determine if it may be discharged without treatment.

e. Discharge Monitoring. - Unless the discharge from any containment system outlet is permitted by an individual SPDES permit as an outfall with explicit effluent and monitoring requirements, the permittee shall monitor the outlet as follows:

(1) Storage Area Secondary Containment Systems - The volume of each discharge from each outlet must be monitored. Discharge volume may be calculated by measuring the depth of water within the containment area times the wetted area converted to gallons or by other suitable methods. A representative sample shall be collected of the first discharge (*See footnote 13*) following any cleaned up spill or leak. The sample must be analyzed for pH, the substance(s) stored within the containment area and any other pollutants the permittee knows or has reason to believe are present (*See footnote 14*).

(2) Transfer Area Secondary Containment Systems - The first discharge (*See footnote 13*) following any spill or leak must be sampled for flow, pH, the substance(s) transferred in that area and any other pollutants the permittee knows or has reason to believe are present (*See footnote 14*).

<sup>13</sup> Note: Discharge includes stormwater discharges and snow and ice removal. If applicable, a representative sample of snow and/or ice should be collected and allowed to melt prior to assessment.

<sup>14</sup> If the stored substance is gasoline or aviation fuel then sample for oil & grease, benzene, ethylbenzene, naphthalene, toluene and total xylenes (EPA method 602). If the stored substance is kerosene, diesel fuel, fuel oil, or lubricating oil then sample for oil & grease and polynuclear aromatic hydrocarbons (EPA method 610). In all cases an estimated discharge volume and pH monitoring is required.

f. **Discharge Reporting** - Any results of monitoring required above, must be maintained with the facility's SWPPP and retained in accordance with Part IV.C. Failure to perform the required monitoring shall constitute a violation of the terms of this permit.

g. **Prohibited Discharges** - In all cases, any discharge which contains a visible sheen, foam, or odor, or may cause or contribute to a violation of water quality is prohibited.

4. **Additional Requirements for Salt Storage** - Storage piles of salt used for deicing or other commercial or industrial purposes shall be enclosed or covered to prevent exposure to precipitation, except during active operations to add or remove materials from the pile.

#### **Part IV. MONITORING, REPORTING AND RETENTION OF RECORDS**

A. **Monitoring Requirements** - There are six individual and separate categories of monitoring requirements that a facility may be subject to under this permit. The monitoring requirements applicable to a facility depend on the types of industrial activities generating stormwater runoff from the facility. Part VIII of the permit identifies monitoring requirements applicable to specific sectors of industrial activity. The permittee must review Parts III, IV and VIII of the permit to determine which monitoring requirements and/or numeric limitations apply to the facility. Unless otherwise specified, monitoring requirements under Parts III, IV and VIII are additive.

Specific monitoring requirements and limitations are applied to each discharge at a facility. Where stormwater from co-located activities are commingled, the monitoring requirements and limitations are additive. Where more than one numeric limitation for a specific parameter applies to a discharge, compliance with the more restrictive limitation is required. Where monitoring requirements for a monitoring period overlap (e.g., need to monitor TSS once/year for compliance monitoring and also once/year for benchmark monitoring), the permittee may use a single sample to satisfy both monitoring requirements.

##### **1. Types of Monitoring Requirements and Limitations**

a. **Quarterly visual monitoring** - The requirements and procedures for quarterly visual monitoring are applicable to all facilities covered under this permit, regardless of the facility's sector of industrial activity.

(1) The permittee must perform and document a quarterly visual examination of a stormwater discharge associated with industrial activity from each outfall, except discharges exempted below. The examination(s) must be made at least once in each of the following three month periods: January through March, April through June, July through September, and October through December. No analytical tests are required to be performed on the samples for the purpose of meeting the visual monitoring requirements. The examination must document observations of color, odor, clarity, floating solids, settled solids, suspended solids, foam, oil sheen, and



any other obvious indicators of stormwater pollution. The visual examination must be made during daylight hours (e.g., normal working hours). The examination must be conducted in a well-lit area. Where practicable, the same individual should carry out the collection and examination of discharges for the entire permit term for consistency.

(2) Visual examinations must be made of samples collected within the first 30 minutes (or as soon thereafter as practical, but not to exceed one hour) of when the runoff or snowmelt begins discharging from the facility. All samples (except snowmelt samples) must be collected from the discharge resulting from a storm event that is greater than 0.1 inches in magnitude and that occurs at least 72 hours from the previously measurable (greater than 0.1 inch rainfall) storm event. The 72-hour storm interval is waived if the preceding measurable storm did not result in a stormwater discharge (e.g., a storm event in excess of 0.1 inches may not result in a stormwater discharge at some facilities). If no qualifying storm event resulted in runoff from the facility during a monitoring quarter, the permittee is excused from visual monitoring for that quarter provided that documentation is included with the monitoring records indicating that no qualifying storm event occurred that resulted in stormwater runoff during that quarter. If a visual examination was performed and the storm event was later determined not to be a measurable (greater than 0.1 inch rainfall) storm event, the visual examination should be included in the SWPPP records. All documentation must be signed and certified in accordance with Part V.H. A Quarterly Visual Monitoring Form has been included in Appendix D as guidance and may be used by the permittee.

(3) If the visual examination indicates the presence of stormwater pollution (e.g., color, odor, floating solids, settled solids, suspended solids, foam, oil sheen, or other indicators), the permittee must evaluate the facility for potential sources of stormwater contamination. Any sources of contamination that are identified must be remedied. Such remedies may include implementation of non-structural or structural BMPs to prevent recurrence. The facility's SWPPP must be updated to reflect these revisions within 14 days of the inspection for items that can be readily resolved. More complicated maintenance or repairs shall be performed in accordance with the timeframes for more complicated maintenance and repairs described under Sections III.D - Maintenance or III.I.2 - Follow-up Actions.

(4) The visual examination must be documented and maintained on-site with the Stormwater Pollution Prevention Plan (SWPPP) in accordance with Part IV.C. The report must include the outfall location, the examination date and time, examination personnel, the nature of the discharge (i.e., runoff or snow melt), visual quality of the stormwater discharge (including observations of color, odor, clarity, floating solids, settled solids, suspended solids, foam, oil sheen, and other obvious indicators of stormwater pollution), probable sources of any observed stormwater contamination and actions taken to eliminate these sources.

(5) Inactive and unstaffed sites - When the permittee is unable to conduct visual stormwater examinations at an inactive and unstaffed site, a waiver of the monitoring requirement may be exercised as long as the facility remains inactive and unstaffed. If this waiver is exercised, the permittee must maintain a certification with the SWPPP stating that the site is inactive and unstaffed and that performing visual examinations during a qualifying event is not feasible. The waiver must be signed and certified in accordance with Part V.H.

b. Annual dry weather flow monitoring - The requirements and procedures for annual dry weather flow monitoring are applicable to all facilities covered under this permit, regardless of the facility's sector of industrial activity.

(1) The permittee must perform and document at least one dry weather flow inspection each year after at least three (3) consecutive days of no precipitation. The dry weather flow inspection shall be conducted to determine the presence of nonstormwater discharges to the stormwater drainage system.

(2) If a nonstormwater discharge is discovered, the Permittee shall identify its source to determine whether it is an authorized discharge (e.g., a discharge covered by another SPDES permit or an authorized non-stormwater discharge addressed under Part I.C.3). The Permittee shall modify the SWPPP to address any newly identified allowable non-stormwater discharges identified in Part I.C.3 that were not previously certified in accordance with Part III.E.1.

(3) The Permittee shall notify the Department within 14 days of any non-authorized discharge that cannot be easily eliminated. Appropriate actions may require coverage under an individual industrial SPDES permit or connection to the sanitary sewer system.

(4) Results of the dry weather flow inspections must be documented and retained on-site with the Stormwater Pollution Prevention Plan (SWPPP) in accordance with Part IV.C. The report must include the outfall locations, the inspection date and time, inspection personnel, description of discharges identified, the source of any discharges and actions taken to address any newly identified allowable non-stormwater discharges or elimination of non-authorized discharges.

(5) Inactive and unstaffed sites - If the permittee is unable to conduct a dry weather flow inspection at an inactive and unstaffed site, a waiver of the monitoring requirement may be exercised as long as the facility remains inactive and unstaffed. If this waiver is exercised, the permittee must maintain a certification with the SWPPP stating that the site is inactive and unstaffed and that performing visual examinations during a qualifying event is not feasible. The waiver must be signed and certified in accordance with Part V.H.

c. Benchmark monitoring of discharges associated with specific industrial activities - Table IV-1 identifies the specific industrial sectors subject to the benchmark monitoring requirements of this permit and the industry-specific pollutants of concern. The permittee must refer to the tables found in the individual sectors in Part VIII for benchmark monitoring cut-off concentrations. Co-located industrial activities at the facility that are described in more than one sector in Part VIII must comply with all applicable benchmark monitoring requirements from each sector.

The benchmark monitoring cut-off concentrations are intended as a guideline for the permittee to determine the overall effectiveness of the SWPPP in controlling the discharge of pollutants to receiving waters. The benchmark concentrations do not constitute direct numeric effluent limitations; a benchmark exceedance, therefore in and of itself, is not a permit violation. It does, however, signal the need for the permittee to evaluate potential sources of stormwater contaminants at the facility. Any sources of contamination that are identified must be remedied. Such remedies may include implementation of non-structural or structural BMPs to prevent recurrence. The facility's SWPPP must be updated to reflect these revisions within 14 days of the inspection for items that can be readily resolved. More complicated maintenance or repairs shall be performed in accordance with the timeframes for more complicated maintenance and repairs described under Sections III.D - Maintenance or III.I.2 - Follow-up Actions. If corrective actions at a facility do not result in achieving benchmark monitoring cut-off concentrations, the facility must continue efforts to implement additional BMPs. Failure to undertake and document the review or take the necessary corrective actions are violations of the permit. Continued exceedance of benchmark monitoring cut-off concentrations may identify facilities that would be more appropriately covered under an individual SPDES permit.

(1) Monitoring periods for benchmark monitoring - If a facility falls within a sector(s) required to conduct benchmark monitoring, monitoring must be performed annually during the calendar year.

(2) Samples must be collected in accordance with Part IV.A.2.b. Monitoring results must be reported in accordance with Part IV.B. and retained in accordance with Part IV.C.

(3) Inactive and unstaffed sites - If the permittee is unable to conduct benchmark monitoring at an inactive and unstaffed site, a waiver of the monitoring requirement may be exercised as long as the facility remains inactive and unstaffed. If the permittee exercises this waiver, a certification must be submitted to the Department and maintained with the SWPPP stating that the site is inactive and unstaffed and that performing benchmark monitoring during a qualifying storm event is not feasible. The waiver must be signed and certified in accordance with Part V.H.

**TABLE IV-1.**  
**INDUSTRIAL SECTORS SUBJECT TO BENCHMARK MONITORING**

Industry Sector <sup>1</sup>	Industry Sub-sector	Benchmark Monitoring Parameters
A .....	General Sawmills and Planing Mills ..... Wood Preserving Facilities ..... Log Storage and Handling ..... Hardwood Dimension and Flooring Mills ..... .....	TSS, COD, Zinc, TN, Phosphorus Arsenic, Chromium, Copper TSS TSS, COD
B .....	Paperboard Mills .....	COD
C .....	Industrial Inorganic Chemicals ..... Plastics, Synthetic Resins, etc. .... Soaps, Detergents, Cosmetics, Perfumes ... Agricultural Chemicals .....	Aluminum, Iron, TN Zinc TN, Zinc TN, Iron, Lead, Zinc, Phosphorus
D .....	Asphalt Paving and Roofing Materials.....	TSS
E .....	Clay Products ..... Concrete Products .....	Aluminum TSS, pH, Iron
F .....	Steel Works, Blast Furnaces, and Rolling .... and Finishing Mills. Iron and Steel Foundries ..... Nonferrous Rolling, Drawing & Extruding .. Nonferrous Foundries (Castings) .....	Aluminum, Zinc  Aluminum, TSS, Copper, Iron, Zinc Copper, Zinc Copper, Zinc
G <sup>2</sup> .....	Ore Mining and Dressing .....	TSS, COD, pH, turbidity, metals
H .....	[Reserved]	
I .....	Oil and Gas Extraction ..... Petroleum Refining .....	TSS, Chlorides, pH Oil & Grease, Lead, Zinc, BTEX <sup>4</sup>
J .....	Sand and Gravel Mining ..... Dimension and Crushed Stone and Non- ..... metallic Minerals (except fuels)	TSS, TN, Iron, Zinc, Phosphorus TSS
K .....	Hazardous Waste Treatment, Storage or ..... Disposal	TSS, COD, TN, Arsenic, Cadmium, Cyanide, Lead, Magnesium, Mercury, Selenium, Silver
L .....	Landfills, Land Application Sites, and Open.. Dumps. Landfills, Land Application Sites and Open .. Dumps, Except Municipal Solid Waste Landfill Sites Closed in accordance with 40 CFR 258.60	Iron, TSS, TN, Phosphorus  Iron, TSS
M .....	Automobile Salvage Yards .....	TSS, Oil & Grease, Aluminum, Iron, Lead, BTEX <sup>4</sup>
N .....	Scrap Recycling/Waste Recycling Facilities .. and Facilities Engaged in Ship Dismantling, Marine Salvaging & Marine Wrecking for Scrap. Scrap & Waste Recycling Facilities which .... include Stormwater Discharges from Shredder Fluff Storage Areas.	TSS, COD, Oil & Grease, Aluminum, Cadmium, Copper, Chromium, Iron, Lead, Zinc  TSS, COD, Oil & Grease, Aluminum, Cadmium, Copper, Chromium, Iron, Lead, Zinc, Mercury, PCBs, BTEX <sup>4</sup>
O .....	Steam Electric Generating Facilities .....	Iron, Oil & Grease, PCBs
P .....	Land Transportation and Warehousing .....	Oil & Grease, COD, BTEX <sup>4</sup>
Q .....	Water Transportation Facilities .....	Aluminum, Iron, Zinc, Lead
S .....	Airports with deicing activities <sup>3</sup> .....	COD, BOD, TN, pH
T .....	Treatment Works .....	COD
U .....	Grain Mill Products ..... Fats and Oils Products .....	TSS, TN, Phosphorus BOD, COD, TSS, TN, Phosphorus
Y .....	Rubber Products .....	Zinc

Z .....	Leather Tanning and Finishing .....	TN, Chromium
AA .....	Fabricated Metal Products Except Coating .. Fabricated Metal Coating and Engraving .....	TN, Aluminum, Iron, Zinc TN, Zinc
AC .....	Electronic, Electrical Equipment and Components, Photographic & Optical Goods	TSS, Copper, Lead
AD .....	Non-classified Facilities Designated by the Department	TSS, COD, Oil & Grease, TN, Iron, Zinc
AE .....	Non-Classified Facilities Designated by the Department for DPW and Highway Maintenance Facilities	TSS, COD, Oil & Grease, BTEX <sup>4</sup>

1 Table does not include parameters for compliance monitoring under effluent limitations guidelines.

2 See Sector G (Part VIII.G) for additional monitoring discharges from waste rock and overburden piles from active ore mining or dressing facilities which includes TSS, COD, turbidity, pH, hardness, and metals.

3 Monitoring requirement for airports with deicing activities utilizing more than 100 tons of urea or more than 100,000 gallons of glycol per year.

4 BTEX is Benzene, Ethylbenzene, Toluene and Xylene.

#### d. Coal pile runoff

(1) Facilities with discharges of stormwater from coal storage piles must comply with the limitations and monitoring requirements of Table IV-2 for all discharges containing the coal pile runoff, regardless of the facility's sector of industrial activity. Permittees shall monitor such stormwater discharges at least annually (once per year).

(2) The coal pile runoff must not be diluted with stormwater or other flows in order to meet this limitation.

(3) If a facility is designed, constructed and operated to treat the volume of coal pile runoff that is associated with a 10-year, 24-hour rainfall event, any untreated overflow of coal pile runoff from the treatment unit is not subject to the 50 mg/L limitation for total suspended solids.

(4) Samples must be collected in accordance with Part IV.A.2.b. Monitoring results must be reported in accordance with Part IV.B. and retained in accordance with Part IV.C.

TABLE IV-2.  
NUMERIC LIMITATIONS FOR COAL PILE RUNOFF

Parameter	Limit	Monitoring Frequency	Sample Type
Total Suspended Solids (TSS)...	50 mg/l, max .....	1/year .....	Grab
pH .....	6.0 - 9.0 min. and max.	1/year .....	Grab

#### e. Compliance monitoring for discharges subject to numerical effluent limitation guidelines

(1) Facilities subject to stormwater effluent limitation guidelines are required to monitor such discharges to evaluate compliance with numerical effluent limitations and are identified in Table IV-3. Industry-specific numerical

limitations and compliance monitoring requirements are described in Part VIII of the permit. Co-located industrial activities at the facility that are described in more than one sector in Part VIII must comply on a discharge-by-discharge basis with all applicable effluent limitations from each sector. Permittees shall monitor the discharges for the presence of the pollutant subject to the effluent limitation at least annually (once per year).

(2) Samples must be collected in accordance with Part IV.A.2.b. The representative outfalls provision of Part IV.A.2.d and the alternative certification provision of Part IV.A.4.b, are not applicable to stormwater discharge monitoring for compliance with effluent limitations. Results of all compliance monitoring must be reported in accordance with Part IV.B. and retained in accordance with Part II.C.

f. Secondary Containment Areas for Storage and Transfer Areas - Discharge screening and monitoring for storage and transfer area secondary containment systems shall be in accordance with Part III.L.3.

TABLE IV-3.  
EFFLUENT LIMITATION GUIDELINES APPLICABLE TO DISCHARGES  
THAT MAY BE ELIGIBLE FOR PERMIT COVERAGE

<b>Effluent Limitation Guideline</b>	<b>Sectors With Affected Facilities</b>
Runoff from material storage piles at cement manufacturing facilities (40 CFR Part 411 Subpart C (2002) (established February 23, 1977))	E
Contaminated runoff from phosphate fertilizer manufacturing facilities (40 CFR Part 418 Subpart A (2002) (established April 8, 1974))	C
Coal pile runoff at steam electric generating facilities (40 CFR Part 423 (2002) (established November 19, 1982))	O
Discharges resulting from spray down or intentional wetting of logs at wet deck storage areas (40 CFR Part 429, Subpart I (2002) (established January 26, 1981))	A
Mine dewatering discharges at crushed stone mines (40 CFR Part 436, Subpart B)	J
Mine dewatering discharges at construction sand and gravel mines (40 CFR Part 436, Subpart C)	J
Mine dewatering discharges at industrial sand mines (40 CFR Part 436, Subpart D)	J
Runoff from asphalt emulsion facilities (40 CFR Part 443 Subpart A (2002) (established July 24, 1975))	D
Runoff from landfills, (40 CFR Part 445, Subpart A and B (2002) (established February 2, 2000))	K & L

## **2. Monitoring Instructions**

a. Monitoring periods - Permittees that are required to conduct monitoring on an annual or quarterly basis must collect samples within the following time periods (unless otherwise specified in Part IV):

(1) The monitoring year is from January 1 to December 31.

(2) If a facility's permit coverage was effective less than one month from the end of a quarterly or yearly monitoring period, the first monitoring period starts with the next respective monitoring period (e.g., if permit coverage begins September 5, the permittee would not need to start quarterly sampling until the October to December quarter, but the permittee would only have from September 5 to December 31 to complete that year's annual monitoring).

b. Collection and analysis of samples - Sampling requirements must be assessed on an outfall by outfall basis. Samples must be collected as follows:

(1) When and How to Sample - A minimum of one grab sample must be taken from the discharge associated with industrial activity resulting from a storm event with at least 0.1 inch of precipitation (defined as a "measurable" event), providing the interval from the preceding measurable storm is at least 72 hours. The 72-hour storm interval is waived if the preceding measurable storm did not result in a stormwater discharge (e.g., a storm event in excess of 0.1 inches may not result in a stormwater discharge at some facilities), or if the permittee is able to document that less than a 72 hour interval is representative for local storm events during the sampling period. The grab sample must be taken during the first 30 minutes (or as soon thereafter as practical, but not to exceed one hour) of the discharge. If the sampled discharge commingles with process or nonprocess water, the permittee must attempt to sample the stormwater discharge before it mixes with the nonstormwater.

(2) Sample Analysis - Monitoring and analysis must be conducted according to test procedures approved under 40 CFR Part 136, or equivalent, unless other test procedures have been specified in this permit.

(3) Any laboratory test or sample analysis required by this permit for which the State Commissioner of Health issues certificates of approval pursuant to section 502 of the Public Health Law shall be conducted by a laboratory that has been issued a certificate of approval.

c. Storm event data - Along with the monitoring results, the permittee must provide the date and duration (in hours) of the storm event(s) sampled; rainfall measurements or estimates (in inches) of the storm event that generated the sampled runoff; the duration between the storm event sampled and the end of the previous measurable (greater than 0.1 inch rainfall) storm event; and an estimate of the total volume (in gallons) of the discharge sampled.

d. Representative outfalls - If a facility has two or more outfalls that discharge substantially identical effluents, based on similarities of the industrial activities, significant materials or stormwater management practices occurring within the drainage areas of the outfalls, the permittee may test the effluent of just one of the outfalls and report that the quantitative data also applies to the substantially identical

outfall(s). This outfall monitoring waiver for substantially identical discharges applies to quarterly visual monitoring as well, but does not apply to compliance monitoring for discharges subject to numerical effluent limitation guidelines (see Part IV.A.1.c. and Part IV.A.1.d. The permittee should collect a sample from the anticipated "worst case" outfall as indicated by the area or level of industrial activity. If the drainage areas are similar, or if all past monitoring has been below benchmark monitoring cut-off concentrations, permittee may vary which outfall is sampled as part of the monitoring program. The permittee must include the following information in the SWPPP, and in any SWMRs that are required to be submitted to the department:

- (1) The locations of the outfalls;
- (2) Why the outfalls are expected to discharge substantially identical effluents;
- (3) Estimates of the size of the drainage area (in square feet) for each of the outfalls; and
- (4) An estimate of the runoff coefficient of the drainage areas (low: under 40%; medium: 40% to 65%; high: above 65%).

3. **Monitoring Required by the Department** - The Department may provide written notice to any facility including those otherwise exempt from the sampling requiring discharge sampling for specific parameters and a specific monitoring frequency. Any such notice will briefly state the reason for the monitoring, parameters to be monitored, frequency and period of monitoring, sample types and reporting requirements.

4. **Monitoring Waivers** - Unless specifically stated otherwise, the following waivers may be applied to any monitoring required under this permit.

a. **Adverse climatic conditions waiver** - When adverse weather conditions prevent the collection of samples, a substitute sample may be taken during a qualifying storm event in the next monitoring period. Adverse weather conditions are those that are dangerous or create inaccessibility for personnel, and may include such things as local flooding, high winds, electrical storms, or situations that otherwise make sampling impracticable, such as drought or extended frozen conditions.

b. **Alternative certification of "Not Present" or "No Exposure"** - The permittee will not be subject to the continued benchmark monitoring requirements of Parts IV and VIII provided that:

- (1) A certification is made for a given outfall, or on a pollutant-by-pollutant basis in lieu of monitoring required under Part VIII, that material handling equipment or activities, raw materials, intermediate products, final products, waste materials, by-products, industrial machinery or operations, or significant materials from past industrial activity that are located in areas of the facility within the drainage area



of the outfall are not exposed to stormwater and are not expected to be exposed to stormwater for the certification period;

(2) The certification must be signed in accordance with Part V.H., submitted to the Department with the annual certification report and a copy retained with the SWPPP;

(3) At least one annual sampling event for benchmark parameters must be conducted and documented to be at or below the Practical Quantitation Limit<sup>(15)</sup> prior to making this certification in order to confirm that sources of stormwater contamination do not exist that the permittee was not aware of. A copy of this monitoring must be attached to the certification in subparagraph (2) above;

(4) If certification cannot be made for an entire period, the permittee must document the date exposure was eliminated and must perform any monitoring required up until that date; and

(5) This monitoring waiver is not applicable to compliance monitoring of coal pile run-off or discharges subject to numerical effluent limitations established in Parts IV and VIII.

## **B. Reporting Monitoring Results and Annual Certification Reporting**

1. **Annual Certification Report** - The annual certification report is the primary mechanism for reporting to the Department. A copy of the annual certification report form is provided in Appendix C of this permit.

a. Every facility covered by this general permit must complete and submit an annual certification report form in accordance with the submission deadlines in Table IV-4.

b. Monitoring results for benchmark parameters and numeric effluent limitations must be reported on Discharge Monitoring Report (DMR) forms that will be provided by the Department. The completed DMR forms and any additional monitoring requested by the Department, where applicable, must be submitted along with the annual certification report as described in Table IV-4.

c. Permittees shall submit results for each outfall associated with industrial activity. For each outfall, one signed Discharge Monitoring Report (DMR) form must be submitted to the Department per storm event sampled.

<sup>15</sup> For the purpose of the alternative certification of "Not Present" monitoring waiver, at least one annual sampling event for benchmark parameters must be conducted and documented to be at or below the Practical Quantitation Limit (PQL), which is typically 3 times the analytical Method Detection Levels (MDL). An exception to using the PQL would be a condition where the benchmark monitoring cut-off concentration is less than the PQL. Under these circumstances, the sample result must be below the MDL to qualify for the monitoring waiver.

**TABLE IV-4.**  
**Monitoring Reporting Requirements**

<b>Monitoring type</b>	<b>Submission Deadline</b>
Visual Monitoring	Retain documentation with SWPPP. Answer applicable questions on the Annual Certification Report Form and submit by March 31st.
Dry Weather Flow Inspection	Retain documentation with SWPPP. Answer applicable questions on the Annual Certification Report Form and submit by March 31st.
Benchmark Monitoring	Submit results on a Discharge Monitoring Report form (see Appendix E) along with the Annual Certification Report by March 31st.
Coal Pile Run-off	Submit results on a Discharge Monitoring Report form (see Appendix E) along with the Annual Certification Report by March 31st.
Monitoring for Effluent Numeric Limitation	Submit results on a Discharge Monitoring Report form (see Appendix E) along with the Annual Certification Report by March 31st.
Monitoring for Bulk Storage and Loading/Unloading Areas	Retain documentation with SWPPP. Answer applicable questions on the Annual Certification Report Form and submit by March 31st.

d. The annual certification reports and monitoring reports must be submitted to:

Industrial Stormwater General Permit Coordinator  
NYSDEC, Bureau of Water Permits  
625 Broadway  
Albany, New York 12233-3505

e. Monitoring waivers - Any sampling waivers (including representative outfalls or monitoring at inactive/unstaffed sites) should be described in a cover letter accompanying the annual certification report and discharge monitoring report forms. Information should describe the sampling waiver being claimed, the affected outfall(s) and specific parameters (in the case of the alternative certification for "not present" or "no exposure").

f. Additional reporting - In addition to filing the annual certification reports and discharge monitoring reports, permittees with at least one stormwater discharge associated with industrial activity through a municipal separate storm sewer system (MS4), or a municipal system designated by the Department, must submit signed copies of annual certification reports and discharge monitoring reports to the MS4 operator at the same time.

**C. Retention of Monitoring Records** - Monitoring records must be retained to meet both of the following requirements:

1. **Stormwater Pollution Prevention Plan (SWPPP)** - The permittee shall retain the SWPPP developed in accordance with Part III of this permit until at least one year after coverage under this permit terminates. The permittee shall retain all records of monitoring information, copies of all reports required by this permit, and records of all data used to complete the NOIT form to be covered by this permit, until at least one year after

coverage under this permit terminates. This period may be explicitly modified by or extended by request of the Department at any time; and

**2. Recording of Monitoring Activities and Results** - Records must be maintained as follows in accordance with 6 NYCRR Part 750-2.5(c):

a. The permittee shall retain records of all monitoring information, including all calibration and maintenance records and all original strip chart recordings for continuous monitoring instrumentation, copies of all reports required by a SPDES permit, and records of all data used to complete the application for the permit, for a period of at least 5 years from the date of the sample, measurement, report or application. This period may be extended by written request of the Department, provided that the extension is necessary to implement the provisions of this Part or ECL and that the reason or reasons for the extension are provided in the request.

b. Records of monitoring information shall include:

- (1) the date, exact place, and time of sampling or measurements;
- (2) the individual(s) who performed the sampling or measurements;
- (3) the date(s) analyses were performed;
- (4) the individual(s) who performed the analyses;
- (5) the analytical techniques or methods used;
- (6) the results of such analyses; and
- (7) Quality assurance/quality control documentation.

c. When records are stored electronically, the records must be preserved in a manner that reasonably assures their integrity and are acceptable to the Department. Such records must also be in a format which is accessible to the Department.

d. The permittee shall make available to the Department for inspection and copying or furnish to the Department within 25 business days of receipt of a Department request for such information, any information retained in accordance with this subdivision.

**Part V. STANDARD PERMIT CONDITIONS**

**A. Duty to Comply** - The permittee must comply with all terms and conditions of the permit. Any permit noncompliance constitutes a violation of the Environmental Conservation Law and the Clean Water Act and is grounds for enforcement action, permit suspension, revocation, modification or denial of a permit renewal application.

**B. Continuation of the Expired General Permit** - This permit shall expire on March 27, 2012. In the event a new general permit is not issued prior to termination of this general permit, then the permittee may continue to operate and discharge in accordance with the terms and conditions of this general permit until such time that a new general permit is issued.

**C. Penalties for Violations of Permit Conditions** - There are substantial criminal, civil, and administrative penalties associated with violating the provisions of this permit. Fines of up to \$37,500 per day for each violation and imprisonment for up to fifteen (15) years may be assessed depending upon the nature and degree of the offense.

**D. Need to Halt or Reduce Activity Not a Defense** - It shall not be a defense for a permittee in an enforcement action that it would have been necessary to halt or reduce the permitted activity in order to maintain compliance with the conditions of this permit.

**E. Duty to Mitigate** - The permittee shall take all reasonable steps to minimize or prevent any discharge in violation of this permit which has a reasonable likelihood of adversely affecting human health or the environment.

**F. Duty to Provide Information** - The permittee shall furnish to the Department, within a specified time, any information requested to determine compliance with this permit in accordance with 6 NYCRR Part 750-2.1(i). The permittee shall also furnish upon request, copies of records required by this permit.

**G. Other Information** - When the permittee becomes aware that he or she failed to submit any relevant facts or submitted incorrect information in the Notice of Intent or Termination (NOIT) form or in any other report to the Department, he or she shall promptly submit corrected facts or information.

→ **H. Signatory Requirements** - All Notices of Intent or Termination (NOIT) forms, stormwater pollution prevention plans, reports, certifications or information submitted to the Department (and/or the operator of a large or medium municipal separate storm sewer system), or records that this permit requires to be maintained by the permittee, shall be signed as follows:

1. All Notices of Intent or Termination (NOIT) forms shall be signed as follows:

a. For a corporation: by a responsible corporate officer. For the purpose of this section, a responsible corporate officer means:

(1) a president, secretary, treasurer, or vice-president of the corporation in charge of a principal business function, or any other person who performs similar policy or decision-making functions for the corporation; or

(2) the manager of one or more manufacturing, production or operating facilities, provided, the manager is authorized to make management decisions which govern the operation of the regulated facility including having the explicit or implicit duty of making major capital investment recommendations, and initiating and directing

other comprehensive measures to assure long term environmental compliance with environmental laws and regulations; the manager can ensure that the necessary systems are established or actions taken to gather complete and accurate information for permit application requirements, and where authority to sign documents has been assigned or delegated to the manager in accordance with corporate procedures.

b. For a partnership or sole proprietorship: by a general partner or the proprietor, respectively; or

c. For a municipality: State, Federal, or other public agency: by either a principal executive officer or ranking elected official. For purposes of this section, a principal executive officer of a Federal agency includes (1) the chief executive officer of the agency, or (2) a senior executive officer having responsibility for the overall operations of a principal geographic unit of the agency (e.g. Regional Administrators of EPA).

2. All reports required by the permit and other information requested by the Department shall be signed by a person described above or by a duly authorized representative of that person. A person is a duly authorized representative only if:

a. The authorization is made in writing by a person described above and submitted to the Department.

b. The authorization specifies either an individual or a position having responsibility for the overall operation of the regulated facility or activity, such as the position of manager, owner or operator, superintendent, or position of equivalent responsibility or an individual or position having overall responsibility for environmental matters for the company. (A duly authorized representative may thus be either a named individual or any individual occupying a named position).

c. Changes to authorization - If an authorization under Part VI.G.1. is no longer accurate because a different individual or position has responsibility for the overall operation of the facility, letter notification satisfying the requirements above must be submitted to the Department prior to or together with any reports, information, or applications to be signed by an authorized representative.

d. Certification - Any person signing documents under this section shall make the following certification: "I certify under penalty of law that this document and all attachments were prepared under my direction or supervision in accordance with a system designed to assure that qualified personnel properly gathered and evaluated the information submitted. Based on my inquiry of the person or persons who manage the system, or those persons directly responsible for gathering the information, the information submitted is, to the best of my knowledge and belief, true, accurate, and complete. I am aware that there are significant penalties for submitting false information, including the possibility of fine and imprisonment for knowing violations.

**I. Penalties for Falsification of Reports** - In accordance with 6 NYCRR Part 750-2.4(f) any person who knowingly makes any false material statement, representation, or certification in any application, record, report or other document filed or required to be maintained under this permit, including reports of compliance or noncompliance shall, upon conviction, be punished by a fine of not more than \$37,500, or by imprisonment for not more than 2 years, or by both.

**J. Penalties for Falsification of Monitoring Systems** - In accordance with 6 NYCRR Part 750-2.5(a)(6) any person who falsifies, tampers with, or knowingly renders inaccurate any monitoring device or method required to be maintained under this permit shall, upon conviction, be punished by fines and imprisonment.

**K. Oil and Hazardous Substance Liability** - Nothing in this permit shall be construed to preclude the institution of any legal action or relieve the permittee from any responsibilities, liabilities, or penalties to which the permittee is or may be subject under section 311 of the CWA or section 106 of the Comprehensive Environmental Response, Compensation and Liability Act of 1980 ("CERCLA").

**L. Property Rights** - The issuance of this permit does not convey any property rights of any sort, nor any exclusive privileges, nor does it authorize any injury to private property nor any invasion of personal rights, nor any infringement of Federal, State or local laws or regulations.

**M. Severability** - The provisions of this permit are severable, and if any provision of this permit, or the application of any provision of this permit to any circumstance, is held invalid, the application of such provision to other circumstances, and the remainder of this permit shall not be affected thereby.

**N. Requiring an Individual Permit or an Alternative General Permit**

1. At its sole discretion, the Department may require any person authorized by this general permit to apply for and/or obtain either an individual SPDES permit or an alternative SPDES general permit in accordance with 6 NYCRR Part 750-1.21(e).

2. Any owner or operator authorized by this permit may request to be excluded from the coverage of this permit by applying for an individual permit. The owner or operator shall submit an individual application (Form 1 and Form 2F) with reasons supporting the request to the Department. Individual permit applications shall be submitted to the address of the appropriate DEC Office (see Appendix G of this permit). The request may be granted by the issuance of any individual permit or an alternative general permit if the reasons cited by the owner or operator are adequate to support the request.

3. When an individual SPDES permit is issued to a discharger authorized to discharge under a general SPDES permit for the same discharge(s), the general permit authorization for outfalls authorized under the individual permit is automatically terminated on the effective date of the individual permit unless termination is earlier in accordance with 6 NYCRR Part 750.

**O. State/Environmental Laws**

1. Nothing in this permit shall be construed to preclude the institution of any legal action or relieve the permittee from any responsibilities, liabilities, or penalties established pursuant to any applicable State law or regulation under authority preserved by section 510 of the Clean Water Act.
2. No condition of this permit shall release the permittee from any responsibility or requirements under other environmental statutes or regulations.

**P. Proper Operation and Maintenance** - The permittee shall at all times properly operate and maintain all facilities and systems of treatment and control (and related appurtenances) which are installed or used by the permittee to achieve compliance with the conditions of this permit and with the requirements of stormwater pollution prevention plans. Proper operation and maintenance also includes adequate laboratory controls and appropriate quality assurance procedures. Proper operation and maintenance requires the operation of backup or auxiliary facilities or similar systems installed by a permittee only when necessary to achieve compliance with the conditions of the permit.

**Q. Inspection and Entry** - The permittee shall allow the Department or an authorized representative of EPA, the State, or, in the case of a facility which discharges through a municipal separate storm sewer, an authorized representative of the municipal operator of the separate storm sewer receiving the discharge, upon the presentation of credentials and other documents as may be required by law, to:

1. Enter upon the permittee's premises where a regulated facility or activity is located or conducted or where records must be kept under the conditions of this permit;
2. Have access to and copy at reasonable times, any records that must be kept under the conditions of this permit: and
3. Inspect at reasonable times any facilities or equipment (including monitoring and control equipment).

**R. Permit Actions** - At the Department's sole discretion, this permit may, at any time, be modified, revoked or renewed. The filing of a request by the permittee for a permit modification, reissuance, termination, or a notification of planned changes or anticipated noncompliance does not stay any permit condition.

**S. Definitions** - Definitions are included in Appendix A of this permit. Additional definitions are provided within the Part VIII industrial sectors for definitions that are specific to those industries.

## **Part VI. REOPENER CLAUSE**

A. If there is evidence indicating potential or realized impacts on water quality due to any stormwater discharge associated with industrial activity covered by this permit, the owner or operator of such discharge may be required to obtain an individual permit or an alternative general permit in accordance with Part VI.N (requiring an individual permit or alternative general permit) of this permit or the permit may be modified to include different limitations and/or requirements.

B. Permit modification or revocation will be conducted according to 6 NYCRR Part 621 and 6 NYCRR Part 750-1.18.

## **Part VII. TERMINATION OR TRANSFER OF COVERAGE**

A. **Notice of Intent or Termination (NOIT) Form** - Where all stormwater discharges associated with industrial activity that are authorized by this permit are eliminated, or where the owner or operator of the stormwater discharges associated with industrial activity at a facility changes, the owner or operator of the facility may submit a Notice of Intent or Termination (NOIT) form that is signed in accordance with Part V.H. (signatory requirements) of this permit. Additionally, the owner or operator must notify the new owner or operator of the possible requirement to submit a new NOIT in order to obtain coverage under this permit. The terminating NOIT should include the following information, as appropriate, in order to define the activity for which permit authority under this general permit to discharge stormwater is terminated:

1. Name, mailing address, and location of the facility for which the notification is submitted. Where a street address for the site is not available, the location of the approximate center of the site must be described in terms of the latitude and longitude of the facility to the nearest 15 seconds;
2. The name, address and telephone number of the owner or operator addressed by the NOIT form;
3. The SPDES permit number for the stormwater discharge associated with industrial activity identified by the NOIT;
4. An indication of whether the stormwater discharges associated with industrial activity have been eliminated or the owner or operator of the discharges has changed; and
5. The certification signed in accordance with Part V.H (signatory requirements) of this permit.



**B. Addresses**

All Notices of Intent or Termination (NOIT) forms are to be sent, using the form provided by the Department (or a photocopy thereof), to the address indicated on the form which (as of the issuance date of this permit) is:

Industrial Stormwater General Permit Coordinator  
NYS DEC, Division of Water  
Bureau of Water Permits  
625 Broadway  
Albany, NY 12233-3505

**PART VIII. SECTOR SPECIFIC PERMIT REQUIREMENTS**

The permittee must comply with the additional requirements of Part VIII that apply to the specific industrial activity located at the permittee's facility. These requirements are in addition to the general requirements specified in the previous sections of this permit. The industry-specific requirements are broken down into sections referred to as industrial sectors A through AE.

If the facility has more than one industrial activity occurring on-site, those industrial activities are considered to be co-located. Stormwater discharges from co-located industrial activities are authorized by this permit, provided that the permittee complies with any and all of the requirements applicable to each industrial activity at the facility.

## **Sector A - Timber Products**

1. **Discharges Covered Under This Section** - The requirements listed under this section apply to stormwater discharges associated with industrial activity from facilities generally classified under SIC Major Group 24 that are engaged in the following activities: cutting timber and pulpwood (those that have log storage or handling areas), mills, including merchant, lath, shingle, cooperage stock, planing, plywood and veneer; producing lumber and wood materials; wood preserving; manufacturing wood buildings or mobile homes; and manufacturing finished articles made entirely of wood or related materials, except for wood kitchen cabinet manufacturers (SIC Code 2434), which are addressed under Sector W. The requirements of this section do not apply to active timber harvesting sites including the felling, skidding, preparation, loading and the incidental stacking and temporary storage of harvested timber on the harvest site prior to its initial transport to intermediate storage areas or other processing areas.

### **2. Special Conditions**

a. **Prohibition of non-stormwater discharges** - Discharges of stormwater from areas where there may be contact with chemical formulations sprayed to provide surface protection are not authorized by this permit. These discharges must be covered under a separate SPDES permit.

b. **Authorized non-stormwater discharges** - In addition to the discharges described in Paragraph I.D.1, the following non-stormwater discharges may be authorized by this permit provided the non-stormwater component of the discharge is in compliance with Paragraph III.C.6.(stormwater controls): discharges from the spray down of lumber and wood product storage yards where no chemical additives are used in the spray down waters and no chemicals are applied to the wood during storage.

3. **Stormwater Pollution Prevention Plan Requirements** - In addition to the requirements of Part III, the SWPPP shall include, at a minimum, the following items.

#### **a. Site description**

(1) **Site map** - The site map shall identify where any of the following may be exposed to precipitation/surface runoff: processing areas; treatment chemical storage areas; treated wood and residue storage areas; wet decking areas; dry decking areas; untreated wood and residue storage areas; and treatment equipment storage areas.

(2) **Summary of potential pollutant sources** - Where information is available, facilities that have used chlorophenolic, creosote, or chromium-copper-arsenic formulations for wood surface protection or wood preserving activities on-site in the past shall identify in the inventory the following: areas where contaminated soils, treatment equipment,

and stored materials still remain, and the management practices employed to minimize the contact of these materials with stormwater runoff.

b. Stormwater controls - The description of stormwater management controls shall address the following areas of the site: log, lumber and other wood product storage areas; residue storage areas; loading and unloading areas; material handling areas; chemical storage areas; and equipment/vehicle maintenance, storage and repair areas. Facilities that surface protect and/or preserve wood products shall address specific BMPs for wood surface protection and preserving activities. The SWPPP shall address the following minimum components:

(1) Good housekeeping - Good housekeeping measures in storage areas, loading and unloading areas, and material handling areas should be designed to:

- (a) Limit the discharge of wood debris;
- (b) Minimize the leachate generated from decaying wood materials; and
- (c) Minimize the generation of dust.

(2) Routine facility inspections - Inspections at processing areas, transport areas, and treated wood storage areas of facilities performing wood surface protection and preservation activities should be performed monthly to assess the usefulness of practices in minimizing the deposit of treatment chemicals on unprotected soils and in areas that will come in contact with stormwater discharges.

#### 4. Numeric Effluent Limitations

a. The following limitations shall be met by existing and new facilities:

Wet deck storage area runoff - Non-stormwater discharges from areas used for the storage of logs where water, without chemical additives, is intentionally sprayed or deposited on logs to deter decay or infestation by insects are required to meet the following effluent limitations:

Table VIII-A-1.  
Sector A - Numeric Effluent Limitations

Parameter	Effluent Limitations
<b>Wet Decking Discharges at Log Storage and Handling Areas (SIC 2411) Subject to the Point Source Category Provisions of 40CFR Part 429 Subpart I.</b>	
pH	6.0 - 9.0 s.u.
Debris (woody material such as bark, twigs, branches, heartwood, or sapwood)	No discharge of debris that will not pass through a 2.54 cm (1") diameter round opening.

**5. Benchmark Monitoring and Reporting Requirements** - Timber product facilities are required to monitor their stormwater discharges for the pollutants of concern listed in the appropriate section of Table VIII-A-2.

Table VIII-A-2.  
Sector A - Benchmark Monitoring Requirements

Pollutants of Concern	Analytical Method	Benchmark Monitoring Cut-Off Concentration
<b>General Sawmills and Planing Mills (SIC 2421)</b>		
Chemical Oxygen Demand (COD)	EPA 410.4	120 mg/l
Total Suspended Solids (TSS)	EPA 160.2	100 mg/L
Total Nitrogen (TN) *	EPA 350.1, 351.2, 353.2	6 mg/L
Total Phosphorus	EPA 365.1	2 mg/L
Total Recoverable Zinc	EPA 200.7	120 ug/L
<b>Wood Preserving Facilities (SIC 2491)</b>		
Total Recoverable Arsenic	EPA 200.7	168 ug/L
Total Recoverable Chromium	EPA 200.7	1.8 mg/L
Total Recoverable Copper	EPA 200.7	64 ug/L
<b>Log Storage and Handling Facilities (SIC 2411)</b>		
Total Suspended Solids (TSS)	EPA 160.2	100 mg/L
<b>Hardwood Dimension and Flooring Mills; Special Products Sawmills, not elsewhere classified; Millwork, Veneer, Plywood and Structural Wood; Wood Containers; Wood Buildings and Mobile Homes; Reconstituted Wood Products; and Wood Products Facilities not elsewhere classified (SIC Codes 2426, 2429, 2431-2439 (except 2434), 2448, 2449, 2451, 2452, 2493, and 2499).</b>		
Chemical Oxygen Demand (COD)	EPA 410.4	120 mg/l
Total Suspended Solids (TSS)	EPA 160.2	100 mg/L

\* Total Nitrogen is calculated as the sum of ammonia, nitrate-nitrite and organic nitrogen.

## **Sector B - Paper and Allied Products Manufacturing**

1. **Discharges Covered Under This Section** - The requirements listed under this section apply to stormwater discharges associated with industrial activity from facilities classified as paper and allied products manufacturing under SIC Major Group 26 that are engaged in the following activities: the manufacture of pulps from wood and other cellulose fibers and from rags; the manufacture of paper and paperboard into converted products, such as paper coated off the paper machine, paper bags, paper boxes and envelopes; and the manufacture of bags of plastic film and sheet.

2. **Benchmark Monitoring and Reporting Requirements** - Paperboard mills are required to monitor their stormwater discharges for the pollutants of concern listed in Table VIII-B-1.

Table VIII-B-1.  
Sector B - Benchmark Monitoring Requirements

Pollutants of Concern	Analytical Method	Benchmark Monitoring Cut-Off Concentration
<b>Paperboard Mills (SIC 2631)</b>		
Chemical Oxygen Demand (COD)	EPA 410.4	120 mg/L

## **Sector C - Chemical and Allied Products Manufacturing**

**1. Discharges Covered Under This Section** - The requirements listed under this section apply to stormwater discharges associated with industrial activity from facilities engaged in manufacturing the following products and generally described by the SIC code shown:

- a. Basic industrial inorganic chemicals (including SIC Code 281);
- b. Plastic materials and synthetic resins, synthetic rubbers, and cellulosic and other manmade fibers, except glass (including SIC Code 282);
- c. Medicinal chemicals and pharmaceutical products, including the grading, grinding and milling of botanicals (including SIC Code 283);
- d. Soap and other detergents, including facilities producing glycerin from vegetable and animal fats and oils; specialty cleaning, polishing, and sanitation preparations; surface active preparations used as emulsifiers, wetting agents, and finishing agents, including sulfonated oils; and perfumes, cosmetics, and other toilet preparations (including SIC Code 284);
- e. Paints (in paste and ready-mixed form); varnishes; lacquers; enamels and shellac; putties, wood fillers, and sealers; paint and varnish removers; paint brush cleaners; and allied paint products (including SIC Code 285);
- f. Industrial organic chemicals (including SIC Code 286);
- g. Nitrogenous and phosphatic basic fertilizers, mixed fertilizer, pesticides, and other agricultural chemicals (including SIC Code 287);
- h. Industrial and household adhesives, glues, caulking compounds, sealants, and linoleum, tile, and rubber cements from vegetable, animal, or synthetic plastics materials; explosives; printing ink, including gravure ink, screen process and lithographic inks ; miscellaneous chemical preparations, such as fatty acids, essential oils, gelatin (except vegetable), sizes, bluing, laundry soaps, and writing and stamp pad ink; industrial compounds, such as boiler and heat insulating compounds; and chemical supplies for foundries (including SIC Code 289); and
- i. Ink and paints, including china painting enamels, India ink, drawing ink, platinum paints for burnt wood or leather work, paints for china painting, artists' paints and artists' water colors (SIC Code 3952, limited to those listed; for others in SIC Code 3952 not listed above, see Sector Y).

## **2. Special Conditions**

a. **Prohibition of non-stormwater discharges** - In addition to the general prohibition of non-stormwater discharges in Paragraph I.D.1, the following discharges not covered by this permit include, but are not limited to: inks, paints, or substances (hazardous, nonhazardous, etc.) resulting from an on-site spill, including materials collected in drip pans; washwaters from material handling and processing areas; or washwaters from drum, tank, or container rinsing and cleaning.

3. **Stormwater Pollution Prevention Plan Requirements** - In addition to the requirements of Part III, the plan shall include, at a minimum, the following items.

### **a. Site description**

(1) **Site map** - The site map shall identify where any of the following may be exposed to precipitation/surface runoff: processing and storage areas; access roads, rail cars and tracks; areas where substances are transferred in bulk; and operating machinery.

(2) **Summary of potential pollutant sources** - A description of the following sources and activities that have potential pollutants associated with them: loading, unloading and transfer of chemicals; outdoor storage of salt, pallets, coal, drums, containers, fuels; fueling stations; vehicle and equipment maintenance/cleaning areas; areas where the treatment, storage or disposal (on-site or off-site) of waste/wastewater occur; storage tanks and other containers; processing and storage areas; access roads, rail cars and tracks; areas where the transfer of substances in bulk occurs; and areas where machinery operates.

### **b. Stormwater controls**

(1) **Good housekeeping** - At a minimum, the SWPPP shall include:

(a) A schedule for regular pickup and disposal of garbage and waste materials, or adopt other appropriate measures to reduce the potential for the discharge of stormwater that has come into contact with garbage or waste materials; and

(b) Routine inspections of the condition of drums, tanks and containers for potential leaks.

4. **Numeric Effluent Limitations** - The following effluent limitations shall be met by existing and new discharges with phosphate fertilizer manufacturing runoff. The provisions of this paragraph are applicable to stormwater discharges from the phosphate subcategory of the fertilizer manufacturing point source category (40 CFR 418.10, Subpart A). The term contaminated stormwater runoff shall mean precipitation runoff, that during manufacturing or processing, comes into contact with any raw materials, intermediate product, finished product,

by-products or waste product. The concentration of pollutants in stormwater discharges shall not exceed the effluent limitations in Table VIII-C-1.

Table VIII-C-1.  
Sector C - Numeric Effluent Limitations

Parameter	Effluent Limitations	
	Daily Maximum	30-day Average
<b>Phosphate Subcategory of the Fertilizer Manufacturing Point Source Category (40 CFR 418.10) - applies to precipitation runoff that, during manufacturing or processing, comes into contact with any raw materials, intermediate product, finished product, by-products or waste product (SIC 2874)</b>		
Total Phosphorus (as P)	105 mg/L	35 mg/L
Fluoride	75 mg/L	25 mg/L

5. **Benchmark Monitoring and Reporting Requirements** - Agricultural chemical manufacturing facilities; industrial inorganic chemical facilities; soaps, detergents, cosmetics, and perfume manufacturing facilities; and plastics, synthetics, and resin manufacturing facilities are required to monitor their stormwater discharges for the pollutants of concern listed in Table VIII-C-2 below.

Table VIII-C-2.  
Sector C - Benchmark Monitoring Requirements

Pollutants of Concern	Analytical Method	Benchmark Monitoring Cut-Off Concentration
<b>Agricultural Chemicals (SIC 2873-2879)</b>		
Total Nitrogen (TN)	EPA 350.1, 351.2, 353.2	6 mg/L
Total Recoverable Iron	EPA 200.7	1 mg/L
Total Recoverable Lead	EPA 200.7	82 ug/L
Total Recoverable Zinc	EPA 200.7	120 ug/L
Total Phosphorus	EPA 365.1	2 mg/L
<b>Industrial Inorganic Chemicals (SIC 2812-2819)</b>		
Total Recoverable Aluminum	EPA 200.7	750 ug/L
Total Recoverable Iron	EPA 200.7	1 mg/L
Total Nitrogen (TN)	EPA 350.1, 351.2, 353.2	6 mg/L
<b>Soaps, Detergents, Cosmetics, and Perfumes (SIC 2841-2844)</b>		
Total Nitrogen (TN)	EPA 350.1, 351.2, 353.2	6 mg/L
Total Recoverable Zinc	EPA 200.7	120 ug/L
<b>Plastics, Synthetics, and Resins (SIC 2821-2824)</b>		
Total Recoverable Zinc	EPA 200.7	120 ug/L

\* Total Nitrogen is calculated as the sum of ammonia, nitrate-nitrite and organic nitrogen.



## **Sector D - Asphalt Paving and Roofing Materials and Lubricant Manufacturers**

1. **Discharges Covered Under This Section** - The requirements listed under this section apply to stormwater discharges associated with industrial activity from facilities engaged in the following activities: manufacturing asphalt paving and roofing materials, including those facilities commonly identified by SIC Codes 2951 and 2952; portable asphalt plants (also commonly identified by SIC Code 2951); and manufacturing miscellaneous products of petroleum and coal, including those facilities classified as SIC Code 2992 and 2999.

2. **Limitations on Coverage** - The following stormwater discharges associated with industrial activity are not authorized by this section of the permit:

- a. Stormwater discharges from petroleum refining facilities, including those that manufacture asphalt or asphalt products that are classified as SIC Code 2911;
- b. Stormwater discharges from oil recycling facilities; and
- c. Stormwater discharges associated with fats and oils rendering.

3. **Stormwater Pollution Prevention Plan Requirements** - In addition to the requirements of Part III, the plan shall include monthly routine facility inspections as part of the maintenance program at material storage and handling areas, liquid storage tanks, hoppers or silos, vehicle and equipment maintenance, cleaning, and fueling areas, material handling vehicles, equipment and processing areas.

4. **Numeric Effluent Limitations** - Discharges from areas where production of asphalt paving and roofing emulsions occurs may not exceed the limitations in Table VIII-D-1.

Table VIII-D-1.  
Sector D - Numeric Effluent Limitations

Parameter	Effluent Limitations	
	Daily Maximum	30-day Average
<b>Discharges from areas where production of asphalt paving and roofing emulsions occurs (SIC 2951, 2952) Subject to the Point Source Category Provisions of 40 CFR Part 443 Subpart A.</b>		
Total Suspended Solids (TSS)	23 mg/L	15 mg/L
Oil and Grease	15 mg/L	10 mg/L
pH	6.0 - 9.0 s.u.	

5. **Benchmark Monitoring and Reporting Requirements** - Asphalt paving and roofing materials manufacturing facilities are required to monitor their stormwater discharges for the pollutant of concern listed in Table VIII-D-2.

Table VIII-D-2.  
Sector D - Benchmark Monitoring Requirements

Pollutants of Concern	Analytical Method	Benchmark Monitoring Cut-Off Concentration
<b>Asphalt Paving and Roofing Materials (SIC 2951, 2952)</b>		
Total Suspended Solids (TSS)	EPA 160.2	100 mg/L

## **Sector E - Glass, Clay, Cement, Concrete, and Gypsum Products**

1. **Discharges Covered Under This Section** - The requirements listed under this section apply to stormwater discharges associated with industrial activity from facilities generally classified under SIC Major Group 32 that are engaged in either manufacturing the following products or performing the following activities: flat, pressed, or blown glass or glass containers; hydraulic cement; clay products including tile and brick; pottery and porcelain electrical supplies; concrete products; gypsum products; nonclay refractories; minerals and earths, ground or otherwise treated; lime manufacturing; cut stone and stone products; asbestos products; and mineral wool and mineral wool insulation products.

2. **Stormwater Pollution Prevention Plan Requirements** - In addition to the requirements of Part III, the plan shall include, at a minimum, the following items:

a. **Site description and site map** - The site map shall identify the locations of the following, if applicable: bag house or other dust control device; recycle/sedimentation pond, clarifier or other device used for the treatment of process wastewater and the areas that drain to the treatment device.

b. **Stormwater controls**

(1) **Good housekeeping**

(a) Facilities shall prevent or minimize the discharge of: spilled cement; aggregate (including sand or gravel); kiln dust; fly ash; settled dust; and other significant materials in stormwater from paved portions of the site that are exposed to stormwater. Measures used to minimize the presence of these materials may include regular sweeping, or other equivalent measures. The plan shall indicate the frequency of sweeping or equivalent measures. The frequency shall be determined based upon consideration of the amount of industrial activity occurring in the area and frequency of precipitation, but shall not be less than once per week if cement, aggregate, kiln dust; fly ash, or settled dust are being handled or processed.

(b) Facilities shall prevent the exposure of fine granular solids (such as cement, kiln dust, etc.) to stormwater. Where practicable, these materials shall be stored in enclosed silos or hoppers, buildings, or under other covering.

(2) **Routine facility inspections** - The inspection shall take place while the facility is in operation and shall include all of the following areas that are exposed to stormwater: material handling areas, aboveground storage tanks, hoppers or silos, dust collection/containment systems, truck wash down/equipment cleaning areas.

(3) Certification of non-stormwater discharges - Facilities engaged in production of ready-mix concrete, concrete block, brick or similar products shall include in the certification a description of measures that ensure that process wastewater that results from washing of trucks, mixers, transport buckets, forms or other equipment are discharged in accordance with a separate SPDES permit or are recycled.

3. **Numeric Effluent Limitations** - The following limitations shall be met by existing and new facilities: Cement manufacturing facility, material storage runoff. Any discharge composed of runoff that derives from the storage of materials including raw materials, intermediate products, finished products, and waste materials that are used in or derived from the manufacture of cement shall not exceed the limitations in Table VIII-E-1. Runoff from the storage piles shall not be diluted with other stormwater runoff or flows to meet these limitations. Any untreated overflow from facilities designed, constructed and operated to treat the volume of material storage pile runoff that is associated with a 10-year, 24-hour rainfall event shall not be subject to the TSS or pH limitations. Facilities subject to these numeric effluent limitations must be in compliance with these limits upon commencement of coverage and for the entire term of this permit.

Table VIII-E-1.  
Sector E - Numeric Effluent Limitations

Parameter	Effluent Limitations	
	Daily Maximum	30-day Average
<b>Cement Manufacturing Facility, Material Storage Runoff: Any discharge composed of runoff that derives from the storage of materials including raw materials, intermediate products, finished products, and waste materials that are used in or derived from the manufacture of cement. Subject to the Point Source Category Provisions of 40 CFR Part 411 Subpart C.</b>		
Total Suspended Solids (TSS)	50 mg/L	NA
pH	6.0 - 9.0 s.u.	

4. **Benchmark Monitoring and Reporting Requirements** - Clay product manufacturers (SIC 3245-3259, SIC 3261-3269) and concrete and gypsum product manufacturers (SIC 3271-3275) are required to monitor their stormwater discharges for the pollutants of concern listed in Table VIII-E-2.

Table VIII-E-2.  
Sector E - Benchmark Monitoring Requirements

Pollutants of Concern	Analytical Method	Benchmark Monitoring Cut-Off Concentration
<b>Clay Product Manufacturers (SIC 3245-3259, 3261-3269)</b>		
Total Recoverable Aluminum	EPA 200.7	750 ug/L
<b>Concrete and Gypsum Product Manufacturers (SIC 3271-3275)</b>		
Total Suspended Solids (TSS)	EPA 160.2	100 mg/L
pH	EPA 150.1	6.0 - 9.0 s.u.
Total Recoverable Iron	EPA 200.7	1 mg/L

## **Sector F - Primary Metals**

1. **Discharges Covered Under This Section** - The requirements listed under this section apply to stormwater discharges associated with industrial activity from the following types of facilities in the primary metal industry, and generally described by the SIC code shown:

- a. Steel works, blast furnaces, and rolling and finishing mills, including: steel wire drawing and steel nails and spikes; cold-rolled steel sheet, strip, and bars; and steel pipes and tubes (SIC Code 331);
- b. Iron and steel foundries, including: gray and ductile iron, malleable iron, steel investment, and steel foundries not elsewhere classified (SIC Code 332);
- c. Primary smelting and refining of nonferrous metals, including: primary smelting and refining of copper, and primary production of aluminum (SIC Code 333);
- d. Secondary smelting and refining of nonferrous metals (SIC Code 334);
- e. Rolling, drawing, and extruding of nonferrous metals, including: rolling, drawing, and extruding of copper; rolling, drawing and extruding of nonferrous metals except copper and aluminum; and drawing and insulating of nonferrous wire (SIC Code 335);
- f. Nonferrous foundries (castings), including: aluminum die-castings, nonferrous die-castings, except aluminum, aluminum foundries, copper foundries, and nonferrous foundries, except copper and aluminum (SIC Code 336); and
- g. Miscellaneous primary metal products, not elsewhere classified, including: metal heat treating, and primary metal products, not elsewhere classified (SIC Code 339).

Activities covered include, but are not limited to, stormwater discharges associated with coking operations, sintering plants, blast furnaces, smelting operations, rolling mills, casting operations, heat treating, extruding, drawing, or forging of all types of ferrous and nonferrous metals, scrap, and ore.

2. **Stormwater Pollution Prevention Plan Requirements** - In addition to the requirements of Part III, the plan shall include, at a minimum, the following items.

a. **Site description**

(1) **Site map** - The site map shall identify where any of the following activities may be exposed to precipitation/surface runoff: storage or disposal of wastes such as spent solvents/baths, sand, slag/dross; liquid storage tanks/drums; processing areas including pollution control equipment (e.g., baghouses); and storage areas of raw materials such as coal, coke, scrap, sand, fluxes, refractories, or metal in any form. In addition, indicate sources where an accumulation of significant amounts of particulate matter

could occur from such sources as furnace or oven emissions, losses from coal/coke handling operations, etc., and which could result in a discharge of pollutants to surface waters.

(2) Inventory of exposed materials - The inventory of materials handled at the site that potentially may be exposed to precipitation/runoff should include areas where deposition of particulate matter from process air emissions or losses during material handling activities are possible.

b. Stormwater controls

(1) Good housekeeping - The SWPPP shall consider implementation of the following measures, or equivalent measures, where applicable.

(a) Establishment of a cleaning/maintenance program for all impervious areas of the facility where particulate matter, dust, or debris may accumulate, especially areas where material loading/unloading, storage, handling, and processing occur.

(b) The paving of areas where vehicle traffic or material storage occur, but where vegetative or other stabilization methods are not practicable. Sweeping programs shall be instituted in these areas as well.

(c) For unstabilized areas of the facility where sweeping is not practical, the permittee shall consider using stormwater management devices such as sediment traps, vegetative buffer strips, filter fabric fence, sediment filtering boom, gravel outlet protection, or other equivalent measures, that effectively trap or remove sediment.

(2) Routine facility inspections - Inspections shall be conducted at least quarterly, and shall address all potential sources of pollutants, including (if applicable):

(a) Air pollution control equipment (e.g., baghouses, electrostatic precipitators, scrubbers, and cyclones) shall be inspected for any signs of degradation (e.g., leaks, corrosion, or improper operation) that could limit their efficiency and lead to excessive emissions. The permittee shall consider monitoring air flow at inlets/outlets, or equivalent measures, to check for leaks (e.g., particulate deposition) or blockage in ducts;

(b) All process or material handling equipment (e.g., conveyors, cranes, and vehicles) shall be inspected for leaks, drips, or the potential loss of materials; and

(c) Material storage areas (e.g., piles, bins or hoppers for storing coke, coal, scrap, or slag, as well as chemicals stored in tanks/drums) shall be examined for signs of material losses due to wind or stormwater runoff.

3. **Benchmark Monitoring and Reporting Requirements** - Primary metals facilities are required to monitor their stormwater discharges for the pollutants of concern listed in Table VIII-F-1 below.

Table VIII-F-1.  
Sector F - Benchmark Monitoring Requirements

Pollutants of Concern	Analytical Method	Benchmark Monitoring Cut-Off Concentration
<b>Steel Works, Blast Furnaces, and Rolling and Finishing Mills (SIC 3312-3317)</b>		
Total Recoverable Aluminum	EPA 200.7	750 ug/L
Total Recoverable Zinc	EPA 200.7	120 ug/L
<b>Iron and Steel Foundries (SIC 3321-3325)</b>		
Total Recoverable Aluminum	EPA 200.7	750 ug/L
Total Suspended Solids (TSS)	EPA 160.2	100 mg/L
Total Recoverable Copper	EPA 200.7	64 ug/L
Total Recoverable Iron	EPA 200.7	1 mg/L
Total Recoverable Zinc	EPA 200.7	120 ug/L
<b>Rolling, Drawing, and Extruding of Nonferrous Metals (SIC 3351-3357)</b>		
Total Recoverable Copper	EPA 200.7	64 ug/L
Total Recoverable Zinc	EPA 200.7	120 ug/L
<b>Nonferrous Foundries (SIC 3363-3369)</b>		
Total Recoverable Copper	EPA 200.7	64 ug/L
Total Recoverable Zinc	EPA 200.7	120 ug/L

## **Sector G - Metal Mining (Ore Mining and Dressing)**

**1. Discharges Covered Under This Section** - The requirements listed under this section apply to stormwater discharges associated with industrial activity from active, temporarily inactive and inactive metal mining and ore dressing facilities including mines abandoned on federal lands, as classified under SIC Major Group 10. Coverage is required for facilities that discharge stormwater that has come into contact with, or is contaminated by, any overburden, raw material, intermediate product, finished product, byproduct, or waste product located on the site of the operation. SIC Major Group 10 includes establishments primarily engaged in mining of ores, developing mines, or exploring for metallic minerals (ores) and also includes ore dressing and beneficiating operations, whether performed at co-located, dedicated mills or at separate mills, such as custom mills. For the purposes of this section, the term "metal mining" includes any of the separate activities listed above. Covered discharges include:

- a. All stormwater discharges from inactive metal mining facilities; and
- b. Stormwater discharges from the following areas of active and temporarily inactive metal mining facilities: waste rock/overburden piles if composed entirely of stormwater and not combining with mine drainage; topsoil piles; off-site haul/access roads; on-site haul/access roads constructed of waste rock/overburden if composed entirely of stormwater and not combining with mine drainage; on-site haul/access roads not constructed of waste rock/overburden/spent ore except if mine drainage is used for dust control; runoff from tailings dams/dikes when not constructed of waste rock/tailings and no process fluids are present; runoff from tailings dams/dikes when constructed of waste rock/tailings and no process fluids are present if composed entirely of stormwater and not combining with mine drainage; concentration building if no contact with material piles; mill site if no contact with material piles; office/administrative building and housing if mixed with stormwater from industrial area; chemical storage area; docking facility if no excessive contact with waste product that would otherwise constitute mine drainage; explosive storage; fuel storage; vehicle/equipment maintenance area/building; parking areas (if necessary); power plant; truck wash areas if no excessive contact with waste product that would otherwise constitute mine drainage; unreclaimed, disturbed areas outside of active mining area; reclaimed areas released from reclamation bonds prior to December 17, 1990; and partially/inadequately reclaimed areas or areas not released from reclamation bonds.

## **2. Limitations on Coverage**

- a. Stormwater discharges from active metal mining facilities that are subject to the effluent limitation guidelines for the Ore Mining and Dressing Point Source Category (40 CFR Part 440) are not authorized by this permit. Note: Discharges that come in contact with overburden/waste rock are subject to 40 CFR Part 440, providing: the discharges drain to a point source (either naturally or as a result of intentional diversion), and they combine with mine drainage that is otherwise regulated under 40 CFR Part 440. Discharges from overburden/waste rock can be covered under this permit if they are composed entirely of



stormwater and do not combine with sources of mine drainage that are subject to 40 CFR Part 440 and meet other eligibility criteria in Paragraph I.C.2.

### 3. Special Conditions

a. Prohibition of non-stormwater discharges - In addition to the general prohibition of non-stormwater discharges in Paragraph I.D.1, the following discharges not covered by this permit include, but are not limited to: adit drainage or contaminated springs or seeps.

b. Stormwater discharges from construction activities - A comprehensive Stormwater Pollution Prevention Plan (SWPPP) addressing the storm water run-on and run-off control systems needed during the mines construction, operation and reclamation phases must be prepared prior to the commencement of any construction activity that will result in a land disturbance of one or more acres of land. The plan must be prepared in accordance with the New York Standards and Specifications for Erosion and Sediment Control dated August 2005, or the most current version or its successor. If alternative erosion and sedimentation controls are proposed, the owner or operator must demonstrate equivalence to this technical standard.

c. The SWPPP must be kept current and should address effective stormwater controls for all appurtenances and components associated with the mine, including but not limited to: access roads, haul roads, paved areas, associated buildings and structures, perimeter ditches, and berms.

### 4. Special Definitions - The following definitions are only for this section of the general permit:

*"Active metal mining facility"* means a place where work or other activity related to the extraction, removal, or recovery of metal ore is being conducted. For surface mines, this definition does not include any land where grading has returned the earth to a desired contour and reclamation has begun.

*"Active phase"* means activities including each step from extraction through production of a salable product.

*"Exploration and construction phase"* entails exploration and land disturbance activities to determine the financial viability of a site. Construction includes the building of site access roads and removal of overburden and waste rock to expose mineable minerals.

*"Final Stabilization"* means that all soil-disturbing activities at the site have been completed and a uniform, perennial vegetative cover with a density of eighty (80) percent has been established or equivalent stabilization measures (such as the use of permanent landscape mulches, riprap, or washed/crushed stone) have been employed on all unpaved areas and areas not covered by permanent structures.

*"Inactive metal mining facility"* means a site or portion of a site where metal mining and/or milling occurred in the past but is not an active facility as defined above, and where the inactive portion is not covered by an active mining permit issued by the applicable (federal or state) governmental agency.

*"Mining operation"* typically consists of three phases, any one of which individually qualifies as a "mining activity." The phases are the exploration and construction phase, the active phase, and the reclamation phase.

*"Reclamation phase"* means activities intended to return the land to a pre-approved, post-mining land use.

*"Temporarily inactive metal mining facility"* means a site or portion of a site where metal mining and/or milling occurred in the past but currently are not being actively undertaken, and the facility is covered by an active mining permit issued by the applicable (federal or state) government agency.

**5. Stormwater Pollution Prevention Plan Requirements** - In addition to the requirements of Part III, the plan shall include, at a minimum, the following items.

a. SWPPP requirements for active and temporarily inactive metal mining facilities.

(1) Site description

(a) Activities at the facility - A description of the mining and associated activities taking place at the site that can potentially affect stormwater discharges covered by this permit. The description shall include the total acreage within the mine site; an estimate of the number of acres of disturbed land; an estimate of the total amount of land proposed to be disturbed throughout the life of the mine and a general description of the location of the site relative to major transportation routes and communities.

(b) Site map - The site map shall identify the locations of the following, as appropriate: mining/milling site boundaries; access and haul roads; an outline of the drainage areas of each stormwater outfall within the facility, and an indication of the types of discharges from the drainage areas; equipment storage, fueling and maintenance areas; materials handling areas; outdoor manufacturing, storage or material disposal areas; storage areas for chemicals and explosives; areas used for storage of overburden, materials, soils or wastes; location of mine drainage (where water leaves mine) or any other process water; tailings piles/ponds, both proposed and existing; heap leach pads; points of discharge from the property for mine drainage/process water; surface waters; and boundary of tributary areas that are subject to effluent limitations guidelines.

(2) Summary of potential pollutant sources - For each area of the mine/mill site where stormwater discharges associated with industrial activities occur, the types of pollutants likely to be present in significant amounts must be identified (e.g., heavy metals, sediment). The following factors must be considered: the mineralogy of the ore and waste rock (e.g., acid forming); toxicity and quantity of chemicals used, produced or discharged; the likelihood, if any, of contact with stormwater; vegetation of site; history of reportable leaks/spills of toxic or hazardous pollutants. A summary of any existing ore or waste rock/overburden characterization data and test results for potential generation of acid rock shall also be included. If the ore or waste rock/overburden characterization data are updated due to a change in the ore type being mined, the SWPPP shall be updated with the new data.

(3) Stormwater controls

(a) Nonstructural BMPs

(i) Routine facility inspections - Active mining sites must be inspected at least monthly. Temporarily inactive sites must be inspected at least quarterly unless adverse weather conditions make the site inaccessible.

(ii) Employee training - Employee training shall be conducted at least annually at active mining and temporarily inactive sites.

(b) Structural BMPs - Each of the following BMPs shall be considered in the SWPPP. The potential pollutants identified in subpart 5.a.(2) above shall determine the priority and appropriateness of the BMPs selected. If it is determined that one or more of these BMPs are not appropriate for the facility, the plan must explain why it is not appropriate. If BMPs are implemented or planned but are not listed here (e.g., substituting a less toxic chemical for a more toxic one), descriptions of them must be included in the SWPPP.

(i) Sediment and erosion control - The measures to consider include: diversion of flow away from areas susceptible to erosion (measures such as interceptor dikes and swales, diversion dikes, curbs and berms); stabilization methods to prevent or minimize erosion (such as temporary or permanent seeding; vegetative buffer strips; protection of trees; topsoiling; soil conditioning; contouring; mulching; geotextiles (matting, netting, or blankets); riprap; gabions; and retaining walls); and structural methods for controlling sediment (such as check dams; rock outlet protection; level spreaders; gradient terraces; silt fences; gravel or stone filter berms; brush barriers; sediment traps; grass swales; pipe slope drains; earth dikes; other controls such as entrance stabilization, waterway crossings or wind breaks; or other equivalent measures). The design, installation, maintenance and repair of erosion and sediment controls shall conform to the New York Standards and Specifications for Erosion and Sediment Control dated August 2005, or the most current

version or its successor. If alternative erosion controls are proposed, the owner or operator must demonstrate equivalence to this technical standard.

(ii) Stormwater diversion - A description of how and where stormwater will be diverted away from potential pollutant sources to prevent stormwater contamination. BMP options may include the following: interceptor dikes and swales; diversion dikes, curbs and berms; pipe slope drains; subsurface drains; drainage/stormwater conveyance systems (channels or gutters, open top box culverts and waterbars; rolling dips and road sloping; roadway surface water deflector and culverts); or equivalent measures.

(iii) Management of runoff - The potential pollutant sources given in Paragraph VIII.G.5.a(2) must be considered when determining reasonable and appropriate measures for managing runoff.

(iv) Capping - Where capping of a potential stormwater pollution source is necessary, the source being capped and materials and procedures used to cap the contaminant source must be identified.

(v) Treatment - If treatment of a stormwater discharge is necessary to protect water quality, include a description of the type and location of stormwater treatment that will be used. Stormwater treatments include the following: chemical or physical systems; oil/water separators; artificial wetlands; etc.

(vi) Certification of discharge testing - The permittee must test or evaluate for the presence of specific mining-related non-stormwater discharges such as seeps or adit discharges or discharges subject to effluent limitations guidelines, such as mine drainage or process water. Alternatively (if applicable), the permittee may certify in the SWPPP that a particular discharge comprised of commingled stormwater and non-stormwater is covered under a separate SPDES permit; and that permit subjects the non-stormwater portion to effluent limitations prior to any commingling. This certification shall identify the non-stormwater discharges, the applicable SPDES permit(s), the effluent limitations placed on the non-stormwater discharge by the permit(s), and the points at which the limitations are applied.

b. SWPPP requirements for inactive metal mining facilities

(1) Site description

(a) Activities at the facility - The SWPPP shall briefly describe the mining and associated activities that took place at the site that can potentially affect the stormwater discharges covered by this permit. The following must be included: approximate dates of operation; total acreage within the mine and/or processing

site; estimate of acres of disturbed earth; activities currently occurring on-site (e.g., reclamation); a general description of site location with respect to transportation routes and communities.

(b) Site map - The site map shall identify the locations of the following, as appropriate: mining/milling site boundaries; access and haul roads; an outline of the drainage areas of each stormwater outfall within the facility, and an indication of the types of discharges from the drainage areas; equipment storage, fueling and maintenance areas; materials handling areas; outdoor manufacturing, storage or material disposal areas; storage areas for chemicals and explosives; areas used for storage of overburden, materials, soils or wastes; location of mine drainage (where water leaves mine) or any other process water; tailings piles/ponds, both proposed and existing; heap leach pads; points of discharge from the property for mine drainage/process water; surface waters; and boundary of tributary areas that are subject to effluent limitations guidelines.

(2) Summary of potential pollutant sources - For each area of the mine/mill site where stormwater discharges associated with industrial activities occur, the types of pollutants likely to be present in significant amounts must be identified (e.g., heavy metals, sediment). The following factors must be considered: the mineralogy of the ore and waste rock (e.g., acid forming); toxicity and quantity of chemicals used, produced or discharged; the likelihood, if any, of contact with stormwater; vegetation of site; history of reportable leaks/spills of toxic or hazardous pollutants. A summary of any existing ore or waste rock/overburden characterization data and test results for potential generation of acid rock shall also be included. If the ore or waste rock/overburden characterization data are updated due to a change in the ore type being mined, the SWPPP shall be updated with the new data.

(3) Stormwater controls

(a) Nonstructural BMPs - The nonstructural controls in the general requirements at Part III.B.6.b(1) are not required for inactive facilities.

(b) Structural BMPs - Each of the following BMPs shall be considered in the SWPPP. The potential pollutants identified in Paragraph VIII.G.5.b(2) above shall determine the priority and appropriateness of the BMPs selected. If it is determined that one or more of these BMPs are not appropriate for the facility, the plan must explain why it is not appropriate. If BMPs are implemented or planned but are not listed here (e.g., substituting a less toxic chemical for a more toxic one), descriptions of them must be included in the SWPPP.

(i) Sediment and erosion control - The measures to consider include: diversion of flow away from areas susceptible to erosion (measures such as interceptor dikes and swales, diversion dikes, curbs and berms); stabilization methods to prevent or minimize erosion (such as temporary or permanent seeding; vegetative buffer strips; protection of trees; topsoiling; soil conditioning; contouring; mulching; geotextiles (matting; netting; or blankets); riprap; gabions; and retaining walls; and structural methods for controlling sediment (such as check dams; rock outlet protection; level spreaders; gradient terraces; silt fences; gravel or stone filter berms; brush barriers; sediment traps; grass swales; pipe slope drains; earth dikes; other controls such as entrance stabilization, waterway crossings or wind breaks); or other equivalent measures. The permittee shall comply with the New York State Standards and Specifications for Erosion and Sediment Control dated August 2005, or the most current version or its successor. If alternative erosion and sedimentation controls are proposed, the owner or operator must demonstrate equivalence to this technical standard.

(ii) Stormwater diversion - A description of how and where stormwater will be diverted away from potential pollutant sources to prevent stormwater contamination. BMP options may include the following: interceptor dikes and swales; diversion dikes, curbs and berms; pipe slope drains; subsurface drains; drainage/stormwater conveyance systems (channels or gutters, open top box culverts and waterbars; rolling dips and road sloping; roadway surface water deflector and culverts); or equivalent measures.

(iii) Management of runoff - The potential pollutant sources given in Paragraph VIII.G.5.b(2) must be considered when determining reasonable and appropriate measures for managing runoff.

(iv) Capping - Where capping of a potential stormwater pollution source is necessary, the source being capped and materials and procedures used to cap the contaminant source must be identified.

(v) Treatment - If treatment of a stormwater discharge is necessary to protect water quality, include a description of the type and location of stormwater treatment that will be used. Stormwater treatments include the following: chemical or physical systems; oil/water separators; artificial wetlands; etc..

(4) Comprehensive site compliance evaluation - Annual site compliance evaluations may be impractical for inactive mining sites due to remote location/inaccessibility of the site, in which case the permittee must conduct the evaluation at least once every three years. The SWPPP must be documented to explain why annual compliance evaluations are not possible. If the evaluations will be conducted more often than every three years, the frequency of evaluations must be specified.

## 6. Benchmark Monitoring and Reporting Requirements

a. Discharges from waste rock and overburden piles at active ore mining and dressing facilities - Active ore mining and dressing facilities with discharges from waste rock and overburden piles must perform analytic monitoring for the parameters listed in Table VIII-G-1. Facilities must also monitor for the parameters listed in Table VIII-G-2. However, the director may notify the facility that additional monitoring must be performed to accurately characterize the quality and quantity of pollutants discharged from the waste rock/overburden piles. Monitoring requirements for discharges from waste rock and overburden piles are not eligible for the waiver in Part IV.A.4. b.

Table VIII-G-1.  
Sector G - Benchmark Monitoring Requirements

Pollutants of Concern	Analytical Method	Benchmark Monitoring Cut-Off Concentration
<b>Discharges From Waste Rock and Overburden Piles From Active Ore Mining or Dressing Facilities Iron Ores; Copper Ores; Lead and Zinc Ores; Gold and Silver Ores; Ferroalloy Ores Except Vanadium; Miscellaneous Metal Ores (SIC Codes 1011, 1021, 1031, 1041, 1044, 1061, 1081, 1094, 1099)</b>		
Total Suspended Solids (TSS)	EPA 160.2	100 mg/L
Chemical Oxygen Demand (COD)	EPA 410.4	120 mg/L
Turbidity (NTUs)	EPA 180.1	5 NTUs above background
pH	EPA 150.1	6.0 - 9.0 s.u.
Hardness (as CaCO <sub>3</sub> )	EPA 130.1	no benchmark value
Total Recoverable Antimony	EPA 200.7	636 ug/L
Total Recoverable Arsenic	EPA 200.7	168 ug/L
Total Recoverable Beryllium	EPA 200.7	130 ug/L
Total Recoverable Cadmium	EPA 200.7	3.9 ug/L
Total Recoverable Copper	EPA 200.7	64 ug/L
Total Recoverable Iron	EPA 200.7	1.0 mg/L
Total Recoverable Lead	EPA 200.7	82 ug/L
Total Recoverable Manganese	EPA 200.7	1.0 mg/L
Total Recoverable Mercury	EPA 245.7	2.4 ug/L
Total Recoverable Nickel	EPA 200.7	1.4 mg/L
Total Recoverable Selenium	EPA 200.7	238 ug/L
Total Recoverable Silver	EPA 200.7	32 ug/L
Total Recoverable Zinc	EPA 200.7	120 ug/L

\* Total Nitrogen is calculated as the sum of ammonia, nitrate-nitrite and organic nitrogen.

Table VIII-G-2.  
Sector G - Additional Monitoring Requirements for Discharges From Waste Rock and  
Overburden Piles From Active Ore Mining or Dressing Facilities

Type of Ore Mined	Pollutants of Concern		
	TSS (mg/L)	pH	Metals, Total Recoverable
Iron Ore	X	X	Iron (Dissolved).
Titanium Ore	X	X	Iron, Nickel (H), Zinc (H).
Copper, Lead, Zinc, Gold, Silver and Molybdenum	X	X	Arsenic, Cadmium (H), Copper (H), Lead (H), Mercury, Zinc (H).

Note: (H) indicates that hardness must also be measured when this pollutant is measured.

The above monitoring must be compared to benchmark monitoring cut-off concentrations in Table VIII-G-1 with the exception of radium and uranium which have not been assigned cut-off values.

Table VIII-G-3  
Applicability of the Multi-Sector General Permit to Stormwater Runoff From Active  
Mining and Dressing Sites, Temporarily Inactive Sites, and Sites Undergoing Reclamation

Discharge/Source of Discharge	Note/Comment
<b>Piles</b>	
Waste rock/overburden	If composed entirely of stormwater and not combining with mine drainage. See note below.
Topsoil	no comment
<b>Roads constructed of waste rock or spent ore</b>	
Onsite haul roads	If composed entirely of stormwater and not combining with mine drainage. See note below.
Offsite haul and access roads	no comment
<b>Roads not constructed of waste rock or spent ore</b>	
Onsite haul roads	Except if mine drainage is used for dust control
Offsite haul and access roads	no comment
<b>Milling/concentrating</b>	
Runoff from tailings dams and dikes when constructed of waste rock/tailings	Except if process fluids are present and only if composed entirely of stormwater and not combining with mine drainage. See Note below.
Runoff from tailings dams/dikes when not constructed of waste rock and tailings	Except if process fluids are present
Concentration building	If stormwater only and no contact with piles
Mill site	If stormwater only and no contact with piles
<b>Ancillary areas</b>	
Office and administrative building and housing	If mixed with stormwater from the industrial area
Chemical storage area	no comment
Docking facility	Except if excessive contact with waste product that would otherwise constitute mine drainage
Explosive storage	no comment



Discharge/Source of Discharge	Note/Comment
Fuel storage (oil tanks/coal piles)	no comment
Vehicle and equipment maintenance area/building	no comment
Parking areas	But coverage unnecessary if only employee and visitor-type parking
<b>Power plant</b>	
Truck wash area	Except when excessive contact with waste product that would otherwise constitute mine drainage
<b>Reclamation-related areas</b>	
Any disturbed area (unreclaimed)	Only if not in active mining area
Reclaimed areas released from reclamation bonds prior to Dec. 17, 1990	no comment
Partially/inadequately reclaimed areas or areas not released from reclamation bond	no comment
<p>Note: Stormwater runoff from these sources are subject to the SPDES program for stormwater unless mixed with discharges subject to the 40 CFR Part 440 that are not regulated by another permit prior to mixing. Nonstormwater discharges from these sources are subject to SPDES permitting and may be subject to the effluent limitation guidelines under 40 CFR Part 440. Discharges from overburden/waste rock and overburden/waste rock related areas are not subject to 40 CFR Part 440 unless: (1) it drains naturally (or is intentionally diverted) to a point source; and (2) combines with "mine drainage" that is otherwise regulated under the Part 440 regulations. For such sources, coverage under this permit would be available if the discharge composed entirely of stormwater does not combine with other sources of mine drainage that are not subject to 40 CFR Part 440, as well as meeting other eligibility criteria contained in Section I.C. of the permit. Permit applicants bear the initial responsibility for determining the applicable technology-based standard for such discharges. DEC recommends that permit applicants contact the relevant SPDES permit issuance authority for assistance to determine the nature and scope of the "active mining area" on a mine-by-mine basis, as well as to determine the appropriate permitting mechanism for authorizing such discharges.</p>	

## Sector H - [Reserved]

## **Sector I - Oil and Gas Extraction and Refining**

1. **Discharges Covered Under This Section** - The requirements listed under this section apply to stormwater discharges associated with industrial activity from oil and gas extraction and refining facilities listed under SIC Major Group 13 which have had a discharge of a reportable quantity (RQ) of oil or a hazardous substance for which notification is required under 40 CFR 110.6, 40 CFR 117.21 or 40 CFR 302.6. These include oil and gas exploration, production, processing, or treatment operations, or transmission facilities that discharge stormwater contaminated by contact with or that has come into contact with any overburden raw material, intermediate products, finished products, by-products or waste products located on the site of such operations. Industries in SIC Major Group 13 include the extraction and production of crude oil and natural gas; the production of hydrocarbon liquids and natural gas from coal; and associated oilfield service, supply and repair industries. This section also covers petroleum refineries listed under SIC Code 2911. Contaminated stormwater discharges from petroleum refining or drilling operations that are subject to nationally established BAT or BPT guidelines found at 40 CFR Part 419 and 40 CFR Part 435 respectively are not authorized by this permit.

Note: most contaminated discharges from petroleum refining and drilling facilities are subject to these effluent guidelines and are not eligible for coverage under this permit.

### **2. Special Conditions**

a. **Prohibition of non-stormwater discharges** - In addition to the general prohibition of non-stormwater discharges in Paragraph I.D.1, the following discharges not covered by this permit include, but are not limited to: discharges of vehicle and equipment washwater, including tank cleaning operations. Alternatively, washwater discharges must be authorized under a separate SPDES permit, or be discharged to a sanitary sewer in accordance with applicable industrial pretreatment requirements.

3. **Stormwater Pollution Prevention Plan Requirements** - In addition to the requirements of Part III, the SWPPP shall include, at a minimum, the following items.

#### **a. Site description**

(1) **Site map** - The site map shall identify where any of the following may be exposed to precipitation/surface runoff: reportable quantity (RQ) releases; locations used for the treatment, storage or disposal of wastes; processing areas and storage areas; chemical mixing areas; construction and drilling areas; all areas subject to the effluent guidelines requirement of "No Discharge" in accordance with 40 CFR 435.32 and the structural controls to achieve compliance with the "No Discharge" requirement.

(2) **Summary of potential pollutant sources**

(a) The plan shall also include a description of the potential pollutant sources from the following activities: chemical, cement, mud or gel mixing activities; drilling or mining activities; and equipment cleaning and rehabilitation activities.

(b) The plan must include information about the RQ release which triggered the permit application requirements, including: the nature of the release (e.g., spill of oil from a drum storage area); the amount of oil or hazardous substance released; amount of substance recovered; date of the release; cause of the release (e.g., poor handling techniques and lack of containment in the area); areas affected by the release, including land and waters; procedure to cleanup release; actions or procedures implemented to prevent or improve response to a release; and remaining potential contamination of stormwater from release (taking into account human health risks, the control of drinking water intakes, and the designated uses of the receiving water).

**b. Stormwater controls**

(1) Routine facility inspections - All equipment and areas addressed in the SWPPP shall be inspected at a minimum of six month intervals. Equipment and vehicles which store, mix (including all on-site and off-site mixing tanks) or transport chemicals/hazardous materials (including those transporting supplies to oil field activities) will be inspected at least quarterly. For temporarily or permanently inactive oil and gas extraction facilities within Major SIC Group 13, which are remotely located and unstaffed, the inspections shall be performed at least annually.

(2) Sediment and erosion control - Unless covered by a SPDES General Permit for Stormwater Discharges from Construction Activity, the additional erosion control requirement for well drilling are as follows:

(a) Site description - Each plan shall provide a description of the following:

(i) A description of the nature of the exploration activity;

(ii) Estimates of the total area of the site and the area of the site that is expected to be disturbed due to the exploration activity;

(iii) An estimate of the runoff coefficient of the site;

(iv) A site map indicating drainage patterns and approximate slopes; and

(v) The name of all receiving water(s).

(b) Vegetative controls - The SWPPP shall include a description of vegetative practices designed to preserve existing vegetation where attainable and revegetate open areas as soon as practicable after grade drilling. Such practices may include: temporary or permanent seeding, mulching, sod stabilization, vegetative buffer strips, tree protection practices. The permittee shall initiate appropriate vegetative practices on all disturbed areas within 14 calendar days of the last activity at that disturbed area. The permittee shall comply with the New York State Standards and Specifications for Erosion and Sediment Control dated August 2005, or the most current version or its successor. If alternative erosion and sedimentation controls are proposed, the owner or operator must demonstrate equivalence to this technical standard.

(c) Off-site vehicle tracking of sediments shall be minimized.

(d) Procedures in the plan shall provide that all erosion controls on the site are inspected at least once every seven calendar days.

(3) Good housekeeping measures

(a) Vehicle and equipment storage areas - The storage of vehicles and equipment awaiting or having completed maintenance must be confined to designated areas (delineated on the site map). The plan must describe measures that prevent or minimize contamination of the stormwater runoff from these areas (e.g., drip pans under equipment, indoor storage, use of berms and dikes); or other equivalent measures.

(b) Materials and chemical storage areas - Storage units of all chemicals and materials must be maintained in good condition so as to prevent contamination of stormwater. Hazardous materials must be plainly labeled.

(c) Chemical mixing areas - The plan must describe measures that prevent or minimize contamination of the stormwater runoff from chemical mixing areas.

**4. Benchmark Monitoring and Reporting Requirements** - Oil and gas extraction facilities (SIC Major Group 13) and petroleum refineries (SIC 2911) covered under this section are required to monitor their stormwater discharges for the pollutants of concern listed in Table VIII-I-1.

## **Sector N - Scrap Recycling and Waste Recycling Facilities**

**1. Discharges Covered Under This Section** - The requirements listed under this section apply to stormwater discharges associated with industrial activity from scrap and waste recycling facilities (SIC Code 5093) that are engaged in the processing, reclaiming and wholesale distribution of scrap and waste materials such as ferrous and nonferrous metals, paper, plastic, cardboard, glass, animal hides, and facilities that are engaged in reclaiming and recycling liquid wastes such as used oil, antifreeze, mineral spirits, and industrial solvents. Separate permit requirements have been established for recycling facilities that only receive source-separated recyclable materials primarily from nonindustrial and residential sources (e.g., common consumer products including paper, newspaper, glass, cardboard, plastic containers, aluminum and tin cans). This includes recycling facilities commonly referred to as material recovery facilities (MRF). This sector also includes permit requirements for facilities that are engaged in dismantling ships, marine salvaging, and marine wrecking of ships for scrap (SIC 4499). Others activities listed under SIC 4499 are covered in Sector Q.

### **2. Special Conditions**

a. **Prohibition of non-stormwater discharges** - In addition to the general non-stormwater prohibition in Paragraph I.D.1, non-stormwater discharges from turnings containment areas are not covered by this permit. Discharges from containment areas in the absence of a storm event are prohibited unless covered by a separate SPDES permit.

b. **Automobile Dismantling** - If any vehicle dismantling activities occur at this facility, the Permittee must also comply with applicable industry specific requirements outlined in Sector M - Automobile Salvage Yards.

**3. Stormwater Pollution Prevention Plan Requirements** - In addition to the requirements of Part III, all facilities are required to comply with the general SWPPP requirement in subdivision "a" of this subsection. Subdivisions "b" through "e" of this subsection have SWPPP requirements for specific types of recycling facilities. The permittee shall develop and implement their SWPPP to address those items that apply. Included are lists of BMP options that, along with any functional equivalents, shall be considered for implementation. At a minimum the permittee must assess the applicability of the following BMPs.

#### **a. Site description**

(1) **Site map** - The site map shall identify the locations where any of the following activities or sources may be exposed to precipitation/surface runoff: scrap and waste material storage, outdoor scrap and waste processing equipment, and containment areas for turnings exposed to cutting fluids.

training in the plan. Training must be conducted annually at a minimum, however, more frequent training may be necessary at facilities with high employee turnover.

(5) **Management of runoff** - The plan must consider management practices, such as berms or drainage ditches on the property line, that may be used to prevent runoff from neighboring properties. Berms must be considered for uncovered outdoor storage of oily parts, engine blocks, and aboveground liquid storage. The permittee shall consider the installation of detention ponds, filtering devices, and oil/water separators.

5. **Benchmark Monitoring and Reporting Requirements** - Automobile salvage yards are required to monitor their stormwater discharges for the pollutants of concern listed in Table VIII-M-1.

Table VIII-M-1.  
Sector M - Benchmark Monitoring Requirements

Pollutants of Concern	Analytical Method	Benchmark Monitoring Cut-Off Concentration
<b>Automobile Salvage Yards (SIC 5015)</b>		
Total Suspended Solids (TSS)	EPA 160.2	100 mg/L
Oil & Grease	EPA 1664 or EPA 1664A	15 mg/L
Benzene	EPA 602	50 ug/L
Ethylbenzene	EPA 602	50 ug/L
Toluene	EPA 602	50 ug/L
Xylene	EPA 602	50 ug/L
Total Recoverable Aluminum	EPA 200.7	750 ug/L
Total Recoverable Iron	EPA 200.7	1 mg/L
Total Recoverable Lead	EPA 200.7	82 ug/L

- (i) Maintain good integrity of all storage containers;
- (ii) Provide containment and a roof over liquid storage areas;
- (iii) Inspect storage tanks to detect potential leaks and perform preventive maintenance;
- (iv) Inspect piping systems (pipes, pumps, flanges, couplings, hoses, and valves) for failures or leaks; and
- (v) Train employees on proper filling and transfer procedures.

(2) Spill and leak prevention procedures - As indicated in section II.B, the discharge of hazardous substances or petroleum in the stormwater discharge(s) from the facility shall be prevented or minimized in accordance with the stormwater pollution prevention plan for the facility. Any spill of petroleum must be reported in accordance with 6 NYCRR Part 613.8. Any spill of a hazardous substance must be reported in accordance with 6 NYCRR Part 595.3. Notification must be reported to the DEC hotline (1-800- 457-7362) within two hours of identifying a release. Spills or leaks outside of containment areas shall be cleaned up immediately and spills or leaks within containment shall be controlled immediately and cleaned up as stated in section III.L.3.b. After clean up from a spill, absorbents must be promptly placed in containers for proper disposal. Additionally, all vehicles that are intended to be dismantled must be properly drained of all fluids prior to being dismantled or crushed, or other equivalent means must be taken to prevent leaks or spills of fluids including motor oil, transmission fluid, fuel and antifreeze.

(3) Inspections - Routine facility inspections conducted by qualified facility personnel identified in Part III.C.6.b(1)(e) shall include, but is not limited to the following:

- (i) All incoming vehicles upon arrival at the site for leakage;
- (ii) Outdoor storage of vehicles, parts or equipment for leakage at least quarterly;
- (iii) Outdoor storage of fluids in tanks or containers for leakage at least quarterly;
- (iv) Prior to crushing, spot check vehicles for removal of fluids, battery, mercury switches, lead battery connectors, lead tire balance weights, PCB capacitors, etc.

(4) Employee training - Employee training must, at a minimum, address the following areas when applicable to a facility: used oil management; spill prevention and response; good housekeeping practices; used battery management; removal of parts containing mercury, lead and PCBs, and proper handling (i.e., collection, storage, and disposal) of all fluids. Permittees are required to include a schedule for conducting



- (iii) Install curbing, berms or dikes around storage areas;
- (iv) Confine storage of parts, equipment and vehicles to designated areas;
- (v) Cover all parts storage areas with a permanent cover (e.g., roofs) or temporary cover (e.g., canvas tarps);
- (vi) Used batteries shall be stored within nonleaking secondary containment or by other equivalent means to prevent leaks of acid into stormwater discharges;
- (vii) Inspect the storage yard for filling drip pans and other problems regularly; and
- (viii) Train employees on procedures for storage and inspection items.

(c) Vehicle, Equipment, and Parts Cleaning Areas - The plan must describe measures that prevent or minimize contamination of stormwater from all areas used for vehicle, equipment, and parts cleaning. Washwaters from vehicle, equipment, and parts cleaning areas are process wastewaters that are not authorized discharges under this section. The facility must consider performing all cleaning operations indoors. At a minimum the permittee must assess the applicability of the corresponding BMPs:

- (i) Avoid washing parts or equipment outside;
- (ii) Designate an area for cleaning activities;
- (iii) Install curbing, berms or dikes around cleaning areas;
- (iv) Consider using detergent-based or water-based cleaning systems in place of organic solvent degreasers;
- (v) Use phosphate-free biodegradable detergents;
- (vi) Contain steam cleaning washwaters or discharge under an applicable SPDES permit;
- (vii) Inspect cleaning area regularly; and
- (viii) Train employees on proper washing procedures.

(d) Liquid Storage Areas - The plan must describe measures that prevent or minimize contamination of the stormwater runoff from all areas used for liquid storage. At a minimum the permittee must:

- (xi) Plug floor drains that are connected to the storm or sanitary sewers;
  - (xii) Vehicle dismantling activities shall include removal of lead acid batteries, other lead parts such as tire weights and battery cable ends, mercury switches, other mercury containing parts for recycling;
  - (xiii) Recover air conditioner refrigerants using EPA certified recycling equipment;
  - (xiv) Maintain an organized inventory of materials used in the maintenance shop;
  - (xv) Nonhazardous substances that are contaminated with a hazardous substance are considered to be a hazardous substance;
  - (xvi) Dispose of greasy rags, air filters, and degreasers properly;
  - (xvii) Label and track the recycling of waste material (e.g., used oil, spent solvents, batteries);
  - (xviii) Drain oil and transmission filters before disposal or recycling;
  - (xix) Inspect the maintenance area regularly for proper implementation of control measures;
  - (xx) Use dry cleanup methods and prohibit the practice of hosing down the shop floor;
  - (xxi) Recycle mineral spirits and solvents;
  - (xxii) Provide treatment of stormwater discharges with devices such as oil-water separators; and
  - (xxiii) Train employees on proper waste control and disposal procedures.
- (b) Vehicle, Parts and Equipment Storage Areas - The plan must describe measures that prevent or minimize contamination of the stormwater runoff from vehicle, parts and equipment storage areas. At a minimum the permittee must assess the applicability of the corresponding BMPs:
- (i) Use drip pans under all vehicles and equipment waiting for maintenance and during maintenance;
  - (ii) Large plastic or metal bins with secure lids should be used to store oily parts (e.g., small engine parts);

(2) Summary of potential pollutant sources - The permittee must assess the potential for the following activities to contribute pollutants to stormwater discharges: vehicle storage areas; dismantling areas; parts storage areas (e.g., engine blocks, tires, hub caps, batteries, and hoods ); and fueling stations.

b. Stormwater controls

(1) Good housekeeping measures

(a) Vehicle Dismantling and Maintenance Areas - The plan must describe measures that prevent or minimize contamination of stormwater runoff from all areas used for vehicle dismantling and maintenance. At a minimum the permittee must assess the applicability of the corresponding BMPs:

- (i) Inspect all incoming vehicles for leaks and take appropriate actions to prevent the release of automobile fluids to the ground;
- (ii) Remove fuel, refrigerants and the battery as soon as possible;
- (iii) Vehicle draining and dismantling activities must be conducted in a bermed area, constructed of concrete or other surfaces that allows equivalent protection to groundwater;
- (iv) The dismantling area should also be covered;
- (v) Promptly transfer any drained fluids to segregated storage containers that are properly labeled and in good condition (e.g, anti-freeze, gasoline, used oil, transmission fluid, brake fluids, window washer fluid) for reuse or recycling;
- (vi) Drain and collect all fluids to the maximum extent practicable in accordance with best available industry standards from engines, radiators, transmissions, heater core, brake fluid reservoirs, differentials, hoses, fuel tanks, air conditioning units and window washing fluids before crushing or storage over bare ground;
- (vii) Do not leave full drip pans or other open containers around the shop;
- (viii) Properly store batteries for recycling or resale;
- (ix) Store cracked batteries in a non-leaking covered container;
- (x) Do not pour liquid waste down floor drains, sinks, or outdoor storm drain inlets;

## **Sector M - Automobile Salvage Yards**

1. **Discharges Covered Under This Section** - The requirements listed under this section apply to stormwater discharges associated with industrial activity from facilities engaged in dismantling or wrecking used motor vehicles for parts recycling/resale and for scrap (SIC Code 5015).

### **2. Special Conditions**

a. **Prohibition of non-stormwater discharges** - In addition to the general prohibition of non-stormwater discharges in Paragraph I.D.1, the following discharges not covered by this permit include, but are not limited to: discharges of vehicle, equipment and floor washwater. All washwater discharges must be authorized under a separate SPDES permit or discharged to a sanitary sewer in accordance with applicable industrial pretreatment requirements.

3. **Guidance in Developing the Stormwater Pollution Prevention Plan** - Permittees operating facilities engaged in dismantling or wrecking used motor vehicles for parts recycling/resale and for scrap (SIC Code 5015) must review the following guidance documents to ensure that operating practices meet regulatory requirements and follow pollution prevention measures which will minimize waste and promote environmental compliance.

a. NYSDEC's **Environmental Compliance and Pollution Prevention Guide for Automobile Recyclers**, January 2003

b. **Auto Recyclers Guide to a Cleaner Environment - Best Management Practices**, April 2001, prepared by the Monroe County Small Business Pollution Prevention Task Force and NYSDEC

These documents are available at: <http://www.dec.state.ny.us/website/ppu/armainpage.html>

4. **Stormwater Pollution Prevention Plan Requirements** - In addition to the requirements of Part III, the SWPPP shall include, at a minimum, the following items:

#### **a. Site description**

(1) **Site map** - The map must include: the location of each discharge and monitoring point; an estimation (in acres) of the total area used for industrial activity including, but not limited to, dismantling, storage, and maintenance of used motor vehicle parts. The site map must also identify where any of the following may be exposed to precipitation/surface runoff: vehicle storage areas; dismantling areas; parts storage areas (e.g., engine blocks, tires, hub caps, batteries, hoods, mufflers); and liquid storage tanks and drums for fuel and other fluids.

6. **Benchmark Monitoring and Reporting Requirements** - Landfill and land application sites are required to monitor their stormwater discharges for the pollutants of concern listed in Table VIII-L-2. These benchmark monitoring cutoff concentrations apply to stormwater discharges associated with industrial activity other than contaminated stormwater discharges from landfills subject to the numeric effluent limitations set forth in Table VIII-L-1.

Table VIII-L-2.  
Sector L - Benchmark Monitoring Requirements

Pollutants of Concern	Analytical Method	Benchmark Monitoring Cut-Off Concentration
<b>Landfills, Land Application Sites and Non-Compliant Landfills (Industrial Activity Code "LF").</b>		
Total Suspended Solids (TSS)	EPA 160.2	100 mg/L
Total Nitrogen (TN)	EPA 350.1, 351.2, 353.2	6 mg/L
Total Phosphorus (TP)	EPA 365.1	2 mg/L
Total Recoverable Iron	EPA 200.7	1 mg/L
<b>Landfills, Land Application Sites and Non-Compliant Landfills, Except Municipal Solid Waste Landfill Areas Closed in Accordance With 40 CFR 258.60 (Industrial Activity Code "LF")</b>		
Total Suspended Solids (TSS)	EPA 160.2	100 mg/L
Total Recoverable Iron	EPA 200.7	1 mg/L

\* Total Nitrogen is calculated as the sum of ammonia, nitrate-nitrite and organic nitrogen.

**5. Numeric Effluent Limitations** - As set forth at 40 CFR Part 445 Subpart B, the numeric effluent limitations in Table VIII-L-1 apply to contaminated stormwater discharges from municipal solid waste landfills (MSWLFs) that have not been closed in accordance with 40 CFR 258.60, and contaminated stormwater discharges from those landfills that are subject to the provisions of 40 CFR Part 257 except for discharges from any of the facilities described in subdivisions "a" through "d" of this subsection:

- a. Landfills operated in conjunction with other industrial or commercial operations when the landfill receives only wastes generated by the industrial or commercial operation directly associated with the landfill;
- b. Landfills operated in conjunction with other industrial or commercial operations when the landfill receives wastes generated by the industrial or commercial operation directly associated with the landfill and also receives other wastes provided the other wastes received for disposal are generated by a facility that is subject to the same provisions in 40 CFR Subchapter N as the industrial or commercial operation or the other wastes received are of a nature similar to the wastes generated by the industrial or commercial operation;
- c. Landfills operated in conjunction with centralized waste treatment (CWT) facilities subject to 40 CFR Part 437 so long as the CWT facility commingles the landfill wastewater with other non-landfill wastewater for discharge. A landfill directly associated with a CWT facility is subject to this part if the CWT facility discharges landfill wastewater separately from other CWT wastewater or commingles the wastewater from its landfill only with wastewater from other landfills; or
- d. Landfills operated in conjunction with other industrial or commercial operations when the landfill receives wastes from public service activities so long as the company owning the landfill does not receive a fee or other remuneration for the disposal service.

Table VIII-L-1.  
Sector L - Numeric Effluent Limitations

Parameter	Effluent Limitations	
	Daily Maximum	30-day Average
<b>Landfills (Industrial Activity Code "LF") That Are Subject to the Point Source Category Provisions of 40 CFR Part 445 Subpart B.</b>		
Biochemical Oxygen Demand (BOD5)	140 mg/L	37 mg/L
Total Suspended Solids (TSS)	88 mg/L	27 mg/L
Ammonia	10 mg/L	4.9 mg/L
Alpha Terpineol	0.033 mg/L	0.016 mg/L
Benzoic Acid	0.12 mg/L	0.071 mg/L
p-Cresol	0.025 mg/L	0.014 mg/L
Phenol	0.026 mg/L	0.015 mg/L
Zinc (Total)	0.20 mg/L	0.11 mg/L
pH	Within the range of 6.0 - 9.0 s.u.	

application has been completed, inspections shall be conducted at least once every month.

(b) Inspections of inactive sites - Inactive landfills, non-compliant landfills, and land application sites shall be inspected at least quarterly. Qualified personnel shall inspect landfill stabilization and structural erosion control measures and leachate collection and treatment systems, and all closed land application areas.

(4) Non-stormwater discharge test certification - The discharge test and certification must also be conducted for the presence of leachate and vehicle washwater.

(5) Erosion and sediment control plan -

The plan shall include details of temporary and permanent structural and vegetative measures that will be used to control erosion and sedimentation for each phase of landfill construction, operation and closure. The design, installation, maintenance and repair of erosion and sediment controls shall conform to the New York State Standards and Specifications for Erosion and Sediment Control dated August 2005, or the most current version or its successor. If alternative erosion and sedimentation controls are proposed, the owner or operator must demonstrate equivalence to this technical standard.

If any phase of the landfill construction or closure will result in the disturbance of five (5) or more acres of land at any one time, the owner or operator must obtain approval from the Regional Office stormwater contact person prior to disturbing more than five acres.

(6) Post-construction Stormwater Management Controls - Stormwater runoff from all disturbed areas that is not handled as leachate shall be captured and treated by a post-construction stormwater management control(s). The design, construction and maintenance of all post-construction stormwater management controls shall conform to the New York State Stormwater Management Design Manual. All controls shall be designed to meet the Unified Stormwater Sizing Criteria in Chapter 4 of the New York State Stormwater Management Design Manual. If alternative post-construction controls are proposed, the owner or operator must demonstrate equivalence to this technical standard.

(7) Comprehensive site compliance evaluation - Areas contributing to a stormwater discharge associated with industrial activities at landfills, non-compliant landfills and land application sites shall be evaluated for evidence of, or the potential for, pollutants entering the drainage system.

4. **Stormwater Pollution Prevention Plan Requirements** - In addition to the requirements in Part III, the SWPPP shall include, at a minimum, the following items.

a. **Site description**

(1) **Site map** - The site map shall identify where any of the following may be exposed to precipitation/surface runoff: active and closed landfill cells or trenches; active and closed land application areas; locations where open dumping is occurring or has occurred; locations of any known leachate breakouts or other areas where uncontrolled leachate may commingle with runoff; and leachate collection and handling systems.

(2) **Summary of potential pollutant sources** - The SWPPP shall also include a description of potential pollutant sources associated with any of the following: fertilizer, herbicide and pesticide application; earth/soil moving; waste hauling and loading/unloading; outdoor storage of significant materials including daily, interim and final cover material stockpiles, as well as, temporary waste storage areas; exposure of active and inactive landfill and land application areas; uncontrolled leachate flows; and failure or leaks from leachate collection and treatment systems.

b. **Stormwater controls.**

(1) **Preventive maintenance program** - As part of the preventive maintenance program, the permittee shall maintain: all containers used for outdoor chemical/significant materials storage to prevent leaking; all elements of leachate collection and treatment systems to prevent commingling of leachate with stormwater; and the integrity and effectiveness of any intermediate or final cover (including making repairs to the cover as necessary to minimize the effects of settlement, sinking, and erosion).

(2) **Good housekeeping measures** - As part of the good housekeeping program, the permittee shall consider providing protected storage areas for pesticides, herbicides, fertilizer and other significant materials.

(3) **Routine facility inspections**

(a) **Inspections of active sites** - Operating landfills, non-compliant landfills, and land application sites shall be inspected at least once every seven days. Qualified personnel shall inspect areas of landfills that have not yet been finally stabilized, active land application areas, areas used for storage of materials/wastes that are exposed to precipitation, stabilization and structural control measures, leachate collection and treatment systems, and locations where equipment and waste trucks enter and exit the site. Erosion and sediment control measures shall be observed to ensure they are operating correctly. For stabilized sites and areas where land



**"Contaminated stormwater"** means stormwater that comes in direct contact with landfill wastes, the waste handling and treatment areas, or landfill wastewater as defined below. Some specific areas of a landfill that may produce contaminated stormwater include, but are not limited to: the open face of an active landfill with exposed waste (including areas with daily cover); the areas around wastewater treatment operations; trucks, equipment or machinery that has been in direct contact with the waste; and waste dumping areas.

**"Drained free liquids"** means aqueous wastes drained from waste containers (e.g., drums, etc.) prior to landfilling.

**"Land application facility"** means a site where solid waste is applied to the soil surface or injected into the upper layer of the soil to improve soil quality or provide plant nutrients. Solid waste suitable for this purpose includes, but is not limited to, certain food processing waste, sewage treatment plant sludge and septage.

**"Landfill"** means land or a disposal facility or part of one where solid waste or its residue after treatment is intentionally placed and which is not a land application facility, surface impoundment, injection well or waste pile.

**"Landfill wastewater"** as defined in 40 CFR Part 445 (Landfills Point Source Category) means all wastewater associated with, or produced by, landfilling activities except for sanitary wastewater, noncontaminated stormwater, contaminated groundwater, and wastewater from recovery pumping wells. Landfill wastewater includes, but is not limited to, leachate, gas collection condensate, drained free liquids, laboratory-derived wastewater, contaminated stormwater and contact washwater from washing truck, equipment, and railcar exteriors and surface areas that have come in direct contact with solid waste at the landfill facility.

**"Leachate"** means any solid waste in the form of a liquid, including any suspended components in the liquid, that results from contact with or passage through solid waste.

**"Noncontaminated stormwater"** means stormwater that does not come into direct contact with landfill wastes, the waste handling and treatment areas, or landfill wastewater as defined above. Noncontaminated stormwater includes stormwater that flows off the final cover of the landfill, runoff from intermediate cover that has not come in contact with leachate or waste and runoff from portions of the landfill where waste has not yet been disposed of and which are segregated from active portions of the landfill.

**"Surface impoundment"** means a solid waste management facility or part of one that is a natural topographical depression, excavation, or diked area formed primarily of earthen materials (although it may be lined with synthetic materials), that is designed to hold solid waste in semisolid or liquid form and that is not an injection well. Examples of surface impoundments are holding, storage, settling, and aeration pits, ponds and lagoons.

## **Sector L - Landfills, Land Application Sites and Non-Compliant Landfills**

**1. Discharges Covered Under This Section** - The requirements listed under this section apply to stormwater discharges associated with industrial activity from waste disposal at landfills, land application sites, and non-compliant landfills (Industrial Activity Code "LF") that receive or have received industrial wastes (waste that is received from industrial activities at any of the facilities described under 40 CFR Part 122.26(b)(14) categories (i) - (xi)). The requirements listed under this section are intended to apply to initial, as well as ongoing construction activities at landfills. [Note: Non-compliant landfills are solid waste disposal units that are not in compliance with state/federal criteria established under RCRA Subtitle D.] Landfills that have been closed in accordance with 6 NYCRR Part 360 are not required to maintain SPDES permit coverage for stormwater discharges provided that the landfill is or has been maintained under a post closure care program.

### **2. Special Conditions**

a. **Prohibition of Non-stormwater Discharges** - In addition to the general non-stormwater prohibition in Paragraph I.D.1, the discharges not covered by this permit include, but are not limited to: leachate, gas collection condensate, drained free liquids, contaminated ground water, laboratory wastewater, and contact washwater from washing truck, railcar and equipment exteriors and surface areas that have come in direct contact with solid waste or daily cover at the landfill facility.

b. **Stormwater Discharges from Construction Activities** - A comprehensive Stormwater Pollution Prevention Plan (SWPPP) addressing the storm water run-on and run-off control systems needed during the landfill's construction, operation and closure phases must be prepared prior to the commencement of any construction activity that will result in a land disturbance of one or more acres of land. The plan must be prepared in accordance with the New York Standards and Specifications for Erosion and Sediment Control, dated August 2005; and the New York State Stormwater Management Design Manual. If alternative erosion and sedimentation controls or stormwater management practices are proposed, the owner or operator must demonstrate equivalence to these technical standards.

The SWPPP must be kept current and should address effective stormwater controls for all appurtenances and components associated with the landfill, including but not limited to, haul roads, paved areas, associated buildings and structures, landfill surfaces, perimeter ditches, and berms.

### **3. Definitions**

*"Contaminated groundwater"* means water below the land surface in the zone of saturation which has been contaminated by activities associated with waste disposal.

Table VIII-K-2.  
Sector K - Benchmark Monitoring Requirements

Pollutants of Concern	Analytical Method	Benchmark Monitoring Cut-Off Concentration
<b>Hazardous Waste Treatment, Storage, or Disposal Facilities (Industrial Activity Code "HZ")</b>		
Total Nitrogen (TN)	EPA 350.1, 351.2, 353.2	6 mg/L
Total Suspended Solids (TSS)	EPA 160.2	100 mg/L
Chemical Oxygen Demand (COD)	EPA 410.4	120 mg/L
Total Recoverable Magnesium	EPA 200.7	64 ug/L
Total Recoverable Arsenic	EPA 200.7	168 ug/L
Total Recoverable Cadmium	EPA 200.7	16 ug/L
Total Cyanide	EPA 335.2	64 ug/L
Total Recoverable Lead	EPA 200.7	82 ug/L
Total Recoverable Mercury	EPA 245.7	2.4 ug/L
Total Recoverable Selenium	EPA 200.7	238 ug/L
Total Recoverable Silver	EPA 200.7	32 ug/L

\* Total Nitrogen is calculated as the sum of ammonia, nitrate-nitrite and organic nitrogen.

wastewater separately from other CWT wastewater or commingles the wastewater from its landfill only with wastewater from other landfills; or

d. Landfills operated in conjunction with other industrial or commercial operations when the landfill receives wastes from public service activities so long as the company owning the landfill does not receive a fee or other remuneration for the disposal service.

Table VIII-K-1.  
Sector K - Numeric Effluent Limitations

Parameter	Effluent Limitations	
	Daily Maximum	30-day Average
<b>Hazardous Waste Treatment, Storage, or Disposal Facilities (Industrial Activity Code "HZ") Subject to the Point Source Category Provisions of 40 CFR Part 445 Subpart A.</b>		
Biochemical Oxygen Demand (BOD5)	220 mg/L	56 mg/L
Total Suspended Solids (TSS)	88 mg/L	27 mg/L
Ammonia	10 mg/L	4.9 mg/L
Alpha Terpineol	0.042 mg/L	0.019 mg/L
Aniline	0.024 mg/L	0.015 mg/L
Benzoic Acid	0.119 mg/L	0.073 mg/L
Naphthalene	0.059 mg/L	0.022 mg/L
p-Cresol	0.024 mg/L	0.015 mg/L
Phenol	0.048 mg/L	0.029 mg/L
Pyridine	0.072 mg/L	0.025 mg/L
Arsenic (Total)	1.1 mg/L	0.54 mg/L
Chromium (Total)	1.1 mg/L	0.46 mg/L
Zinc (Total)	0.535 mg/L	0.296 mg/L
pH	Within the range of 6.0 - 9.0 s.u.	

5. **Benchmark Monitoring and Reporting Requirements** - Permittees with hazardous waste treatment, storage, or disposal facilities (TSDFs) are required to monitor their stormwater discharges for the pollutants of concern listed in Table VIII-K-2. These benchmark monitoring cutoff concentrations apply to stormwater discharges associated with industrial activity other than contaminated stormwater discharges from landfills subject to the numeric effluent limitations set forth in Table VIII-K-1.

stormwater and contact washwater from washing truck, equipment, and railcar exteriors and surface areas that have come in direct contact with solid waste at the landfill facility.

"*Leachate*" means a liquid, including any suspended components or dissolved compounds in the liquid, which has been in contact with or passed through solid waste, including hazardous waste.

"*Noncontaminated stormwater*" means stormwater that does not come into direct contact with landfill wastes, the waste handling and treatment areas, or landfill wastewater as defined above. Noncontaminated stormwater includes stormwater that flows off the final cover of the landfill, runoff from intermediate cover that has not come in contact with leachate or waste and runoff from inactive portions of the landfill which are segregated from active portions of the landfill.

"*Pile*" means any noncontainerized accumulation of solid, nonflowing hazardous waste that is used for treatment or storage and that is not a containment building.

"*Surface impoundment*" or "*impoundment*" means a facility or part of a facility which is a natural topographical depression, human-made excavation, or diked area formed primarily of earthen materials (although it may be lined with human-made materials), which is designed to hold an accumulation of liquid wastes or wastes containing free liquids, and which is not an injection well. Examples of surface impoundments are holding, storage, settling, and aeration pits, ponds and lagoons.

**4. Numeric Effluent Limitations** - As set forth at 40 CFR Part 445 Subpart A, the numeric limitations in Table VIII-K-1 apply to contaminated stormwater discharges from hazardous waste landfills subject to the provisions of RCRA Subtitle C at 40 CFR Parts 264 (Subpart N) and 265 (Subpart N) except for any of the facilities described in subdivisions "a" through "d" of this subsection:

- a. Landfills operated in conjunction with other industrial or commercial operations when the landfill only receives wastes generated by the industrial or commercial operation directly associated with the landfill;
- b. Landfills operated in conjunction with other industrial or commercial operations when the landfill receives wastes generated by the industrial or commercial operation directly associated with the landfill and also receives other wastes provided the other wastes received for disposal are generated by a facility that is subject to the same provisions in 40 CFR Subchapter N as the industrial or commercial operation or the other wastes received are of similar nature to the wastes generated by the industrial or commercial operation;
- c. Landfills operated in conjunction with Centralized Waste Treatment (CWT) facilities subject to 40 CFR Part 437 so long as the CWT facility commingles the landfill wastewater with other nonlandfill wastewater for discharge. A landfill directly associated with a CWT facility is subject to this part if the CWT facility discharges landfill

## **Sector K - Hazardous Waste Treatment, Storage, or Disposal Facilities**

1. **Discharges Covered Under This Section** - The requirements listed under this section apply to stormwater discharges associated with industrial activity from facilities that treat, store, or dispose of hazardous wastes, including those that are operating under interim status or a permit under Subtitle C of RCRA (Industrial Activity Code "HZ"). Disposal facilities that have been properly closed and capped, and have no significant materials exposed to stormwater, are considered inactive and do not require permits.

### **2. Special Conditions**

a. **Prohibition of non-stormwater discharges** - In addition to the general prohibition of non-stormwater discharges in Paragraph I.D.1, the following discharges not covered by this permit include, but are not limited to: leachate, gas collection condensate, drained free liquids, contaminated ground water, laboratory-derived wastewater and contact washwater from washing truck and railcar exteriors and surface areas that have come in direct contact with solid waste at the landfill facility.

### **3. Definitions**

"*Contaminated stormwater*" means stormwater that comes in direct contact with landfill wastes, the waste handling and treatment areas, or landfill wastewater as defined in this section. Some specific areas of a landfill that may produce contaminated stormwater include, but are not limited to: the open face of an active landfill with exposed waste (including areas with daily cover); the areas around wastewater treatment operations; trucks, equipment or machinery that has been in direct contact with the waste; and waste dumping areas.

"*Drained free liquids*" means aqueous wastes drained from waste containers (e.g., drums, etc.) prior to landfilling.

"*Land treatment facility*" means a facility or part of a facility at which solid waste, including hazardous waste, is applied onto or incorporated into the soil surface. Such facilities are disposal facilities if the waste will remain after closure.

"*Landfill*" means a disposal facility or part of a facility where solid waste, including hazardous waste, is placed in or on land, and which is not a pile, a land treatment facility, a surface impoundment, an underground injection well, a salt dome formation, a salt bed formation, an underground mine, a cave, or a corrective action management unit.

"*Landfill wastewater*" as defined in 40 CFR Part 445 (Landfills Point Source Category) means all wastewater associated with, or produced by, landfilling activities except for sanitary wastewater, noncontaminated stormwater, contaminated ground water, and wastewater from recovery pumping wells. Landfill wastewater includes, but is not limited to, leachate, gas collection condensate, drained free liquids, laboratory derived wastewater, contaminated

Table VIII-J-2.  
Sector J - Benchmark Monitoring Requirements

Pollutants of Concern	Analytical Method	Benchmark Monitoring Cut-Off Concentration
<b>Sand and Gravel Mining (SIC 1442, 1446)</b>		
Total Nitrogen (TN)	EPA 350.1, 351.2, 353.2	6 mg/L
Total Phosphorus (TP)	EPA 365.1	2 mg/L
Total Suspended Solids (TSS)	EPA 160.2	100 mg/L
Total Recoverable Iron	EPA 200.7	1 mg/L
Total Recoverable Zinc	EPA 200.7	120 ug/L
<b>Dimension and Crushed Stone and Nonmetallic Minerals (except fuels) (SIC 1411, 1422-1429, 1481, 1499)</b>		
Total Suspended Solids (TSS)	EPA 160.2	100 mg/L

\* Total Nitrogen is calculated as the sum of ammonia, nitrate-nitrite and organic nitrogen.

b. **Erosion and Sediment Control Plan** - The Stormwater Pollution Prevention Plan (SWPPP) shall include details of temporary and permanent structural and vegetative measures that will be used to control erosion and sedimentation for each phase of mine construction, operation and reclamation. The design, installation, maintenance and repair of erosion and sediment controls shall conform to the New York Standards and Specifications for Erosion and Sediment Control dated August 2005, or the most current version or its successor. If alternative erosion and sedimentation controls are proposed, the owner or operator must demonstrate equivalence to this technical standard.

c. The SWPPP must be kept current and should address effective stormwater controls for all appurtenances and components associated with the mine, including but not limited to: access roads, haul roads, paved areas, associated buildings and structures, perimeter ditches, and berms.

5. **Numeric Effluent Limitations** - The following effluent limitations shall be met by existing and new discharges from mine dewatering activities at construction sand and gravel; industrial sand; and crushed stone mining facilities (SIC 1422-1429, 1442, 1446) in accordance with 40 CFR 436:

Table VIII-J-1.  
Sector J - Numeric Effluent Limitations

Parameter	Effluent Limitations	
	Daily Maximum	30-day Average
<b>Mine Dewatering Activities at Construction Sand and Gravel; Industrial Sand; and Crushed Stone Mining Facilities (SIC 1422-1429, 1442, 1446) Subject to the Point Source Category Provisions of 40CFR Part 436 Subparts B, C &amp; D.</b>		
Total Suspended Solids (TSS)	45 mg/L	25 mg/L
pH	6.0 - 9.0 s.u.	

6. **Benchmark Monitoring and Reporting Requirements** - Sand and gravel mining facilities (SIC 1442, 1446) and facilities manufacturing dimension, crushed stone and nonmetallic minerals (except fuels (SIC 1411, 1422-1429, 1481, 1499) are required to monitor their stormwater discharges for the pollutants of concern listed in Table VIII-J-2.



*“Exploration and Construction”* means exploration and land disturbance activities to determine the financial viability of a site. Construction includes the building of site access roads and removal of overburden and waste rock to expose mineable minerals.

*“Active Phase”* means any activities including each step from extraction through production of a salable product.

*“Reclamation phase”* means activities intended to return the land to a pre-approved, post-mining land use.

Note: The following definitions are not intended to supercede the definitions of active and inactive mining facilities established by 40 CFR 122.26(b)(14)(iii).

*“Active Mineral Mining Facility”* means a place where work or other activity related to the extraction, removal or recovery of minerals is being conducted. This definition does not include any land where grading has returned the earth to a desired contour and reclamation has begun.

*“Inactive Mineral Mining Facility”* means a site or portion of a site where mineral mining and/or dressing occurred in the past but is not an active facility as defined above, and where the inactive portion is not covered by an active permit issued by the applicable State or Federal government agency.

*“Temporarily Inactive Mineral Mining Facility”* means a site or portion of a site where mineral mining and/or dressing occurred in the past but currently are not being actively undertaken, and the facility is covered by an active mining permit issued by the applicable State or Federal government agency.

*“Final Stabilization”* means that all soil-disturbing activities at the site have been completed and a uniform, perennial vegetative cover with a density of eighty (80) percent has been established or equivalent stabilization measures (such as the use of permanent landscape mulches, riprap, or washed/crushed stone) have been employed on all unpaved areas and areas not covered by permanent structures.

#### **4. Stormwater Pollution Prevention Plan Requirements**

a. **Routine facility inspections** - All BMPs at the active mining facilities shall be inspected quarterly. Temporarily or permanently inactive facilities shall be inspected annually. The inspection program shall, at a minimum, include: assessment of the integrity of stormwater discharge diversions, conveyance systems, sediment control and collection systems and containment structures; inspections to determine if soil erosion has occurred at, or as a result of vegetative BMPs, serrated slopes and benched slopes; inspections of material handling and storage areas and other potential sources of pollution for evidence of actual or potential discharges of contaminated stormwater.

## **Sector J - Mineral Mining and Dressing**

1. **Discharges Covered Under This Section** - The requirements listed under this section apply to stormwater discharges associated with industrial activity from active and inactive mineral mining and dressing facilities as identified by the SIC Major Group 14. The types of activities that permittees under Sector J are primarily engaged in are: exploring for minerals (e.g., stone, sand, clay, chemical and fertilizer minerals, non-metallic minerals, etc.); developing mines and the mining of minerals; mineral dressing, and nonmetallic mineral services. Most stormwater discharges subject to an existing effluent limitation guideline in 40 CFR Part 436 are not authorized by this permit, except for mine dewatering discharges composed entirely of stormwater or ground water seepage from construction sand and gravel, industrial sand, and crushed stone mining facilities.

### **2. Special Conditions**

a. **Prohibition of non-stormwater discharges** - In addition to the general prohibitions of non-stormwater discharges in paragraph I.D.1, the following discharges not covered by this permit include, but are not limited to: mineral wash water, transport (slurry) water, wet scrubber blowdown, contact cooling water, noncontact cooling water, floor and equipment washing, water used for dust suppression (except as indicated in subparagraph VIII.J.2.b), cooling tower and boiler blowdowns, vehicle and equipment maintenance fluids and intake water treatment backwashes. These discharges must be covered under a separate SPDES permit.

b. **Authorized non-stormwater discharges** - In addition to the discharges described in Paragraph I.D.1, the discharge of clean water applied to roadways for dust control may be authorized by this permit provided that BMPs are in place to limit application rates thus minimizing surface runoff.

c. **Stormwater discharges from construction activities** - A comprehensive Stormwater Pollution Prevention Plan (SWPPP) addressing the storm water run-on and run-off control systems needed during the mines construction, operation and reclamation phases must be prepared prior to the commencement of any construction activity that will result in a land disturbance of one or more acres of land. The plan must be prepared in accordance with the New York Standards and Specifications for Erosion and Sediment Control dated August 2005, or the most current version or its successor. If alternative erosion and sedimentation controls are proposed, the owner or operator must demonstrate equivalence to this technical standard.

### **3. Definitions**

***“Mining Operation”*** means any of the three-phases which qualifies as a “mining activity.” The phases are the exploration and construction phase, the active phase and the reclamation phase.

Table VIII-I-1.  
Sector I - Benchmark Monitoring Requirements

Pollutants of Concern	Analytical Method	Benchmark Monitoring Cut-Off Concentration
<b>Oil and Gas Extraction (SIC Major Group 13)</b>		
Total Suspended Solids (TSS)	EPA 160.2	100 mg/L
Chlorides	EPA 325.3	860 mg/L
pH	EPA 150.1	6.0 - 9.0 s.u.
<b>Petroleum Refineries (SIC 2911)</b>		
Oil and Grease	EPA 1664 or EPA 1664A	100 mg/L
Benzene	EPA 602	50 ug/L
Ethylbenzene	EPA 602	50 ug/L
Toluene	EPA 602	50 ug/L
Xylene	EPA 602	50 ug/L
Total Recoverable Lead	EPA 200.7	82 ug/L
Total Recoverable Zinc	EPA 200.7	120 ug/L

(c) Aircraft, ground vehicle and equipment storage areas - The storage of aircraft, ground vehicles and equipment awaiting maintenance must be confined to designated areas (delineated on the site map). The following BMPs (or their equivalents) shall be considered: indoor storage of aircraft and ground vehicles; the use of drip pans for the collection of fluid leaks; and perimeter drains, dikes or berms surrounding storage areas.

(c) Material storage areas - Storage vessels of all materials (e.g., used oils, hydraulic fluids, spent solvents, and waste aircraft fuel) must be maintained in good condition, so as to prevent or minimize contamination of stormwater, and plainly labeled (e.g., "used oil," "Contaminated Jet A," etc.). The permittee must describe and implement measures that prevent or minimize contamination of precipitation/runoff from storage areas. The following BMPs or their equivalents shall be considered: indoor storage of materials; centralized storage areas for waste materials; and installation of berms/dikes around storage areas.

(e) Airport fuel system and fueling areas - The permittee must describe and implement measures that prevent or minimize the discharge of fuels to the storm sewer/surface waters resulting from fuel servicing activities or other operations conducted in support of the airport fuel system. The following BMPs (or their equivalents) shall be considered: implementing spill and overflow practices (e.g., placing absorptive materials beneath aircraft during fueling operations); using dry cleanup methods; and collecting the stormwater runoff.

(2) Source reduction - Owners or operators who conduct deicing/anti-icing operations shall consider alternatives to the use of urea and glycol-based deicing/anti-icing chemicals to reduce the aggregate amount of deicing/anti-icing chemicals used and/or lessen the environmental impact. Chemical options to replace ethylene glycol, propylene glycol and urea include: potassium acetate; magnesium acetate; calcium acetate; and anhydrous sodium acetate.

(a) Runway deicing operations - Owners or operators shall evaluate present application rates to ensure against excessive over application by analyzing application rates and adjusting as necessary, consistent with considerations of flight safety. Also the following BMP options shall be considered (or their equivalents): metered application of chemicals; prewetting dry chemical constituents prior to application; installation of runway ice detection systems; and implementing anti-icing operations as a preventive measure against ice buildup.

(b) Aircraft deicing/anti-icing operations - Owners or operators shall determine whether excessive application of deicing/anti-icing chemicals occurs, and adjust as necessary, consistent with considerations of flight safety. This evaluation should be carried out by the personnel most familiar with the particular aircraft and flight

**a. Site description**

(1) Site map - The site map shall identify where any of the following activities may be exposed to precipitation/surface runoff: aircraft and runway deicing/anti-icing operations; fueling stations; aircraft, ground vehicle and equipment maintenance/cleaning areas; and storage areas for aircraft, ground vehicles and equipment awaiting maintenance.

(2) Summary of potential pollutant sources - A narrative description of the potential pollutant sources from the following activities: aircraft, runway, ground vehicle and equipment maintenance and cleaning; aircraft and runway deicing/anti-icing operations (including apron and centralized aircraft deicing/anti-icing stations, runways, taxiways and ramps). Facilities which conduct deicing/anti-icing operations shall maintain a record of the types (including the Material Safety Data Sheets (MSDS)) and monthly quantities of deicing/anti-icing chemicals used, either as measured amounts, or in the absence of metering, as estimated amounts. This includes all deicing/anti-icing chemicals, not just glycols and urea (e.g., potassium acetate). Tenants and fixed-base operators who conduct deicing/anti-icing operations shall provide the above information to the airport authority for inclusion in the stormwater pollution prevention plan for the entire facility.

**b. Stormwater controls**

**(1) Good housekeeping**

(a) Aircraft, ground vehicle and equipment maintenance areas - The permittee must describe and implement measures that prevent or minimize the contamination of stormwater runoff from all areas used for aircraft, ground vehicle and equipment maintenance (including the maintenance conducted on the terminal apron and in dedicated hangars). The following practices (or their equivalents) shall be considered: performing maintenance activities indoors; maintaining an organized inventory of materials used in the maintenance areas; draining all parts of fluids prior to disposal; preventing the practice of hosing down the apron or hangar floor; using dry cleanup methods; and collecting the stormwater runoff from the maintenance area and providing treatment or recycling.

(b) Aircraft, ground vehicle and equipment cleaning areas - Permittees shall ensure that cleaning of equipment is conducted in designated areas only and clearly identify these areas on the ground and delineate them on the site map. The permittee must describe and implement measures that prevent or minimize the contamination of the stormwater runoff from cleaning areas.

## **Sector S - Air Transportation**

**1. Discharges Covered Under This Section** - The requirements listed under this section apply to stormwater discharges associated with industrial activity from air transportation facilities including air transportation (scheduled and non-scheduled); air courier services; airports; flying fields (except those maintained by aviation clubs); air terminal services including air traffic control (except government); aircraft storage at airports; aircraft upholstery repair; airfreight handling at airports; airport hangar rental; airport leasing, if operating airport; airport terminal services; hangar operation; airport, aircraft service and maintenance including aircraft cleaning and janitorial service; aircraft servicing /repairing (except on a factory basis); vehicle maintenance shops; material handling facilities; equipment clearing operations; and airport/aircraft deicing and anti-icing. [Note: For the purpose of this section, the term "deicing" is defined as the process to remove frost, snow, or ice and "anti-icing" is the process which prevents the accumulation of frost, snow, or ice.] Only those portions of the facility that are either involved in vehicle maintenance (including vehicle rehabilitation, mechanical repairs, painting, fueling, and lubrication), equipment cleaning operations, or deicing/anti-icing operations are addressed under this section.

### **2. Special Conditions**

a. **Prohibition of non-stormwater discharges** - In addition to the general non-stormwater prohibition in Paragraph I.D.1, the following discharges not covered by this permit include, but are not limited to: aircraft, ground vehicle, runway and equipment washwaters, and dry weather discharges of deicing/anti-icing chemicals. These discharges must be covered by a separate SPDES permit.

b. **Releases of reportable quantities of hazardous substances and oil** - Each individual permittee is required to report spills as described at Part II.B. If an airport authority is the sole permittee, then the sum total of all spills at the airport must be assessed against the reportable quantity. If the airport authority is a copermittee with other deicing/anti-icing owners or operators at the airport, such as numerous different airlines, the assessed amount must be the summation of spills by each copermittee. If separate, distinct individual permittees exist at the airport, then the amount spilled by each separate permittee must be the assessed amount for the reportable quantity determination.

**3. Stormwater Pollution Prevention Plan Requirements** - SWPPPs developed for areas of the facility occupied by tenants of the airport shall be integrated with the plan for the entire airport. For the purposes of this permit, tenants of the airport facility include airline passenger or cargo companies, fixed based owners or operators and other parties who have contracts with the airport authority to conduct business operations on airport property and whose operations result in stormwater discharges associated with industrial activity. In addition to the requirements of Part III, the SWPPP shall include, at a minimum, the following items.

(f) Drydock activities - The plan must address the routine maintenance and cleaning of the drydock to minimize the potential for pollutants in the stormwater runoff. The plan must describe the procedures for cleaning the accessible areas of the drydock prior to flooding and final cleanup after the vessel is removed and the dock is raised. Cleanup procedures for oil, grease, or fuel spills occurring on the drydock must also be included within the plan. The permittee shall consider the following measures (or their equivalents): sweeping rather than hosing off debris /spent blasting material from the accessible areas of the drydock prior to flooding and having absorbent materials and oil containment booms readily available to contain/cleanup any spills.

(g) General yard area - The plan must include a schedule for routine yard maintenance and cleanup. Scrap metal, wood, plastic, miscellaneous trash, paper, glass, industrial scrap, insulation, welding rods, packaging, etc., must be routinely removed from the general yard area.

(2) Preventative maintenance - As part of the facility's preventive maintenance program, stormwater management devices shall be inspected and maintained in a timely manner (e.g., oil/water separators and sediment traps cleaned to ensure that spent abrasives, paint chips and solids are intercepted and retained prior to entering the storm drainage system). Facility equipment and systems shall also be inspected and tested to uncover conditions that could cause breakdowns or failures resulting in discharges of pollutants to surface waters.

(3) Routine facility inspections - The following areas shall be included in all monthly inspections: pressure washing area; blasting, sanding, and painting areas; material storage areas; engine maintenance/repair areas; material handling areas; drydock area; and general yard area.

(4) Employee training - Training shall address, at a minimum, the following activities (as applicable): used oil management; spent solvent management; proper disposal of spent abrasives; proper disposal of vessel wastewaters, spill prevention and control; fueling procedures; general good housekeeping practices; painting and blasting procedures; and used battery management.

(5) Comprehensive site compliance evaluation - The permittee shall conduct regularly scheduled evaluations at least once a year and address those areas contributing to a stormwater discharge associated with industrial activity (e.g., pressure washing area, blasting/sanding areas, painting areas, material storage areas, engine maintenance/repair areas, material handling areas, and drydock area). These sources shall be inspected for evidence of, or the potential for, pollutants entering the drainage system.

(b) Blasting and painting areas - The permittee must describe and implement measures to prevent spent abrasives, paint chips and overspray from discharging into the receiving waterbody or the storm sewer system. To prevent the discharge of contaminants, the permittee shall consider containing all blasting/painting activities, or using other methods, such as hanging plastic barriers or tarpaulins during blasting or painting operations to contain debris. Where necessary, the plan should include a schedule for regularly cleaning storm systems to remove deposits of abrasive blasting debris and paint chips. The plan should include any standard operating practices with regard to blasting and painting activities, such as the prohibition of uncontained blasting/painting over open water or the prohibition of blasting/painting during windy conditions that can render containment ineffective.

(c) Material storage areas - All containerized materials (fuels, paints, solvents, waste oil, antifreeze, batteries) must be plainly labeled and stored in a protected, secure location away from drains. The permittee must describe and implement measures to prevent or minimize contamination of precipitation/surface runoff from the storage areas. The plan must specify which materials are stored indoors and consider containment or enclosure for materials that are stored outdoors. The permittee must consider implementing an inventory control plan to limit the presence of potentially hazardous materials on-site. Where abrasive blasting is performed, the plan must specifically include a discussion on the storage and disposal of spent abrasive materials generated at the facility.

(d) Engine maintenance and repair areas - The permittee must describe and implement measures to prevent or minimize contamination of precipitation/surface runoff from all areas used for engine maintenance and repair. The permittee shall consider the following measures (or their equivalent): performing all maintenance activities indoors; maintaining an organized inventory of materials used in the shop; draining all parts of fluids prior to disposal; prohibiting the practice of hosing down the shop floor; using dry cleanup methods; and treating and/or recycling stormwater runoff collected from the maintenance area.

(e) Material handling areas - The permittee must describe and implement measures to prevent or minimize contamination of precipitation/surface runoff from material handling operations and areas (e.g., fueling, paint and solvent mixing, disposal of process wastewater streams from vessels). The permittee shall consider the following methods (or their equivalents): covering fueling areas; using spill/overflow protection; mixing paints and solvents in a designated area (preferably indoors or under a shed); and minimizing runoff of stormwater to material handling areas.



## **Sector R - Ship and Boat Building or Repair Yards**

1. **Discharges Covered Under This Section** - The requirements listed under this section apply to stormwater discharges associated with industrial activity from facilities engaged in ship and boat building and repairing (SIC Code 373). (According to the U.S. Coast Guard, a vessel 65 feet or greater in length is referred to as a ship and a vessel smaller than 65 feet is a boat.)

### **2. Special Conditions**

a. **Prohibition of non-stormwater discharges** - In addition to the general non-stormwater prohibition in Paragraph I.D.1, the following discharges not covered by this permit include, but are not limited to : bilge and ballast water, pressure wash water, sanitary wastes, and cooling water originating from vessels.

3. **Stormwater Pollution Prevention Plan Requirements** - In addition to the requirements of Part III, the SWPPP shall include, at a minimum, the following items.

#### **a. Site description**

(1) **Site map** - The site map shall identify the locations where any of the following activities may be exposed to precipitation/surface runoff: fueling; engine maintenance/repair; vessel maintenance/repair; pressure washing; painting; sanding; blasting; welding; metal fabrication; loading/unloading areas; locations used for the treatment, storage or disposal of wastes; liquid storage tanks; liquid storage areas (e.g., paint, solvents, resins); and material storage areas (e.g., blasting media, aluminum, steel, scrap iron).

(2) **Potential pollutant sources** - The plan shall include a description of the following additional sources and activities that have potential pollutants associated with them (if applicable): outdoor manufacturing/processing activities (e.g., welding, metal fabricating); and significant dust/particulate generating processes (e.g., abrasive blasting, sanding, painting).

#### **b. Stormwater controls**

##### **(1) Good housekeeping measures**

(a) **Pressure washing area** - If pressure washing is used to remove marine growth from vessels, the discharge water must be permitted as a process wastewater by a separate SPDES permit.

shall be inspected for evidence of, or the potential for, pollutants entering the drainage system.

4. **Benchmark Monitoring and Reporting Requirements** - Water transportation facilities are required to monitor their stormwater discharges for the pollutants of concern listed in Table VIII-Q-1.

Table VIII-Q-1.  
Sector Q - Benchmark Monitoring Requirements

Pollutants of Concern	Analytical Method	Benchmark Monitoring Cut-Off Concentration
<b>Water Transportation Facilities (SIC 4412-4499)</b>		
Total Recoverable Aluminum	EPA 200.7	750 ug/L
Total Recoverable Iron	EPA 200.7	1 mg/L
Total Recoverable Lead	EPA 200.7	82 ug/L
Total Recoverable Zinc	EPA 200.7	120 ug/L

(preferably indoors or under a shed); and minimizing runoff of stormwater to material handling areas.

(f) Drydock activities - The plan must address the routine maintenance and cleaning of the drydock to minimize the potential for pollutants in the stormwater runoff. The plan must describe the procedures for cleaning the accessible areas of the drydock prior to flooding and final cleanup after the vessel is removed and the dock is raised. Cleanup procedures for oil, grease, or fuel spills occurring on the drydock must also be included within the plan. The permittee shall consider the following measures (or their equivalents): sweeping rather than hosing off debris /spent blasting material from the accessible areas of the drydock prior to flooding; and having absorbent materials and oil containment booms readily available to contain/cleanup any spills.

(g) General yard area - The plan must include a schedule for routine yard maintenance and cleanup. Scrap metal, wood, plastic, miscellaneous trash, paper, glass, industrial scrap, insulation, welding rods, packaging, etc., must be routinely removed from the general yard area.

(2) Preventative Maintenance - As part of the facility's preventive maintenance program, stormwater management devices shall be inspected and maintained in a timely manner (e.g., oil/water separators and sediment traps cleaned to ensure that spent abrasives, paint chips and solids are intercepted and retained prior to entering the storm drainage system). Facility equipment and systems shall also be inspected and tested to uncover conditions that could cause breakdowns or failures resulting in discharges of pollutants to surface waters.

(3) Routine facility inspections - The following areas shall be included in all monthly inspections: pressure washing area; blasting, sanding, and painting areas; material storage areas; engine maintenance and repair areas; material handling areas; drydock area; and general yard area.

(4) Employee training - Training shall address, at a minimum, the following activities (as applicable): used oil management; spent solvent management; disposal of spent abrasives; disposal of vessel wastewaters; spill prevention and control; fueling procedures; general good housekeeping practices; painting and blasting procedures; and used battery management.

(5) Comprehensive site compliance evaluation - The permittee shall conduct regularly scheduled evaluations at least once a year and address those areas contributing to a stormwater discharge associated with industrial activity (e.g., pressure washing area, blasting/sanding areas, painting areas, material storage areas, engine maintenance/repair areas, material handling areas, and drydock area). These sources

the pressure washing area; the method for the removal of the visible solids; the methods of disposal of the collected solids; and where the discharge will be released.

(b) Blasting and painting areas - The permittee must describe and implement measures to prevent spent abrasives, paint chips, and overspray from discharging into the receiving water or the storm sewer system. The permittee may consider containing all blasting/painting activities, or the use of other measures to prevent or minimize the discharge of contaminants (e.g., hanging plastic barriers or tarpaulins during blasting or painting operations to contain debris). Stormwater conveyances shall be regularly cleaned to remove deposits of abrasive blasting debris and paint chips. The plan shall include any standard operating practices with regard to blasting and painting activities, such as the prohibition of uncontained blasting/painting over open water, or the prohibition of blasting/painting during windy conditions which can render containment ineffective.

(c) Material storage areas - All containerized materials (fuels, paints, solvents, waste oil, antifreeze, batteries) must be plainly labeled and stored in a protected, secure location away from drains. The permittee must describe and implement measures to prevent or minimize the contamination of precipitation/surface runoff from the storage areas. The plan must specify which materials are stored indoors and consider containment or enclosure for materials that are stored outdoors. The permittee must consider implementing an inventory control plan to limit the presence of potentially hazardous materials on-site. Where abrasive blasting is performed, the plan must specifically include a discussion on the storage and disposal of spent abrasive materials generated at the facility.

(d) Engine maintenance and repair areas - The permittee must describe and implement measures to prevent or minimize contamination of precipitation/surface runoff from all areas used for engine maintenance and repair. The permittee shall consider the following measures (or their equivalent): performing all maintenance activities indoors; maintaining an organized inventory of materials used in the shop; draining all parts of fluids prior to disposal; prohibiting the practice of hosing down the shop floor; using dry cleanup methods; and treating and/or recycling stormwater runoff collected from the maintenance area.

(e) Material handling areas - The permittee must describe and implement measures to prevent or minimize contamination of precipitation/surface runoff from material handling operations and areas (e.g., fueling, paint and solvent mixing, disposal of process wastewater streams from vessels). The permittee shall consider the following measures (or their equivalents): covering fueling areas; using spill/overflow protection; mixing paints and solvents in a designated area

## **Sector Q - Water Transportation**

1. **Discharges Covered Under This Section** - The requirements listed under this section apply to stormwater discharges associated with industrial activity from water transportation facilities (generally identified by SIC Major Group 44), that have vehicle (vessel) maintenance shops and/or equipment cleaning operations. The water transportation industry includes facilities engaged in foreign or domestic transport of freight or passengers in deep sea or inland waters; marine cargo handling operations; ferry operations; towing and tugboat services; and marinas.

### **2. Special Conditions**

a. **Prohibition of non-stormwater discharges** - In addition to the general non-stormwater prohibition in Paragraph I.D.1, the following discharges not covered by this permit include, but are not limited to: bilge and ballast water, sanitary wastes, pressure wash water, and cooling water originating from vessels.

3. **Stormwater Pollution Prevention Plan Requirements** - In addition to the requirements of Part III, the SWPPP shall include, at a minimum, the following items.

#### **a. Site description**

(1) **Site map** - The site map shall identify the locations where any of the following activities may be exposed to precipitation/surface runoff: fueling; engine maintenance/repair; vessel maintenance/repair, pressure washing; painting; sanding; blasting; welding; metal fabrication; loading/unloading areas; locations used for the treatment, storage or disposal of wastes; liquid storage tanks; liquid storage areas (e.g., paint, solvents, resins); and material storage areas (e.g., blasting media, aluminum, steel, scrap iron).

(2) **Summary of potential pollutant sources** - The plan shall describe the following additional sources and activities that have potential pollutants associated with them: outdoor manufacturing or processing activities (i.e., welding, metal fabricating); and significant dust or particulate generating processes (e.g., abrasive blasting, sanding, painting).

#### **b. Stormwater controls**

##### **(1) Good housekeeping**

(a) **Pressure washing area** - If pressure washing is used to remove marine growth from vessels, the discharge water must be permitted by a separate SPDES permit. The SWPPP must describe: the measures to collect or contain the discharge from

(2) **Routine facility inspections** - The following areas /activities shall be included in all inspections: storage area for vehicles /equipment awaiting maintenance; fueling areas; indoor and outdoor vehicle/equipment maintenance areas; material storage areas; vehicle/equipment cleaning areas; and loading/unloading areas.

(3) **Employee training** - Employee training shall take place, at a minimum, annually (once per calendar year). Employee training must address the following, as applicable: used oil and spent solvent management; fueling procedures; general good housekeeping practices; proper painting procedures; and used battery management.

3. **Benchmark Monitoring and Reporting Requirements** - Land transportation and warehousing facilities are required to monitor their stormwater discharges for the pollutant of concern listed in Table VIII-P-1.

Table VIII-P-1.  
Sector P - Benchmark Monitoring Requirements

Pollutants of Concern	Analytical Method	Benchmark Monitoring Cut-Off Concentration
<b>Land Transportation and Warehousing Facilities (SIC Codes 4011, 4013, 4111-4173, 4212-4231, 4311 and 5171)</b>		
Oil & Grease	EPA 1664 or EPA 1664A	15 mg/L
Chemical Oxygen Demand (COD)	EPA 410.4	120 mg/L
Benzene	EPA 602	50 ug/L
Ethylbenzene	EPA 602	50 ug/L
Toluene	EPA 602	50 ug/L
Xylene	EPA 602	50 ug/L

(c) Material storage areas - Storage vessels of all materials (e.g., for used oil/oil filters, spent solvents, paint wastes, hydraulic fluids) must be maintained in good condition, so as to prevent contamination of stormwater, and plainly labeled (e.g., "used oil," "spent solvents," etc.). The permittee shall consider the following measures (or their equivalents): indoor storage of the materials; installation of berms/dikes around the areas, minimizing runoff of stormwater to the areas; using dry cleanup methods; and treating and/or recycling the collected stormwater runoff.

(d) Vehicle and equipment cleaning areas - The permittee shall describe and implement measures that prevent or minimize contamination of stormwater runoff from all areas used for vehicle/equipment cleaning. The permittee shall consider the following measures (or their equivalents): performing all cleaning operations indoors; covering the cleaning operation; ensuring that all washwaters drain to a proper collection system (i.e., not the stormwater drainage system unless SPDES permitted); and treating and/or recycling the collected stormwater runoff.

Note: The discharge of vehicle/equipment wash waters, including tank cleaning operations, are not authorized by this permit and must be covered under a separate SPDES permit or discharged to a sanitary sewer in accordance with applicable industrial pretreatment requirements.

(e) Vehicle and equipment maintenance areas - The permittee shall describe and implement measures that prevent or minimize contamination of the stormwater runoff from all areas used for vehicle/equipment maintenance. The permittee shall consider the following measures (or their equivalents): performing maintenance activities indoors; using drip pans; keeping an organized inventory of materials used in the shop; draining all parts of fluids prior to disposal; prohibiting wet clean up practices where the practices would result in the discharge of pollutants to stormwater drainage systems; using dry cleanup methods; treating and/or recycling collected stormwater runoff; and minimizing runoff of stormwater to maintenance areas.

(f) Locomotive sanding (loading sand for traction) areas - The plan must describe measures that prevent or minimize contamination of the stormwater runoff from areas used for locomotive sanding. The permittee shall consider the following measures (or their equivalents): covering sanding areas; minimizing stormwater runoff; or appropriate sediment removal practices to minimize the off-site transport of sanding material by stormwater.

## **Sector P - Land Transportation and Warehousing**

1. **Discharges Covered Under This Section** - The requirements listed under this section apply to stormwater discharges associated with industrial activity from land transportation and warehousing facilities (generally identified by SIC Codes 4011, 4013, 4111-4173, 4212-4231, 4311 and 5171), that have vehicle and equipment maintenance shops (vehicle and equipment rehabilitation, mechanical repairs, painting, fueling and lubrication) and/or equipment cleaning operations.

2. **Stormwater Pollution Prevention Plan Requirements** - In addition to the requirements of Part III, the SWPPP shall include, at a minimum, the following items.

a. **Site description**

(1) **Site Map** - The site map shall identify the locations of any of the following activities or sources: fueling stations; vehicle/equipment maintenance or cleaning areas; storage areas for vehicle/equipment with actual or potential fluid leaks; loading/unloading areas; areas where treatment, storage or disposal of wastes occur; liquid storage tanks; processing areas; storage areas; and all monitoring areas.

b. **Summary of potential pollutant sources** - The plan shall describe and assess the potential for the following to contribute pollutants to stormwater discharges: on-site waste storage or disposal; dirt/gravel parking areas for vehicles awaiting maintenance; and fueling areas.

c. **Stormwater controls**

(2) **Good housekeeping**

(a) **Vehicle and equipment storage areas** - The storage of vehicles and equipment awaiting maintenance with actual or potential fluid leaks must be confined to designated areas (delineated on the site map). The permittee shall consider the following measures (or their equivalents): the use of drip pans under vehicles and equipment; indoor storage of vehicles and equipment; installation of berms or dikes; use of absorbents; roofing or covering storage areas; and cleaning pavement surface to remove oil and grease.

(b) **Fueling areas** - The permittee shall describe and implement measures that prevent or minimize contamination of the stormwater runoff from fueling areas. The permittee shall consider the following measures (or their equivalents): covering the fueling area; using spill/overflow protection and cleanup equipment; minimizing stormwater runoff to the fueling area; using dry cleanup methods; and treating and/or recycling collected stormwater runoff.



Table VIII-O-1.  
Sector O - Benchmark Monitoring Requirements

Pollutants of Concern	Analytical Method	Benchmark Monitoring Cut-Off Concentration
<b>Steam Electric Generating Facilities (Industrial Activity Code "SE")</b>		
Oil & Grease	EPA 1664 or EPA 1664A	15 mg/L
PCBs	EPA 608	0.065 ug/L per Aroclor*
Total Recoverable Iron	EPA 200.7	1 mg/L

\* Required for Aroclors 1016, 1221, 1232, 1242, 1248, 1254 and 1260

(l) Areas adjacent to disposal ponds or landfills - The permittee shall describe and implement measures that prevent or minimize contamination of stormwater runoff from areas adjacent to disposal ponds or landfills. The permittee must develop procedures to:

(i) Reduce ash residue which may be tracked on to access roads traveled by residue trucks or residue handling vehicles; and

(ii) Reduce ash residue on exit roads leading into and out of residue handling areas.

(m) Landfills, scrapyards, surface impoundments, non-compliant landfills, general refuse sites - The plan must address and include appropriate BMPs for landfills, scrapyards, surface impoundments, non-compliant landfills and general refuse sites.

(n) Vehicle maintenance activities - For vehicle maintenance activities performed on the plant site, the permittee shall use the applicable BMPs outlined in Sector P.

(o) Material storage areas - The permittee shall describe and implement measures that prevent or minimize contamination of stormwater runoff from material storage areas (including areas used for temporary storage of miscellaneous products, and construction materials stored in lay down areas). The permittee shall consider the use of the following measures (or their equivalents): flat yard grades; runoff collection in graded swales or ditches; erosion protection measures at steep outfall sites (e.g., concrete chutes, riprap, stilling basins); covering lay down areas storing materials indoors; and covering materials temporarily with polyethylene, polyurethane, polypropylene, or hypalon. Stormwater runoff may be minimized by constructing an enclosure or building a berm around the area.

(2) Comprehensive site compliance evaluation - As part of the evaluation, qualified facility personnel shall inspect the following areas on a monthly basis: coal handling areas, loading/unloading areas, switchyards, fueling areas, bulk storage areas, ash handling areas, areas adjacent to disposal ponds and landfills, maintenance areas, liquid storage tanks, and long term and short term material storage areas.

4. Numeric Effluent Limitations - Permittees with point sources of coal pile runoff associated with steam electric power generation must monitor these stormwater discharges for the presence of TSS and for pH at least annually in accordance with Paragraph IV.A.1.c.

5. Benchmark Monitoring and Reporting Requirements - Steam electric power generating facilities are required to monitor their stormwater discharges for the pollutant of concern listed in Table VIII-O-1.

(f) Liquid storage tanks - The permittee shall describe and implement measures that prevent or minimize contamination of stormwater runoff from aboveground liquid storage tanks. At a minimum the permittee must consider employing the following measures (or their equivalents):

- (i) Use of protective guards around tanks;
- (ii) Use of containment curbs;
- (iii) Use of spill and overflow protection; and
- (iv) Use of dry cleanup methods.

(g) Large bulk fuel storage tanks - The permittee shall describe and implement measures that prevent or minimize contamination of stormwater runoff from large bulk fuel storage tanks. At a minimum the permittee must consider employing containment berms (or its equivalent). The permittee shall also comply with applicable state and federal laws, including Spill Prevention Control and Countermeasures (SPCC).

(h) Spill reduction measures - The permittee shall describe and implement measures to reduce the potential for an oil/chemical spill, or reference the appropriate section of their SPCC plan. At a minimum the structural integrity of all aboveground tanks, pipelines, pumps and other related equipment shall be visually inspected on a weekly basis. All repairs deemed necessary based on the findings of the inspections shall be completed immediately to reduce the incidence of spills and leaks occurring from such faulty equipment.

(i) Oil bearing equipment in switchyards - The permittee shall describe and implement measures to prevent or minimize contamination of surface runoff from oil bearing equipment in switchyard areas. The permittee shall consider the use of level grades and gravel surfaces to retard flows and limit the spread of spills, and the collection of stormwater runoff in perimeter ditches.

(j) Residue hauling vehicles - All residue hauling vehicles shall be inspected for proper covering over the load, adequate gate sealing and overall integrity of the container body. Vehicles without load coverings or adequate gate sealing, or with leaking containers or beds must be repaired as soon as practicable.

(k) Ash loading areas - The permittee shall describe and implement procedures to reduce or control the tracking of ash/residue from ash loading areas where practicable, clear the ash building floor and immediately adjacent roadways of spillage, debris and excess water before departure of each loaded vehicle.

- (i) Develop procedures for the inspection of delivery vehicles arriving on the plant site, and ensure overall integrity of the body or container; and
  - (ii) Develop procedures to deal with leakage/spillage from vehicles or containers.
- (c) Fuel oil unloading areas - The plan must describe measures that prevent or minimize contamination of precipitation/surface runoff from fuel oil unloading areas. At a minimum the permittee must consider using the following measures, or an equivalent:
- (i) Use of containment curbs in unloading areas;
  - (ii) During deliveries, having station personnel familiar with spill prevention and response procedures present to ensure that any leaks/spills are immediately contained and cleaned up; and
  - (iii) Use of spill and overflow protection (e.g., drip pans, drip diapers, and/or other containment devices placed beneath fuel oil connectors to contain potential spillage during deliveries or from leaks at the connectors).
- (d) Chemical loading/unloading areas - The permittee must describe and implement measures that prevent or minimize the contamination of precipitation/surface runoff from chemical loading/unloading areas. At a minimum the permittee must consider using the following measures (or their equivalents):
- (i) Use of containment curbs at chemical loading/unloading areas to contain spills;
  - (ii) During deliveries, having station personnel familiar with spill prevention and response procedures present to ensure that any leaks/spills are immediately contained and cleaned up; and
  - (iii) Covering chemical loading/unloading areas and storing chemicals indoors.
- (e) Miscellaneous loading/unloading areas - The permittee shall describe and implement measures that prevent or minimize the contamination of stormwater runoff from loading and unloading areas. The permittee shall consider the following, at a minimum (or their equivalents): covering the loading area; grading, berming, or curbing around the loading area to divert runoff; or locating the loading/unloading equipment and vehicles so that leaks are contained in existing containment and flow diversion systems.

## **Sector O - Steam Electric Generating Facilities**

1. **Discharges Covered Under This Section** - The requirements listed under this section apply to stormwater discharges associated with industrial activity from steam electric power generating facilities using coal, natural gas, oil, nuclear energy, etc. to produce a steam source, including coal handling areas; stormwater discharges from coal pile runoff subject to numeric effluent limitations are eligible for coverage under this permit, but are subject to effluent limitations established by 40 CFR 423; and dual fuel co-generation facilities. Stormwater discharges not covered by this permit include: ancillary facilities (e.g., fleet centers, gas turbine stations, and substations ) that are not contiguous to a steam electric power generating facility; and heat capture co-generation facilities.

2. **Special Conditions**

a. **Prohibition of non-stormwater discharges** - In addition to the general non-stormwater prohibition in Paragraph I.D.1, non-stormwater discharges subject to effluent limitation guidelines are also not covered by this permit.

3. **Stormwater Pollution Prevention Plan Requirements** - In addition to the requirements of Part III, the plan shall include, at a minimum, the following items.

a. **Site description.**

(1) **Site map** - The site map shall identify the locations of any of the following activities or sources that may be exposed to precipitation/surface runoff: storage tanks, scrap yards, general refuse areas; short and long term storage of general materials (including, but not limited to: supplies, construction materials, plant equipment, oils, fuels, used and unused solvents, cleaning materials, paint, water treatment chemicals, fertilizer, and pesticides); landfills; construction sites; and stock pile areas (such as coal or limestone piles).

b. **Stormwater controls**

(1) **Good housekeeping measures**

(a) **Fugitive dust emissions** - The permittee shall describe and implement measures that prevent or minimize fugitive dust emissions from coal handling areas. The permittee shall consider establishing procedures to minimize off-site tracking of coal dust such as installing specially designed tires, or washing vehicles in a designated area before they leave the site, and controlling the wash water.

(b) **Delivery vehicles** - The plan must describe measures that prevent or minimize contamination of stormwater runoff from delivery vehicles arriving on the plant site. At a minimum the permittee shall consider the following:

4. **Benchmark Monitoring and Reporting Requirements** - Scrap recycling and waste recycling facilities (nonsource-separated facilities only), and facilities engaged in dismantling ships, marine salvaging, and marine wrecking - ships for scrap are required to monitor their stormwater discharges for the pollutants of concern listed in Table VIII-N-1.

Table VIII-N-1.  
Sector N - Benchmark Monitoring Requirements

Pollutants of Concern	Analytical Method	Benchmark Monitoring Cut-Off Concentration
<b>Scrap Recycling and Waste Recycling Facilities (nonsource-separated facilities only) (SIC 5093) and Facilities Engaged in Dismantling Ships, Marine Salvaging, and Marine Wrecking - Ships For Scrap (SIC 4499, limited to list)</b>		
Total Suspended Solids (TSS)	EPA 160.2	100 mg/L
Chemical Oxygen Demand (COD)	EPA 410.4	120 mg/L
Oil and Grease	EPA 1664 or EPA 1664A	15 mg/L
Total Recoverable Aluminum	EPA 200.7	750 ug/L
Total Recoverable Cadmium	EPA 200.7	16 ug/L
Total Chromium	EPA 200.7	1.8 mg/L
Total Recoverable Copper	EPA 200.7	64 ug/L
Total Recoverable Iron	EPA 200.7	1 mg/L
Total Recoverable Lead	EPA 200.7	82 ug/L
Total Recoverable Zinc	EPA 200.7	120 ug/L
<b>For Scrap Recycling and Waste Recycling Facilities (nonsource-separated facilities) (SIC 5093) Which Include Stormwater Discharges from Shredder Operations and Storage Areas, Permittees Must Sample For the Above Parameters Plus the Following:</b>		
Total Recoverable Mercury	EPA 245.7	2.4 ug/L
PCBs	EPA 608	0.065 ug/L per Aroclor*
Benzene	EPA 602	50 ug/L
Ethylbenzene	EPA 602	50 ug/L
Toluene	EPA 602	50 ug/L
Xylene	EPA 602	50 ug/L

\* Required for Aroclors 1016, 1221, 1232, 1242, 1248, 1254 and 1260

e. Facilities engaged in dismantling ships, marine salvaging, and marine wrecking ships for scrap - The following SWPPP special conditions have been established for facilities that are engaged in dismantling ships, marine salvaging, and marine wrecking - ships for scrap.

(1) Vessel Breaking/Scrapping Activities - Scrapping of vessels shall be accomplished ashore beyond the range of mean high tide, whenever practicable. If this activity must be conducted while a vessel is afloat or grounded in state waters, then the permittee must employ BMPs to reduce the amount of pollutants released. The following BMPs shall be implemented during those periods when vessels (ships, barges, yachts, etc.) are brought to the facility's site for recycling, scrapping and storage prior to scrapping:

(a) Fixed or floating platforms sufficiently sized and constructed to catch and prevent scrap materials and pollutants from entering waters of the United States (or equivalent measures approved by the department) shall be used as work surfaces when working on or near the water surface. These platforms shall be cleaned as required to prevent pollutants from entering state waters and at the end of each work shift. All scrap metals and pollutants shall be collected in a manner to prevent releases (containerization is recommended).

(b) There shall be no discharge of oil or oily wastewater at the facility. Drip pans and other protective devices shall be required for all oil and oily waste transfer operations to catch incidental spillage and drips from hose nozzles, hose racks, drums or barrels. Drip pans and other protective devices shall be inspected and maintained to prevent releases. Oil and oily waste must be disposed at a permitted facility and adequate documentation of off-site disposition shall be retained for review by the board upon request.

(c) During the storage/breaking/scrapping period, oil containment boom(s) shall be deployed either around the vessel being scrapped, or across the mouth of the facility's wet slip, to contain pollutants in the event of a spill. Booms must be inspected, maintained, and repaired as needed. Oil, grease and fuel spills shall be prevented from reaching state waters. Cleanup shall be carried out promptly after an oil, grease, and/or fuel spill is detected.

(d) Paint and solvent spills shall be immediately cleaned up to prevent pollutants from reaching storm drains, deck drains, and state waters.

(e) Contaminated bilge and ballast water shall not be discharged to waters of the United States. If it becomes necessary to dispose of contaminated bilge and ballast waters during a vessel breaking activity, the wastewater must be disposed at a permitted facility and adequate documentation of off-site disposition shall be retained for review by the board upon request.

(c) Provide dikes and curbs for secondary containment (e.g., around bales of recyclable waste paper);

(d) Divert surface runoff away from outside material storage areas;

(e) Provide covers over containment bins, dumpsters, roll-off boxes; and

(f) Store the equivalent one day's volume of recyclable materials indoors.

(3) Indoor storage and material processing - The plan shall include measures to minimize the release of pollutants from indoor storage and processing areas. BMP options include:

(a) Schedule routine good housekeeping measures for all storage and processing areas;

(b) Prohibit a practice of allowing tipping floor washwaters from draining to any portion of the storm sewer system; and

(c) Provide employee training on pollution prevention practices.

(4) Vehicle and equipment maintenance - The plan shall also provide for BMPs in those areas where vehicle and equipment maintenance is occurring outdoors. BMP options include:

(a) Prohibit vehicle and equipment washwater from discharging to the storm sewer system;

(b) Minimize or eliminate outdoor maintenance areas, wherever possible;

(c) Establish spill prevention and clean-up procedures in fueling areas;

(d) Avoid topping off fuel tanks;

(e) Divert runoff from fueling areas;

(f) Store lubricants and hydraulic fluids indoors; and

(g) Provide employee training on proper, handling, storage of hydraulic fluids and lubricants.



(a) Containment and diversionary structures to minimize contact with precipitation or runoff; and

(b) Use of dry cleanup methods, wet vacuuming, roof coverings, or runoff controls.

(4) Quarterly inspections - The quarterly inspections shall also include all areas where waste is generated, received, stored, treated or disposed that are exposed to either precipitation or stormwater runoff.

d. Recycling facilities (source separated materials) - The following SWPPP special conditions have been established for facilities that receive only source-separated recyclable materials primarily from nonindustrial and residential sources.

(1) Inbound recyclable material control - The plan shall include an inbound materials inspection program to minimize the likelihood of receiving nonrecyclable materials (e.g., hazardous materials) that may be a significant source of pollutants in surface runoff. BMP options include:

(a) Information and education measures to inform suppliers of recyclable materials on the types of materials that are acceptable and those that are not acceptable;

(b) A description of training measures for drivers responsible for pickup of recyclable materials;

(c) Clearly marking public drop-off containers regarding which materials can be accepted;

(d) Rejecting nonrecyclable wastes or household hazardous wastes at the source; and

(e) Procedures for the handling and disposal of nonrecyclable materials.

(2) Outdoor storage - The plan shall include procedures to minimize the exposure of recyclable materials to surface runoff and precipitation. The plan shall include good housekeeping measures to prevent the accumulation of particulate matter and fluids, particularly in high traffic areas. BMP options include:

(a) Provide totally-enclosed drop-off containers for the public;

(b) Install a sump/pump with each containment pit, and discharge collected fluids to a sanitary sewer system;

(1) Waste material storage (indoor) - The plan shall include measures and controls to minimize/eliminate contact between residual liquids from waste materials stored indoors and surface runoff. The plan may refer to applicable portions of other existing plans such as SPCC plans required under 40 CFR Part 112. BMP options include:

- (a) Procedures for material handling (including labeling and marking);
- (b) A sufficient supply of dry-absorbent materials or a wet vacuum system to collect spilled or leaked materials;
- (c) An appropriate containment structure, such as trenches, curbing, gutters or other equivalent measures; and
- (d) A drainage system, including appurtenances (e.g., pumps or ejectors, or manually operated valves), to handle discharges from diked or bermed areas. Drainage shall be discharged to an appropriate treatment facility, sanitary sewer system, or otherwise disposed of properly. Discharges from these areas may require coverage under a separate SPDES permit or industrial user permit under the pretreatment program.

(2) Waste material storage (outdoor) - The plan shall describe measures and controls to minimize contact between stored residual liquids and precipitation or runoff. The plan may refer to applicable portions of other existing plans such as SPCC plans required under 40 CFR Part 112. Discharges of precipitation from containment areas containing used oil shall also be in accordance with applicable sections of 40 CFR Part 112. BMP options include:

- (a) Appropriate containment structures (e.g., dikes, berms, curbing, pits ) to store the volume of the largest single tank, with sufficient extra capacity for precipitation;
- (b) Drainage control and other diversionary structures;
- (c) For storage tanks, provide corrosion protection and/or leak detection systems; and
- (d) Dry-absorbent materials or a wet vacuum system to collect spills.

(3) Truck and rail car waste transfer areas - The plan shall describe measures and controls to minimize pollutants in discharges from truck and rail car loading/unloading areas. The plan shall also address measures to clean up spills /leaks resulting from the transfer of liquid wastes. BMP options include:

(7) Spill prevention and response procedures - The SWPPP shall include measures to minimize stormwater contamination at loading/unloading areas, and from equipment or container failures. BMP options include:

- (a) Description of spill prevention and response measures to address areas that are potential sources of fluid leaks or spills;
- (b) Immediate containment and clean up of spills/leaks. If malfunctioning equipment is responsible for the spill/leak, repairs shall also be conducted as soon as possible;
- (c) Cleanup procedures shall be identified in the plan, including the use of dry absorbents. Where dry absorbent cleanup methods are used, an adequate supply of dry absorbent material shall be maintained on-site. Used absorbent material shall be disposed of properly;
- (d) Drums containing liquids, especially oil and lubricants, should be stored: indoors; in a bermed area; in overpack containers or spill pallets; or in similar containment devices;
- (e) Overfill prevention devices should be installed on all fuel pumps or tanks;
- (f) Drip pans or equivalent measures shall be placed under any leaking piece of stationary equipment until the leak is repaired. The drip pans shall be inspected for leaks and potential overflow and all liquids properly disposed of in accordance with RCRA requirements; and
- (g) An alarm and/or pump shut off system should be installed on outdoor equipment with hydraulic reservoirs exceeding 150 gallons in order to prevent draining the tank contents in the event of a line break. Alternatively, the equipment may have a secondary containment system capable of containing the contents of the hydraulic reservoir plus adequate freeboard for precipitation.

(8) Quarterly inspection program - All designated areas of the facility and equipment identified in the plan shall be inspected at least quarterly.

(9) Supplier notification program - The plan shall include a program to notify major suppliers which scrap materials will not be accepted at the facility or are only accepted under certain conditions.

c. Waste recycling facilities (liquid recyclable wastes)

(d) Use of dry-absorbents or other cleanup practices to collect and to dispose/recycle spilled/leaking fluids;

(e) Installation of low-level alarms or other equivalent protection devices on unattended hydraulic reservoirs over 150 gallons in capacity. Alternatively, provide secondary containment with sufficient volume to contain the entire volume of the reservoir;

(f) Containment or diversion structures such as dikes, berms, culverts, trenches, elevated concrete pads, and grading installed where appropriate to minimize contact of stormwater runoff with outdoor processing equipment or stored materials;

(g) Oil/water separators or sumps;

(h) Permanent or semipermanent covers in processing areas where there are residual fluids and grease;

(i) Retention and detention basins or ponds, sediment traps, vegetated swales or strips, to facilitate pollutant settling/filtration;

(j) Catch basin filters or sand filters; and

(k) Use and maintenance of silt and/or other fencing around shredder or other light material processing to prevent migration lightweight materials such as foam by wind and stormwater runoff.

(6) Scrap lead-acid battery program - The plan shall address measures and controls for the proper handling, storage and disposal of scrap lead-acid batteries. BMP options include:

(a) Segregate scrap lead-acid batteries from other scrap materials;

(b) A description of procedures and/or measures for the proper handling, storage and disposal of cracked or broken batteries;

(c) A description of measures to collect and dispose of leaking lead-acid battery fluid;

(d) A description of measures to minimize and, whenever possible, eliminate exposure of scrap lead-acid batteries to precipitation or runoff; and

(e) A description of employee training for the management of scrap batteries.

(ii) There is a barrier around the perimeter of the containment areas to prevent contact with stormwater run-on (e.g., berms, curbing, elevated pads, etc.);

(iii) There is a drainage collection system for runoff generated from containment areas;

(iv) There is a schedule to maintain the oil/water separator (or its equivalent); and

(v) Procedures are identified for the proper disposal or recycling of collected residual fluids.

(4) Scrap and waste material stockpiles/storage (covered or indoor storage) - The plan shall address measures and controls to minimize contact of residual liquids and particulate matter from materials stored indoors or under cover from coming in contact with surface runoff. BMP options include:

(a) Good housekeeping measures, including the use of dry absorbent or wet vacuum clean up methods, to contain or dispose/recycle residual liquids originating from recyclable containers;

(b) Prohibiting the practice of allowing washwater from tipping floors or other processing areas from discharging to the storm sewer system; and

(c) Disconnecting or sealing off all floor drains connected to the storm sewer system.

(5) Scrap and recyclable waste processing areas - The plan shall include measures and controls to minimize surface runoff from coming in contact with scrap processing equipment. In the case of processing equipment that generate visible amounts of particulate residue (e.g., shredding facilities), the plan shall describe measures to minimize the contact of residual fluids and accumulated particulate matter with runoff (i.e., through good housekeeping, preventive maintenance, etc.). BMP options include:

(a) Provide stormwater containment within a 30 foot perimeter of the following fixed equipment: shears, balers, shredders, grinders, screeners and conveyors;

(b) A schedule of regular inspections of equipment for leaks, spills, malfunctioning, worn or corroded parts or equipment;

(c) A preventive maintenance program for processing equipment;

(g) Liquid wastes, including used oil, shall be stored in materially compatible and non-leaking containers, and be disposed or recycled in accordance with all requirements under the Resource Recovery and Conservation Act (RCRA), and state or local requirements.

(2) Scrap and waste material stockpiles/storage (outdoor) - The plan must describe measures and controls to minimize contact of stormwater runoff with stockpiled materials, processed materials and nonrecyclable wastes. BMP options include:

- (a) Maintain lower volumes of exposed materials onsite;
- (b) Permanent or semipermanent covers;
- (c) of sediment traps, vegetated swales and strips, catch basin filters and sand filters to facilitate settling or filtering of sediments;
- (d) Diversion of runoff away from storage areas via dikes, berms, containment trenches, culverts and surface grading;
- (e) Install and maintain silt and/or other fencing around shredder fluff or other light material storage piles to prevent migration of lightweight materials such as foam by wind and stormwater runoff; and
- (f) Oil/water separators, sumps and dry adsorbents for areas where potential sources of residual fluids are stockpiled (e.g., automotive engine storage areas).

(3) Stockpiling of turnings exposed to cutting fluids (outdoor) - The plan shall implement measures necessary to minimize contact of surface runoff with residual cutting fluids. BMP options (use singularly or in combination):

- (a) Storage of all turnings exposed to cutting fluids under some form of permanent or semipermanent cover - Stormwater discharges from these areas are permitted provided the runoff is first treated by an oil/water separator or its equivalent. Procedures to collect, handle, and dispose or recycle residual fluids that may be present shall be identified in the plan;
- (b) Establish dedicated containment areas for all turnings that have been exposed to cutting fluids. Stormwater runoff from these areas can be discharged provided:
  - (i) The containment areas are constructed of either concrete, asphalt or other equivalent type of impermeable material;

b. Scrap recycling and waste recycling facilities (nonsource-separated, nonliquid recyclable materials) - The following SWPPP special conditions have been established for facilities that receive, process and do wholesale distribution of nonliquid recyclable wastes (e.g., ferrous and nonferrous metals, plastics, glass, cardboard and paper). These facilities may receive both nonrecyclable and recyclable materials. This section is not intended for those facilities that only accept recyclable materials primarily from nonindustrial and residential sources.

(1) Inbound recyclable and waste material control program - The plan shall include a recyclable and waste material inspection program to minimize the likelihood of receiving materials that may be significant pollutant sources to stormwater discharges. BMPs must include:

(a) Provisions for information/education flyers, brochures and pamphlets to suppliers of scrap and recyclable waste materials on:

(i) Draining and proper recycling/disposal of residual fluids prior to delivery to the facility (e.g., from vehicles and equipment engines, radiators, and transmissions, oil-filled transformers, and individual containers or drums);

(ii) removal and proper collection, recycling and/or disposal of mercury switches, mercury containing parts, lead tire weights, lead battery cable ends air conditioning refrigerants, and small PCB capacitors from vehicles; and

(iii) removal and proper collection/disposal of PCB capacitors, ballasts, CFCs/HCFs, mercury switches, mercury containing components and other sources of potential contaminants from appliances.

(b) Procedures to require certification by suppliers of inbound shipments of recyclable materials that the items identified above in VIII.N.3.b(1)(a)(i-iii) were completed;

(c) Procedures to inspect inbound shipments of recyclable materials to ensure that the items identified above in VIII.N.3.b(1)(a)(i-iii) were completed;

(d) Procedures to minimize the potential of any residual fluids from coming in contact with precipitation/runoff;

(e) Training targeted for those personnel engaged in the inspection and acceptance of inbound recyclable materials;

(f) Procedures for accepting scrap lead-acid batteries - See requirements for the handling, storage and disposal or recycling of batteries are contained in the scrap lead-acid battery program provisions in Paragraph VIII.N.3.b(6);

operations in question (versus an outside entity such as the airport authority). The use of alternative deicing/anti-icing agents, as well as containment measures for all applied chemicals, shall be considered. Also, the following BMP options (or their equivalents) shall be considered for reducing deicing fluid use: forced-air deicing systems; computer-controlled fixed-gantry systems; infrared technology; hot water; varying glycol content to air temperature; enclosed-basket deicing trucks; mechanical methods; solar radiation; hangar storage; aircraft covers; and thermal blankets for MD-80s and DC-9s. The use of ice-detection systems and airport traffic flow strategies and departure slot allocation systems shall also be considered.

(3) Management of runoff - Where deicing/anti-icing operations occur, owners or operators shall describe and implement a program to control or manage contaminated runoff to reduce the amount of pollutants being discharged from the site. The following BMPs (or their equivalents) shall be considered: establishing a dedicated deicing facility with a runoff collection/recovery system; using vacuum/collection trucks; storing contaminated stormwater/deicing fluids in tanks and releasing controlled amounts to a publicly owned treatment works in accordance with pretreatment program requirements; collecting contaminated runoff in a wet pond for biochemical decomposition (be aware of attracting wildlife that may prove hazardous to flight operations); and directing runoff into vegetative swales or other infiltration measures. The plan shall consider the recovery of deicing/anti-icing materials when these materials are applied during nonprecipitation events (e.g., covering storm sewer inlets, using booms, installing absorptive interceptors in the drains, etc.) to prevent these materials from later becoming a source of stormwater contamination. Used deicing fluid should be recycled whenever possible.

(4) Routine facility inspections - The inspection frequency shall be specified in the plan. At a minimum, inspections shall be conducted once per month during deicing/anti-icing season (e.g., October through April for most airports). If deicing occurs before or after this period, the inspections shall be expanded to include all months during which deicing chemicals may be used. Also, if significantly or deleteriously large quantities of deicing chemicals are being spilled or discharged, or if water quality impacts have been reported, the inspection frequency shall be increased to weekly until such time as the chemical spills/discharges or impacts are reduced to acceptable levels.

(5) Comprehensive site compliance evaluation - The annual site compliance evaluations shall be conducted by qualified facility personnel during periods of actual deicing operations, if possible. If not practicable during active deicing or if the weather is too inclement, the evaluations shall be conducted when deicing operations are likely to occur and the materials and equipment for deicing are in place.



4. **Benchmark Monitoring and Reporting Requirements** - Airports that use more than 100,000 gallons of glycol-based deicing/antiicing chemicals and/or 100 tons or more of urea on an average annual basis shall sample their stormwater discharges for the parameters listed in Table VIII-S-1. Only those outfalls from the airport facility that collect runoff from areas where deicing/anti-icing activities occur must be monitored. The alternative certification provision of Part I A 3 b is not applicable to discharges covered under this section.

Table VIII-S-1.  
Sector S - Benchmark Monitoring Requirements

Pollutants of Concern	Analytical Method	Benchmark Monitoring Cut-Off Concentration
<b>Facilities at airports that use more than 100,000 gallons of glycol-based deicing/anti-icing chemicals and/or 100 tons or more of urea on an average annual basis: monitor ONLY those outfalls from the airport facility that collect runoff from areas where deicing/anti-icing activities occur (SIC 45).</b>		
Biochemical Oxygen Demand (BOD5)	EPA 405.1	30 mg/L
Chemical Oxygen Demand (COD)	EPA 410.4	120 mg/L
Total Nitrogen (TN)	EPA 350.1, 351.2, 353.2	6 mg/L
pH	EPA 150.1	within the range 6.0 to 9.0 s.u.

\* Total Nitrogen is calculated as the sum of ammonia, nitrate-nitrite and organic nitrogen.

## **Sector T - Treatment Works**

1. **Discharges Covered Under This Section** - The requirements listed under this section apply to stormwater discharges associated with industrial activity from treatment works treating domestic sewage or any other sewage sludge or wastewater treatment device or system, used in the storage, treatment, recycling, and reclamation of municipal or domestic sewage, including lands dedicated to the disposal of sewage sludge that are located within the confines of the facility with a design flow of 1.0 MGD or more, or required to have an approved pretreatment program under 40 CFR 403 (Industrial Activity Code "TW"). Farm lands, domestic gardens or lands used for sludge management where sludge is beneficially reused and that are not physically located within the facility, or areas that are in compliance with Section 405 of the CWA are not required to have permit coverage.

### **2 Special Conditions**

a. **Prohibition of non-stormwater discharges** - In addition to the general non-stormwater prohibition in Paragraph I.D.1, the following discharges not covered by this permit include, but are not limited to: sanitary and industrial wastewater; and equipment/vehicle washwaters.

3. **Stormwater Pollution Prevention Plan Requirements** - In addition to the requirements of Part III, the SWPPP shall include, at a minimum, the following items.

#### **a. Site description**

(1) **Site map** - The site map shall identify where any of the following may be exposed to precipitation/surface runoff: grit, screenings and other solids handling, storage or disposal areas; sludge drying beds; dried sludge piles; compost piles; septage or hauled waste receiving station; and storage areas for process chemicals, petroleum products, solvents, fertilizers, herbicides and pesticides.

(2) **Summary of potential pollutant sources** - A description of the potential pollutant sources from the following activities, as applicable: grit, screenings and other solids handling, storage or disposal areas; sludge drying beds; dried sludge piles; compost piles; septage or hauled waste receiving station; and access roads/rail lines.

#### **b. Stormwater controls**

(1) **Best Management Practices (BMPs)** - In addition to the other BMPs considered, the following BMPs shall be considered: routing stormwater to the treatment works; or covering exposed materials (i.e., from the following areas: grit, screenings and other solids handling, storage or disposal areas; sludge drying beds; dried sludge piles; compost piles; septage or hauled waste receiving station).

(2) Inspections - The following areas shall be included in all inspections: access roads/rail lines, grit, screenings and other solids handling, storage or disposal areas; sludge drying beds; dried sludge piles; compost piles; septage or hauled waste receiving station areas.

(3) Employee training - Employee training must, at a minimum, address the following areas when applicable to a facility: petroleum product management; process chemical management; spill prevention and control; fueling procedures; general good housekeeping practices; proper procedures for using fertilizers, herbicides and pesticides.

4. **Benchmark Monitoring and Reporting Requirements** - Treatment works are required to monitor their stormwater discharges for the pollutants of concern listed in Table VIII-T-1.

Table VIII-T-1.  
Sector T - Benchmark Monitoring Requirements

Pollutants of Concern	Analytical Method	Benchmark Monitoring Cut-Off Concentration
<b>Treatment Works (Industrial Activity Code "TW")</b>		
Chemical Oxygen Demand (COD)	EPA 410.4	120 mg/L

## **Sector U - Food and Kindred Products**

1. **Discharges Covered Under This Section** - The requirements listed under this section apply to stormwater discharges associated with industrial activity from food and kindred products processing facilities (commonly identified by SIC Code 20), including: meat products; dairy products; canned, frozen and preserved fruits, vegetables, and food specialties; grain mill products; bakery products; sugar and confectionery products; fats and oils; beverages; and miscellaneous food preparations and kindred products and tobacco products manufacturing (SIC Code 21).

### **2. Special Conditions**

a. **Prohibition of non-stormwater discharges** - In addition to the general non-stormwater prohibition in Paragraph I.D.1, the following discharges not covered by this permit include, but are not limited to: boiler blowdown, cooling tower overflow and blowdown, ammonia refrigeration purging, and vehicle washing/clean-out operations.

3. **Stormwater Pollution Prevention Plan Requirements** - In addition to the requirements of Part III, the SWPPP shall include, at a minimum, the following items.

#### **a. Site description**

(1) **Site map** - The site map shall identify the locations of the following activities if they are exposed to precipitation/surface runoff: vents/stacks from cooking, drying, and similar operations; dry product vacuum transfer lines; animal holding pens; spoiled product; and broken product container storage areas.

(2) **Summary of potential pollutant sources** - In addition to food and kindred products processing-related industrial activities, the plan must also describe application and storage of pest control chemicals (e.g., rodenticides, insecticides, fungicides, etc.) used on plant grounds.

#### **b. Stormwater controls**

(1) **Routine facility inspections** - At a minimum, the following areas, where the potential for exposure to stormwater exists, must be inspected: loading and unloading areas for all significant materials; storage areas, including associated containment areas; waste management units; vents and stacks emanating from industrial activities; spoiled product and broken product container holding areas; animal holding pens; staging areas; and air pollution control equipment.

(2) Employee training - The employee training program must also address pest control.

4. **Benchmark Monitoring and Reporting Requirements** - Grain mills and fats and oils products facilities are required to monitor their stormwater discharges for the pollutants of concern listed in Table VIII-U-1.

Table VIII-U-1.  
Sector U - Benchmark Monitoring Requirements

Pollutants of Concern	Analytical Method	Benchmark Monitoring Cut-Off Concentration
<b>Grain Mill Products (SIC 2041-2048)</b>		
Total Suspended Solids (TSS)	EPA 160.2	100 mg/L
Total Nitrogen (TN)	EPA 350.1, 351.2, 353.2	6 mg/L
Total Phosphorus (TP)	EPA 365.1	2 mg/L
<b>Fats and Oils Products (SIC 2074-2079)</b>		
Total Suspended Solids (TSS)	EPA 160.2	100 mg/L
Biochemical Oxygen Demand (BOD5)	EPA 405.1	30 mg/L
Chemical Oxygen Demand (COD)	EPA 410.4	120 mg/L
Total Nitrogen (TN)	EPA 350.1, 351.2, 353.2	6 mg/L
Total Phosphorus (TP)	EPA 365.1	2 mg/L

\* Total Nitrogen is calculated as the sum of ammonia, nitrate-nitrite and organic nitrogen.

## **Sector V - Textile Mills, Apparel, and Other Fabric Products**

1. **Discharges Covered Under This Section** - The requirements listed under this section apply to stormwater discharges associated with industrial activity from textile mills, apparel and other fabric product manufacturing, generally described by SIC 22 and 23. Facilities in this sector are primarily engaged in the following activities: textile mill products, of and regarding facilities and establishments engaged in the preparation of fiber and subsequent manufacturing of yarn, thread, braids, twine, and cordage, the manufacturing of broad woven fabrics, narrow woven fabrics, knit fabrics, and carpets and rugs from yarn; processes involved in the dyeing and finishing of fibers, yarn fabrics, and knit apparel; the integrated manufacturing of knit apparel and other finished articles of yarn; the manufacturing of felt goods (wool), lace goods, nonwoven fabrics, miscellaneous textiles, and other apparel products. This section also covers facilities engaged in manufacturing finished leather and artificial leather products (SIC 31, except 3111).

### **2. Special Conditions**

a. **Prohibition of non-stormwater discharges** - In addition to the general non-stormwater prohibition in Paragraph I.D.1, the following discharges not covered by this permit include, but are not limited to: discharges of wastewater (e.g., wastewater as a result of wet processing or from any processes relating to the production process); reused/recycled water; and waters used in cooling towers. These discharges must be covered under a separate SPDES permit.

3. **Stormwater Pollution Prevention Plan Requirements** - In addition to the requirements of Part III, the SWPPP shall include, at a minimum, the following items.

#### **a. Site description**

(1) **Summary of potential pollutant sources** - A description of the potential pollutant sources from the following activities: industry-specific significant materials and industrial activities (e.g., backwinding, beaming, bleaching, backing, bonding, carbonizing, carding, cut and sew operations, desizing, drawing, dyeing, flocking, fulling, knitting, mercerizing, opening, packing, plying, scouring, slashing, spinning, synthetic-felt processing, textile waste processing, tufting, turning, weaving, web forming, winging, yarn spinning, and yarn texturing).

#### **b. Stormwater controls**

(1) **Good housekeeping measures**

- (a) Material storage areas - All containerized materials (fuels, petroleum products, solvents, dyes, etc.) must be clearly labeled and stored in a protected area, away from drains. The permittee must describe and implement measures that prevent or minimize contamination of stormwater runoff from such storage areas, and must include a description of the containment area or enclosure for those materials that are stored outdoors. The permittee may consider an inventory control plan to prevent excessive purchasing of potentially hazardous substances. The permittee shall ensure that empty chemical drums/containers are clean (triple-rinsing shall be considered) and residuals are not subject to contact with precipitation/runoff. Washwater from these cleanings must be collected and disposed of properly.
- (b) Material handling area - The permittee must describe and implement measures that prevent or minimize contamination of the stormwater runoff from materials handling operations and areas. The permittee shall consider the following measures (or their equivalents): use of spill/overflow protection; covering fueling areas; and covering and enclosing areas where the transfer of materials may occur. Where applicable, the plan must address the replacement or repair of leaking connections, valves, transfer lines and pipes that may carry chemicals, dyes, or wastewater.
- (c) Fueling areas - The permittee must describe and implement measures that prevent or minimize contamination of the stormwater runoff from fueling areas. The permittee shall consider the following measures (or their equivalents): covering the fueling area; using spill and overflow protection; minimizing runoff of stormwater to the fueling areas; using dry cleanup methods; and treating and/or recycling stormwater runoff collected from the fueling area.
- (d) Aboveground storage tank areas - The permittee must describe and implement measures that prevent or minimize contamination of the stormwater runoff from aboveground storage tank areas, including the associated piping and valves. The permittee shall consider the following measures (or their equivalents): regular cleanup of these areas; preparation of a spill prevention control and countermeasure program; spill and overflow protection; minimizing runoff of stormwater from adjacent areas; restricting access to the area; insertion of filters in adjacent catch basins; absorbent booms in unbermed fueling areas; use of dry cleanup methods; and permanently sealing drains within critical areas that may discharge to a storm drain.
- (2) Routine facility inspections - Inspections shall be conducted at least monthly, and shall include the following activities and areas (at a minimum): transfer and transmission lines; spill prevention; good housekeeping practices; management of process waste products; and all structural and nonstructural management practices.

(3) Employee training - Employee training must, at a minimum address, the following areas when applicable to a facility: use of reused/recycled waters; solvents management; proper disposal of dyes; proper disposal of petroleum products and spent lubricants; spill prevention and control; fueling procedures; and general good housekeeping practices.

(4) Comprehensive Site Compliance Evaluation - Regularly scheduled evaluations shall be conducted at least once a year and address those areas contributing to a stormwater discharge associated with industrial activity. Inspections shall look for evidence of, or the potential for, pollutants entering the drainage system from the following areas, as appropriate: storage tank areas; waste disposal and storage areas; dumpsters and open containers stored outside; materials storage areas; engine maintenance and repair areas; material handling areas and loading dock areas.



## **Sector W - Furniture and Fixtures**

1. **Discharges Covered Under This Section** - The requirements listed under this section apply to stormwater discharges associated with industrial activity from facilities involved in the manufacturing of wood kitchen cabinets (generally described by SIC Code 2434), household furniture (SIC 251); office furniture (SIC 252); public buildings and related furniture (SIC 253); partitions, shelving, lockers, and office and store fixtures (SIC 254); and miscellaneous furniture and fixtures (SIC 259).

2. **Stormwater Pollution Prevention Plan Requirements** - In addition to the requirements of Part III, the SWPPP shall include, at a minimum, the following item:

a. **Site Map** - The site map shall identify where any of the following may be exposed to precipitation/surface runoff: material storage areas (including tanks or other vessels used for liquid or waste storage); outdoor material processing areas; areas where wastes are treated, stored or disposed; access roads; and rail spurs.

## **Sector X - Printing and Publishing**

1. **Discharges Covered Under This Section** - The requirements listed under this section apply to stormwater discharges associated with industrial activity from printing and publishing facilities (generally classified under SIC Major Group 27) including the following: book printing; commercial printing and lithographics; plate making and related services; commercial printing; and commercial printing not elsewhere classified.

2. **Stormwater Pollution Prevention Plan Requirements** - In addition to the requirements of Part III, the SWPPP shall include, at a minimum, the following items:

a. **Site description**

(1) **Site map** - The site map shall identify where any of the following may be exposed to precipitation/surface runoff: aboveground storage tanks, drums and barrels permanently stored outside.

(2) **Summary of potential pollutant sources** - The plan shall include a description of the following additional sources and activities that have potential pollutants associated with them, as applicable: loading and unloading operations; outdoor storage activities; significant dust or particulate generating processes; and on-site waste disposal practices (e.g., blanket wash). Also, the pollutant or pollutant parameter associated with each pollutant source shall be identified (e.g., oil and grease, scrap metal, etc.).

b. **Stormwater controls**

(1) **Good housekeeping measures**

(a) **Material storage areas** - All containerized materials (skids, pallets, solvents, bulk inks, and hazardous waste, empty drums, portable/mobile containers of plant debris, wood crates, steel racks, fuel oil, etc.) shall be properly labeled and stored in a protected area, away from drains. The permittee shall describe and implement measures that prevent or minimize contamination of the stormwater runoff from such storage areas and shall include a description of the containment area or enclosure for those materials which are stored outdoors. The permittee may consider an inventory control plan to prevent excessive purchasing of potentially hazardous substances.

(b) **Material handling areas** - The permittee must describe and implement measures that prevent or minimize contamination of the stormwater runoff from material handling operations and areas (e.g., blanket wash, mixing solvents, loading/unloading materials). The permittee shall consider the following measures (or their equivalents): the use of spill/overflow protection; covering fuel areas; and

covering/enclosing areas where the transfer of materials may occur. Where applicable, the plan must address the replacement or repair of leaking connections, valves, transfer lines and pipes that may carry chemicals, or wastewater.

(c) Fueling areas - The permittee must describe and implement measures that prevent or minimize contamination of the stormwater runoff from fueling areas. The permittee shall consider the following measures (or their equivalents): covering the fueling area; using spill and overflow protection; minimizing runoff of stormwater to the fueling area; using dry cleanup methods; and treating and/or recycling stormwater runoff collected from the fueling areas.

(d) Aboveground storage tank areas - The permittee must describe and implement measures that prevent or minimize contamination of the stormwater runoff from aboveground storage tank areas, including the associated piping and valves. The permittee shall consider the following measures (or their equivalents): regular cleanup of these areas; preparation of a spill prevention control and countermeasure program; spill and overflow protection; minimizing runoff of stormwater from adjacent facilities and properties; restricting access to the area; insertion of filters in adjacent catch basins; absorbent booms in unbermed fueling areas; use of dry cleanup methods; and permanently sealing drains within critical areas that may discharge to a storm drain.

(2) Employee training - Employee training must, at a minimum, address the following areas when applicable to a facility: spent solvent management; spill prevention and control; used oil management; fueling procedures; and general good housekeeping practices.

## **Sector Y - Rubber, Miscellaneous Plastic Products, and Miscellaneous Manufacturing Industries**

1. **Discharges Covered Under This Section** - The requirements listed under this section apply to stormwater discharges associated with industrial activity from rubber and miscellaneous plastic products manufacturing facilities (SIC Major Group 30) and miscellaneous manufacturing industries, except jewelry, silverware, and plated ware (SIC Major Group 39, except 391).

2. **Stormwater Pollution Prevention Plan Requirements** - In addition to the requirements of Part III, the SWPPP shall include, at a minimum, the following items:

a. **Site description** - Summary of potential pollutant sources. The permittee shall review the use of zinc at the facility and the possible pathways through which zinc may be discharged in stormwater runoff.

b. **Stormwater controls**

(1) **Controls for rubber manufacturers** - The permittee shall describe and implement specific controls to minimize the discharge of zinc in stormwater discharges from the facility. Some general BMP options to consider include: using chemicals that are purchased in pre-weighed, sealed polyethylene bags; storing materials that are in use in sealable containers; ensuring an airspace between the container and the cover to minimize "puffing" losses when the container is opened; and using automatic dispensing and weighing equipment. The following possible sources of zinc shall be reviewed and the accompanying BMPs (or their equivalents) shall be considered in the SWPPP:

(a) **Inadequate housekeeping** - All permittees shall review the handling and storage of zinc bags at their facilities and consider the following BMP options: employee training regarding the handling/storage of zinc bags; indoor storage of zinc bags; cleanup of zinc spills without washing the zinc into the storm drain; and the use of 2,500-pound sacks of zinc rather than 50- to 100-pound sacks.

(b) **Dumpsters** - The following BMPs shall be considered to reduce discharges of zinc from dumpsters: providing a cover for the dumpster; move the dumpster to an indoor location; or provide a lining for the dumpster.

(c) **Malfunctioning dust collectors or baghouses** - Permittees shall review dust collectors/baghouses as possible sources in zinc in stormwater runoff. Improperly operating dust collectors/baghouses shall be replaced or repaired as appropriate.

(d) Grinding operations - Permittees shall review dust generation from rubber grinding operations at their facility and, as appropriate, install a dust collection system.

(e) Zinc stearate coating operations - Permittees shall include in the SWPPP appropriate measures to prevent or clean up drips /spills of zinc stearate slurry that may be released to the storm drain. Alternate compounds to zinc stearate shall also be considered.

(2) Controls for plastic products manufacturers - The permittee shall describe and implement specific controls to minimize the discharge of plastic resin pellets in storm water discharges. Some general BMP options to consider include: minimizing spills; cleaning up spills promptly and thoroughly; sweeping thoroughly; pellet capturing; employee education; and disposal precautions.

**3. Benchmark Monitoring and Reporting Requirements** - Rubber product manufacturing facilities are required to monitor their stormwater discharges for the pollutants of concern listed in Table VIII-Y-1.

Table VIII-Y-1.  
Sector Y - Benchmark Monitoring Requirements

Pollutants of Concern	Analytical Method	Benchmark Monitoring Cut-Off Concentration
<b>Tires and Inner Tubes; Rubber Footwear; Gaskets, Packing and Sealing Devices; Rubber Hose and Belting; and Fabricated Rubber Products Not Elsewhere Classified (SIC 3011-3069).</b>		
Total Recoverable Zinc	EPA 200.7	120 ug/L

## **Sector Z - Leather Tanning and Finishing**

1. **Discharges Covered Under This Section** - The requirements listed under this section apply to stormwater discharges associated with industrial activity from leather tanning, currying and finishing (commonly identified by SIC Code 3111).

2. **Stormwater Pollution Prevention Plan Requirements** - In addition to the requirements of Part III, the SWPPP shall include, at a minimum, the following items.

### **a. Site description**

(1) **Site map** - The site map shall identify where any of the following may be exposed to precipitation/surface runoff: processing and storage areas of the beamhouse, tanyard, retan-wet finishing and dry finishing operations; and haul roads, access roads and rail spurs.

(2) **Summary of potential pollutant sources** - A description of potential pollutant sources including (as appropriate): temporary or permanent storage of fresh and brine cured hides; chemical drums, bags, containers and aboveground tanks; leather dust, scraps, trimmings and shavings; spent solvents; extraneous hide substances and hair; empty chemical containers and bags; floor sweepings/washings; refuse and waste piles and sludge; and significant dust/particulate generating processes (e.g., buffing).

### **b. Stormwater controls**

#### **(1) Good housekeeping**

(a) **Storage areas for raw, semiprocessed, or finished tannery by-products** - Pallets/bales of raw, semiprocessed or finished tannery by-products (e.g., splits, trimmings, shavings, etc.) shall be stored indoors or protected by polyethylene wrapping, tarpaulins, roofed storage area or other suitable means. Materials shall be placed on an impermeable surface, the area should be enclosed or bermed or other equivalent measures should be employed to prevent runoff/runoff of stormwater.

(b) **Material storage areas** - Label storage units of all materials (e.g., specific chemicals, hazardous materials, spent solvents, waste materials). Describe and implement measures that prevent or minimize contact with stormwater.

(c) **Buffing and shaving areas** - The permittee must describe and implement measures that prevent or minimize contamination of the stormwater runoff with leather dust from buffing/shaving areas. The permittee may consider dust

collection enclosures, preventive inspection/maintenance programs or other appropriate preventive measures.

(d) Receiving, unloading, and storage areas - The permittee must describe and implement measures that prevent or minimize contamination of the stormwater runoff from receiving, unloading, and storage areas. The following measures (or their equivalents) shall be considered for exposed receiving, unloading and storage areas: hides and chemical supplies protected by a suitable cover; diversion of drainage to the process sewer; and grade berming/curbing area to prevent runoff of stormwater.

(e) Outdoor storage of contaminated equipment - The permittee must describe and implement measures that prevent or minimize contact of stormwater with contaminated equipment. The following measures (or their equivalents) shall be considered: equipment protected by suitable cover; diversion of drainage to the process sewer; and thorough cleaning prior to storage.

(f) Waste management - The permittee must describe and implement measures that prevent or minimize contamination of the stormwater runoff from waste storage areas. The permittee shall consider the following measures (or their equivalents): inspection/maintenance programs for leaking containers or spills; covering dumpsters; moving waste management activities indoors; covering waste piles with temporary covering material such as tarpaulins or polyethylene; and minimizing stormwater runoff by enclosing the area or building berms around the area.

3. Benchmark Monitoring and Reporting Requirements - Leather tanning and finishing facilities are required to monitor their stormwater discharges for the pollutants of concern listed in Table VIII-Z-1.

**Table VIII-Z-1.**  
**Sector Z - Benchmark Monitoring Requirements**

Pollutants of Concern	Analytical Method	Benchmark Monitoring Cut-Off Concentration
<b>Leather Tanning and Finishing (SIC 3111)</b>		
Total Nitrogen (TN)	EPA 350.1, 351.2, 353.2	6 mg/L
Total Recoverable Chromium	EPA 200.7	1.8 mg/L

\* Total Nitrogen is calculated as the sum of ammonia, nitrate-nitrite and organic nitrogen.

## **Sector AA - Fabricated Metal Products**

1. **Discharges Covered Under This Section** - The requirements listed under this section apply to stormwater discharges associated with industrial activity from the fabricated metals industry (except for electrical related industries); fabricated metal products (except machinery and transportation equipment); and jewelry, silverware, and plated ware.

2. **Stormwater Pollution Prevention Plan Requirements** - In addition to the requirements of Part III, the SWPPP shall include, at a minimum, the following items.

### **a. Site description**

(1) **Site Map** - The site map shall identify where any of the following may be exposed to precipitation/surface runoff: raw metal storage areas; finished metal storage areas; scrap disposal collection sites; equipment storage areas; retention and detention basins; temporary/permanent diversion dikes or berms; right-of-way or perimeter diversion devices; sediment traps/barriers; processing areas including outside painting areas; wood preparation; recycling; and raw material storage.

(2) **Spills and Leaks** - When listing reportable spills/leaks, the permittee shall pay attention to the following materials, at a minimum: chromium, toluene, pickle liquor, sulfuric acid, zinc and other water priority chemicals and hazardous chemicals and wastes.

(3) **Summary of potential pollutant sources** - A description of the potential pollutant sources from the following activities: loading and unloading operations for paints, chemicals and raw materials; outdoor storage activities for raw materials, paints, empty containers, corn cob, chemicals, scrap metals; outdoor manufacturing or processing activities such as grinding, cutting, degreasing, buffing, brazing, etc.; and on-site waste disposal practices for spent solvents, sludge, pickling baths, shavings, ingots pieces, refuse and waste piles.

### **b. Stormwater controls**

#### **(1) Good housekeeping**

(a) **Raw steel handling storage** - Describe and implement measures controlling or recovering scrap metals, fines, and iron dust, including measures for containing materials within storage handling areas.

(b) **Paints and painting equipment** - Describe and implement measures to prevent or minimize exposure of paint and painting equipment from exposure to stormwater.



(2) Spill prevention and response procedures - The permittee shall ensure that the necessary equipment to implement a clean up is available to personnel. The following areas should be addressed:

(a) Metal fabricating areas - Describe and implement measures for maintaining clean, dry, orderly conditions in these areas. Use of dry clean-up techniques shall be considered in the plan.

(b) Storage areas for raw metal - Describe and implement measures to keep these areas free of conditions that could cause spills or leakage of materials. The following measures (or their equivalents) shall be considered: storage areas maintained such that there is easy access in the event of a spill; stored materials labeled to aid in identifying spill contents .

(c) Receiving, unloading, and storage areas - Describe and implement measures to prevent spills and leaks; plan for quick remedial clean up and instruct employees on clean-up techniques and procedures.

(d) Storage of equipment - Describe and implement measures for preparing equipment for storage and the proper method to store equipment. The following measures (or their equivalents) shall be considered: protecting with covers; storing indoors; and cleaning potential pollutants from equipment to be stored outdoors.

(e) Metal working fluid storage areas - Describe and implement measures for storage of metal working fluids.

(f) Cleaners and rinse water - Describe and implement measures to control/cleanup spills of solvents and other liquid cleaners; control sand buildup and disbursement from sand-blasting operations; and prevent exposure of recyclable wastes. Environmentally benign cleaners should be substituted when possible.

(g) Lubricating oil and hydraulic fluid operations - Consider using devices or monitoring equipment or other devices to detect and control leaks /overflows. Consider the installation of perimeter controls such as dikes, curbs, grass filter strips, or other equivalent measures.

(h) Chemical storage areas - Describe and implement proper storage methods that prevent stormwater contamination and accidental spillage. The plan should include a program to inspect containers, and identify proper disposal methods .

(3) Inspections - Metal fabricators shall at a minimum include the following areas for inspection: raw metal storage areas; finished product storage areas; material and

chemical storage areas; recycling areas; loading and unloading areas; equipment storage areas; paint areas; and vehicle fueling and maintenance areas.

(4). Comprehensive site compliance evaluation - The site compliance evaluation shall also include inspections of: areas associated with the storage of raw metals; storage of spent solvents and chemicals; outdoor paint areas; and roof drainage. Potential pollutants include chromium, zinc, lubricating oil, solvents, aluminum, oil and grease, methyl ethyl ketone, steel and other related materials.

3. **Benchmark Monitoring and Reporting Requirements** - Metal fabricating facilities are required to monitor their stormwater discharges for the pollutants of concern listed in Table VIII-AA-1.

Table VIII-AA-1.  
Sector AA - Benchmark Monitoring Requirements

Pollutants of Concern	Analytical Method	Benchmark Monitoring Cut-Off Concentration
<b>Fabricated Metal Products Except Coating (SIC 3411-3471, 3482-3499, 3911-3915)</b>		
Total Nitrogen (TN)	EPA 350.1, 351.2, 353.2	6 mg/L
Total Recoverable Aluminum	EPA 200.7	750 ug/L
Total Recoverable Iron	EPA 200.7	1 mg/L
Total Recoverable Zinc	EPA 200.7	120 ug/L
<b>Fabricated Metal Coating and Engraving (SIC 3479)</b>		
Total Nitrogen (TN)	EPA 350.1, 351.2, 353.2	6 mg/L
Total Recoverable Zinc	EPA 200.7	120 ug/L

\* Total Nitrogen is calculated as the sum of ammonia, nitrate-nitrite and organic nitrogen.

## **Sector AB - Transportation Equipment, Industrial or Commercial Machinery**

1. **Discharges Covered Under This Section** - The requirements listed under this section apply to stormwater discharges associated with industrial activity from transportation equipment, industrial or commercial machinery manufacturing facilities (commonly described by SIC Major Group 35 (except SIC Code 357 - computer and office equipment covered by Sector AC), and SIC Major Group 37 (except SIC Code 373 - ship and boat building and repair cover by Sector R)).

2. **Stormwater Pollution Prevention Plan Requirements** - In addition to the requirements of Part III, the SWPPP shall include, at a minimum, the following items:

a. **Site description**

(1) **Site map** - The site map shall identify where any of the following may be exposed to precipitation/surface runoff: vents and stacks from metal processing and similar operations.

b. **Stormwater controls**

(1) **Non-stormwater discharges** - For facilities that discharge wastewater, other than solely domestic wastewater, to the sanitary sewer system, the permittee must notify the owner or operator of the sanitary sewer and associated treatment works of its discharge. In such cases, a copy of a notification letter must be attached to the plan.

**Sector AC - Electronic, Electrical Equipment and Components, Photographic and Optical Goods**

1. **Discharges Covered Under This Section** - The requirements listed under this section apply to stormwater discharges associated with industrial activity from facilities that manufacture: electronic and other electrical equipment and components, except computer equipment (SIC Major Group 36); measuring, analyzing, and controlling instruments; photographic, medical and optical goods; watches and clocks (SIC Major Group 38) and computer and office equipment (SIC Code 357).

2. **Monitoring and Reporting Requirements** - Facilities under this sector are required to monitor their stormwater discharges for the pollutants of concern listed in Table VIII-AC-1.

Table VIII-AC-1.  
Sector AC - Benchmark Monitoring Requirements

Pollutants of Concern	Analytical Method	Benchmark Monitoring Cut-Off Concentration
Electronic and Other Electrical Equipment and Components, Except Computer Equipment (SIC Major Group 36); Measuring, Analyzing, and Controlling Instruments; Photographic, Medical and Optical Goods; Watches and Clocks (SIC Major Group 38) and Computer and Office Equipment (SIC Code 357)		
Total Suspended Solids (TSS)	EPA 160.2	100 mg/L
Total Recoverable Copper	EPA 200.7	64 ug/L
Total Recoverable Lead	EPA 200.7	82 ug/L

**Sector AD - Non-classified Facilities/Stormwater Discharges Designated by the Department as Requiring Permit Coverage**

1. **Discharges Covered Under This Section** - Sector AD is intended to allow permit coverage for stormwater discharges from industrial activities at facilities not covered by Sectors A-AC and where coverage under a general permit would be more suitable than requiring an individual industrial SPDES permit. Facilities must be assigned to Sector AD by the Department and must receive written notification granting permission to use this permit prior to submitting an NOIT.
2. **Stormwater Pollution Prevention Plan** - The Department may establish additional Stormwater Pollution Prevention Plan requirements upon granting permission for coverage under this sector. Additional requirements would be based upon the nature of activities conducted at the facility.
3. **Monitoring and Reporting Requirements** - In addition to monitoring for the following parameters, the Department may establish additional monitoring requirements based upon the nature of activities conducted at the facility and potential pollution sources that are exposed to stormwater.

Table VIII-AD-1.  
Sector AD - Benchmark Monitoring Requirements

Pollutants of Concern	Analytical Method	Benchmark Monitoring Cut-Off Concentration
<b>Non-classified Facilities/Stormwater Discharges Designated by the Department as Requiring Permit Coverage</b>		
Total Suspended Solids (TSS)	EPA 160.2	100 mg/L
Chemical Oxygen Demand (COD)	EPA 410.4	120 mg/L
Oil and Grease	EPA 1664 or EPA 1664A	15 mg/L
Total Nitrogen (TN)	EPA 353.1	6 mg/L
Total Recoverable Iron	EPA 200.7	1 mg/L
Total Recoverable Zinc	EPA 200.7	120 ug/L

\* Total Nitrogen is calculated as the sum of ammonia, nitrate-nitrite and organic nitrogen.

**Sector AE - Department of Public Works and Highway Maintenance Facilities**  
 (A Non-classified Facilities/Stormwater Discharges Designated  
 by the Department as Requiring Permit Coverage)

1. **Discharges Covered Under This Section** - Sector AE is intended to allow permit coverage for stormwater discharges from Department of Public Works and Highway Maintenance facilities that have operations including vehicle and equipment maintenance shops (vehicle and equipment rehabilitation, mechanical repairs, painting, fueling and lubrication), equipment cleaning operations and salt storage for road deicing activities. Facilities must be assigned to Sector AE by the Department and must receive written notification granting permission to use this permit prior to submitting an NOIT. Coverage under this permit may not be required for a municipally owned facility whose stormwater discharge is already addressed through the municipality's MS4 permit.
  
2. **Stormwater Pollution Prevention Plan Requirements** - In addition to the requirements of Part III, the SWPPP shall include, at a minimum, the requirements listed for Sector P - Land Transportation and Warehousing.
  
3. **Benchmark Monitoring and Reporting Requirements** - Department of Public Works and Highway Maintenance facilities are required to monitor their stormwater discharges for the pollutant of concern listed in Table VIII-AE-1.

Table VIII-AE-1.  
 Sector AE - Benchmark Monitoring Requirements

Pollutants of Concern	Analytical Method	Benchmark Monitoring Cut-Off Concentration
<b>Department of Public Works and Highway Maintenance Facilities</b>		
Oil & Grease	EPA 1664 or EPA 1664A	15 mg/L
Total Suspended Solids (TSS)	EPA 160.2	100 mg/L
Benzene	EPA 602	50 ug/L
Ethylbenzene	EPA 602	50 ug/L
Toluene	EPA 602	50 ug/L
Total Xylene	EPA 602	50 ug/L
Chemical Oxygen Demand (COD)	EPA 410.4	120 mg/L

## APPENDIX A

### Definitions

## Definitions and Acronyms

*Note: Additional definitions are provided within the Part VIII industrial sectors for definitions that are specific for those industries.*

**Best Management Practices (BMPs)** - means schedules of activities, prohibitions of practices, maintenance procedures, and other management practices to prevent or reduce the pollution of waters of the state. BMPs also include treatment requirements (if determined necessary by the permittee), operating procedures, and practices to control plant site runoff, spillage and leaks, sludge or waste disposal, or drainage from raw material storage.

**Co-located Industrial Activities** - occurs when a facility has industrial activities included in more than one industrial sector. Stormwater discharges from co-located activities must comply with requirements for all relevant sectors.

**Control Measure** - refers to any BMP or other method (including effluent limitations) used to prevent or reduce the discharge of pollutants to waters of the United States.

**Department** - means the New York State Department of Environmental Conservation as well as meaning the department's designated agent.

**Discharge** - means any addition of any pollutant to waters of the State through an outlet or point source.

**Discharge Authorized by a SPDES Permit** - means discharges of wastewater or stormwater from sources listed in the permit, that do not violate ECL Section 17-0501, that are through outfalls listed in the permit, and that are:

- (i) discharges within permit limitations of pollutants limited in the SPDES permit;
- (ii) discharges within permit limitations of pollutants limited by an indicator limit in the SPDES permit;
- (iii) discharges of pollutants subject to action level requirements in the SPDES permit;
- (iv) discharges of pollutants not explicitly listed in the SPDES permit, but reported in the SPDES permit application record as detected in the discharge or as something the permittee knows or has reason to believe to be present in the discharge, provided the special conditions section of the applicable SPDES permit does not otherwise forbid such a discharge and provided that such discharge does not exceed, by an amount in excess of normal effluent variability, the level of discharge that may reasonably be expected for that pollutant from information provided in the SPDES permit application record;
- (v) discharges of pollutants not required to be reported on the appropriate and current New York State SPDES permit application; provided the special conditions section of the permit does not otherwise forbid such a discharge. The Department may, in accordance with law and regulation, modify the permit to include limits for any pollutant even if that pollutant is not required to be reported on the SPDES permit application; or
- (vi) discharges from fire fighting activities; fire hydrant flushings; testing of fire fighting equipment, provided that such equipment is for water only fire suppression; potable water



sources including waterline flushings; irrigation drainage; lawn watering; uncontaminated infiltration and inflow; leakage from raw water conveyance systems; routine external building washdown and vehicle washing which does not use detergents or other compounds; pavement washwaters where spills or leaks of toxic or hazardous materials, other than minor and routine releases from motor vehicles, have not occurred (unless such material has been removed) and where detergents are not used; air conditioning and steam condensate; springs; uncontaminated groundwater; and foundation or footing drains where flows are not contaminated with process materials such as solvents provided that the permittee has implemented an effective plan for minimizing the discharge of pollutants from all of the sources listed in this subparagraph.

**Discharge Monitoring Report (DMR)** - means a report submitted by a permittee to the department summarizing the effluent monitoring results obtained by the permittee over periods of time as specified in the SPDES permit.

**Environmental Conservation Law (ECL)** - means chapter 43-B of the Consolidated Laws of the State of New York, entitled the Environmental Conservation Law.

**Effluent Limitation** - means any restriction on quantities, quality, rates and concentrations of chemical, physical, biological, and other constituents of effluents that are discharged into waters of the state.

**Effluent Limitation Guideline (ELG)** - means toxic or pretreatment effluent limitations contained in 40 CFR Parts 405 to 471 (see 6 NYCRR 750-1.24 of this Part).

**General SPDES permit** - means a SPDES permit issued pursuant to 6 NYCRR Part 750-1.21 authorizing a category of discharges.

**Groundwater** - means waters in the saturated zone. The saturated zone is a subsurface zone in which all the interstices are filled with water under pressure greater than that of the atmosphere. Although the zone may contain gas-filled interstices or interstices filled with fluids other than water, it is still considered saturated.

**Impaired Water** - a water is impaired if it does not meet its designated use(s). For purposes of this permit 'impaired' refers to threatened and impaired waters in categories 4a (those for which TMDLs have been established), 4b (those for which existing controls such as permits are expected to resolve the impairment), and 5 (those needing a TMDL) of a state's or tribe's integrated report on water quality. Impaired waters compilations are also sometimes referred to as 303(d) lists; 303(d) lists generally include only waters for which TMDLs have not yet been developed. States will generally have associated, but separate lists of impaired waters for which TMDLs have already been established.

**Individual SPDES Permit** - means an SPDES "permit" issued to a single facility in one location in accordance with this Part (as distinguished from a general SPDES permit).

**Industrial Activity** - the 11 categories of industrial activities included in the definition of "stormwater discharges associated with industrial activity."

**Industrial Stormwater** - stormwater runoff associated with the definition of "stormwater discharges associated with industrial activity."

**Industrial Waste** - means any liquid, gaseous, solid or waste substance or a combination thereof resulting from any process of industry, manufacturing, trade, or business or from the development or recovery of any natural resources, which may cause or might reasonably be expected to cause pollution of the waters of the state in contravention of the standards adopted as provided herein.

**Method Detection Level** - means the level at which the analytical procedure referenced is capable of determining with a 99 percent probability that the substance is present. The precision at this level is plus or minus 100 percent.

**Municipality** - means any county, town, city, village, district corporation, special improvement district, sewer authority or agency thereof.

**Municipal Separate Storm Sewer** - a conveyance or system of conveyances (including roads with drainage systems, municipal streets, catch basins, curbs, gutters, ditches, man-made channels, or storm drains):

- (i) Owned or operated by a State, city, town, borough, county, parish, district, association, or other public body (created by or pursuant to State law) having jurisdiction over disposal of sewage, industrial wastes, stormwater, or other wastes, including special districts under State law such as a sewer district, flood control district or drainage district, or similar entity, or an Indian tribe or an authorized Indian tribal organization, or a designated and approved management agency under section 208 of the CWA that discharges to waters of the United States;
- (ii) Designed or used for collecting or conveying stormwater;
- (iii) Which is not a combined sewer; and
- (iv) Which is not part of a Publicly Owned Treatment Works (POTW) as defined at 40 CFR 122.2.

**National Pollutant Discharge Elimination System (NPDES)** - means the national system for the issuance of wastewater and stormwater permits under the Federal Water Pollution Control Act (Clean Water Act).

**No exposure** - all industrial materials or activities are protected by a storm-resistant shelter to prevent exposure to rain, snow, snowmelt, and/or runoff.

**Outfall** - means the terminus of a sewer system, or the point of emergence of any waterborne sewage, industrial waste or other wastes or the effluent therefrom, into the waters of the state.

**Owner or operator** - means the owner or operator of any facility or activity subject to regulation under this Part.

**Permittee** - means the holder of a SPDES permit.

**Person or persons** - means any individual, public or private corporation, political subdivision, government agency, municipality, partnership, association, firm, trust, estate or any other legal entity whatsoever.

**Point source** - means any discernible, confined and discrete conveyance, including but not limited to any pipe, ditch, channel, tunnel, conduit, well, discrete fissure, container, rolling stock, concentrated animal feeding operation, vessel or other floating craft, or landfill leachate collection system from which pollutants are or may be discharged.

**Pollutant** - means dredged spoil, filter backwash, solid waste, incinerator residue, sewage, garbage, sewage sludge, munitions, chemical wastes, biological materials, radioactive materials, heat, wrecked or discarded equipment, rock, sand and industrial, municipal, agricultural waste and ballast discharged into water; which may cause or might reasonably be expected to cause pollution of the waters of the state in contravention of the standards or guidance values adopted as provided in Parts 700 et seq of this Title.

**Qualified Personnel** - Qualified personnel are those who possess the knowledge and skills to assess conditions and activities that could impact stormwater quality at your facility, and who can also evaluate the effectiveness of BMPs.

**Reportable Quantity Release** - a release of a hazardous substance at or above the established legal threshold that requires emergency notification. Refer to 40 CFR Parts 110, 177, and 302 for complete definitions and reportable quantities for which notification is required.

**Runoff coefficient** - the fraction of total rainfall that will appear at the conveyance as runoff.

**Significant materials** - includes, but is not limited to: raw materials; fuels; materials such as solvents, detergents, and plastic pellets; finished materials such as metallic products; raw materials used in food processing or production; hazardous substances designated under section 101(14) of CERCLA; any chemical the facility is required to report pursuant to section 313 of Title III of SARA; fertilizers; pesticides; and waste products such as ashes, slag and sludge that have the potential to be released with stormwater discharges.

**State** - means the State of New York.

**State Pollutant Discharge Elimination System (SPDES)** - means the system established pursuant to Article 17 of the ECL and this Part for issuance of permits authorizing discharges to the waters of the state.

**Stormwater** - means that portion of precipitation that, once having fallen to the ground, is in excess of the evaporative or infiltrative capacity of soils, or the retentive capacity of surface features, which flows or will flow off the land by surface runoff to waters of the state.

**Stormwater Discharges Associated with Industrial Activity** - the discharge from any conveyance that is used for collecting and conveying stormwater and that is directly related to manufacturing, processing or raw materials storage areas at an industrial plant. The term does not include discharges from facilities or activities excluded from the NPDES program under Part 122. For the categories of industries identified in this section, the term includes, but is not limited to, stormwater discharges from industrial plant yards; immediate access roads and rail lines used or traveled by carriers of raw materials, manufactured products, waste material, or by-products used or created by the facility; material handling sites; refuse sites; sites used for the application or disposal of process waste waters (as defined at 40 CFR Part 401 of this chapter); sites used for the storage and maintenance of material handling equipment; sites used for residual treatment, storage, or disposal; shipping and receiving areas; manufacturing buildings; storage areas (including tank farms) for raw materials, and intermediate and final products; and areas where industrial activity has taken place in the past and significant materials remain and are exposed to stormwater. For the purposes of this paragraph, material handling activities include storage, loading and unloading, transportation, or conveyance of any raw material, intermediate product, final product, by-product or waste product. The term excludes areas located on plant lands separate from the plant's industrial activities, such as office buildings and accompanying parking lots as long as the drainage from the excluded areas is not mixed with stormwater drained from the above described areas. Industrial facilities include those that are federally, State, or municipally owned or operated that meet the description of the facilities listed in Appendix D of this permit. The term also includes those facilities designated under the provisions of 40 CFR 122.26(a)(1)(v).

**Total Maximum Daily Loads (TMDLs)** - A TMDL is the sum of the allowable loads of a single pollutant from all contributing point and nonpoint sources. It is a calculation of the maximum amount of a pollutant that a waterbody can receive and still meet water quality standards, and an allocation of that amount to the pollutant's sources. A TMDL stipulates wasteload allocations (WLAs) for point source discharges, load allocations (LAs) for nonpoint sources, and a margin of safety (MOS).

**Waters of the United States - means:**

- (i) All waters which are currently used, were used in the past, or may be susceptible to use in interstate or foreign commerce, including all waters that are subject to the ebb and flow of the tide;
- (ii) All interstate waters, including interstate "wetlands";
- (iii) All other waters, such as interstate lakes, rivers, streams (including intermittent streams), mudflats, sandflats, wetlands, sloughs, prairie potholes, wet meadows, playa lakes, or natural ponds, the use, degradation, or destruction of which would affect or could affect interstate or foreign commerce, including any such waters:
  - a. Which are or could be used by interstate or foreign travelers for recreational or other purposes;
  - b. From which fish or shellfish are or could be taken and sold in interstate or foreign commerce; or
  - c. Which are or could be used for industrial purposes by industries in interstate commerce;
- (iv) All impoundments of waters otherwise defined as waters of the United States under this definition;
- (v) Tributaries of waters identified in paragraphs (1) through (4) of this definition;
- (vi) The territorial sea; and
- (vii) Wetlands adjacent to waters (other than waters that are themselves wetlands) identified in paragraphs 1 through 6 of this definition.

**Waters or Waters of the State** - shall be construed to include lakes, bays, sounds, ponds, impounding reservoirs, springs, wells, rivers, streams, creeks, estuaries, marshes, inlets, canals, the Atlantic ocean within the territorial seas of the state of New York and all other bodies of surface or underground water, natural or artificial, inland or coastal, fresh or salt, public or private (except those private waters that do not combine or effect a junction with natural surface or underground waters), which are wholly or partially within or bordering the state or within its jurisdiction. Waters of the state are further defined in 6 NYCRR Parts 800 to 941.

**Water Quality Standard** - means such measures of purity or quality for any waters in relation to their reasonable and necessary use as promulgated in 6 NYCRR Part 700 et seq.

## ACRONYMS

BOD5 – Biochemical Oxygen Demand (5-day test)  
BMP – Best Management Practice  
CBS - Chemical Bulk Storage  
COD – Chemical Oxygen Demand  
CWA – Clean Water Act (or the Federal Water Pollution Control Act, 33 U.S.C. §1251 et seq)  
DMR – Discharge Monitoring Report  
ECL - Environmental Conservation Law  
ELG – Effluent Limitations Guidelines  
EPA – U. S. Environmental Protection Agency  
EPCRA – Emergency Planning and Community Right-to-know Act  
MDL - Method Detection Limit  
MGD – Million Gallons per Day  
MS4 – Municipal Separate Storm Sewer System  
MSGP – Multi-Sector General Permit  
NOIT – Notice of Intent or Termination  
NPDES – National Pollutant Discharge Elimination System  
NRC – National Response Center  
NTU – Nephelometric Turbidity Unit  
PBS - Petroleum Bulk Storage  
PQL - Practical Quantitation Limit  
RCRA – Resource Conservation and Recovery Act  
RQ – Reportable Quantity  
SIC – Standard Industrial Classification  
SPCC – Spill Prevention, Control, and Countermeasure  
SWPPP – Stormwater Pollution Prevention Plan  
TMDL – Total Maximum Daily Load  
TSS – Total Suspended Solids  
USGS – United States Geological Survey

## **APPENDIX B**

### **Notice of Intent or Termination**

## **APPENDIX C**

### **Annual Certification Report**





**SECTION IV: STORMWATER MONITORING - BENCHMARK PARAMETERS:**

11. Is the permittee required to monitor stormwater at the facility for benchmark parameters? (If no, skip to Section V) ..... ☐ Yes ☐ No
12. Were there any of the sampling results from this year higher than the cut-off values listed in the permit? ..... ☐ Yes ☐ No
13. Were there any monitoring problems? (Answer "Yes" if storm event criteria was not met or if the laboratory indicated quality assurance/quality control problems) ..... ☐ Yes ☐ No
14. If any of the sampling results were higher than the benchmark values listed in the permit, was the facility inspected to identify the source? ..... ☐ Yes ☐ No ☐ NA
15. Did this result in modification of the SWPPP? ..... ☐ Yes ☐ No

**SECTION IV: STORMWATER MONITORING - COMPLIANCE MONITORING**

16. Is the permittee required to conduct compliance monitoring for storm water discharges subject to Point Source Category Effluent Limitation? ..... ☐ Yes ☐ No
17. Is the permittee required to conduct compliance monitoring for storm water discharges from coal piles? (If no to questions 16 & 17, go to Section VI) ..... ☐ Yes ☐ No
18. Were there any monitoring problems? (Answer "Yes" if storm event criteria was not met or if the laboratory indicated quality assurance/quality control problems) ..... ☐ Yes ☐ No
19. Were any of the sampling results from this year higher than the effluent limitation listed in the permit? ..... ☐ Yes ☐ No
20. If any of the sampling results were higher than the effluent limitations listed in the permit, was the facility inspected to identify the source? ..... ☐ Yes ☐ No ☐ NA
21. Did this result in modification of the SWPPP? ..... ☐ Yes ☐ No

**SECTION VI: SUMMARY**

Provide a brief description of any facility changes; problems identified during comprehensive compliance evaluations, quarterly visual observations or monitoring results; and action taken to improve the quality of the stormwater discharge.

**CERTIFICATION**

I certify under penalty of law that this document and all attachments were prepared under my direction or supervision in accordance with a system designed to assure that qualified personnel properly gathered and evaluated the information submitted. Based on my inquiry of the person or persons who manage the system, or those persons directly responsible for gathering the information, the information submitted is, to the best of my knowledge and belief, true, accurate, and complete. I am aware that there are significant penalties for submitting false information, including the possibility of fine and imprisonment for knowing violations.

Owner/Operator First Name (please print or type)

MI

Date

Owner/Operator Last Name (please print or type)

Signature

## **APPENDIX D**

### **Example Quarterly Visual Monitoring Report**

## Quarterly Visual Monitoring Form

*Example*

*Fill out a separate form for each sample you collect (one form per quarter per outfall)*

<b>Facility:</b>		<b>Permit ID: NYR00</b> _____	
<b>Outfall No.:</b>	<b>Examiner's Name &amp; Title:</b>		
<b>Quarter/Year:</b>	<b>Date/Time Collected:</b>	<b>Date/Time Examined:</b>	
<b>Rainfall Amount:</b>	<b>Qualifying Storm?</b> Yes    No	<b>Runoff Source:</b> Rainfall Snowmelt	

Parameter	Parameter Description	Parameter Characteristics
<b>Color</b>	Does the stormwater appear to be colored? Yes                      No	<b>Describe:</b>
<b>Clarity</b>	Is the stormwater clear or transparent? Yes                      No	Which of the following best describes the clarity of the stormwater?    Clear    Milky    Opaque
<b>Oil Sheen</b>	Can you see a rainbow effect or sheen on the water surface? Yes                      No	Which bests describes the sheen?  Rainbow sheen              Floating Oil globules
<b>Odor</b>	Does the sample have an odor? Yes                      No	<b>Describe:</b>
<b>Floating Solids</b>	Is there something floating on the surface of the sample? Yes                      No	<b>Describe:</b>
<b>Suspended Solids</b>	Is there something suspended in the water column of the sample? Yes                      No	<b>Describe:</b>
<b>Settled Solids</b>	Is there something settled on the bottom of the sample? Yes                      No	<b>Describe:</b>
<b>Foam</b>	Is there foam or material forming on the top of the sample surface? Yes                      No	<b>Describe:</b>

*Detail any concerns, corrective actions taken and any other indicators of pollution present in the sample:*

**Stormwater Examiner's Signature:**

## APPENDIX E

### *Example* Discharge Monitoring Report (For Effluent Guideline Limitations and Benchmark Monitoring Cut-Off Concentrations)

PERMITTEE NAME/ADDRESS (include Facility Name, Location & District)  
NAME

ADDRESS

FACILITY  
LOCATION

NATIONAL POLLUTANT DISCHARGE ELIMINATION SYSTEM (NPDES)  
DISCHARGE MONITORING REPORT (DMR)  
12-16 11-11

NY900  
PERMIT NUMBER DISCHARGE NUMBER

MONITORING PERIOD  
YEAR MO DAY YEAR MO DAY  
FROM (20-21) (22-23) (24-25) TO (26-27) (28-29) (30-31)

☐ Check here if No Discharge

NOTE: Read Instructions before completing this form

PARAMETER (32-37)	X	(3 Card Only) (45-48) QUANTITY OR LOADING (4-8)			(4 Card Only) (58-65) QUALITY OR CONCENTRATION (10-11)			NO. TX (62-63)	FREQUENCY OF ANALYSIS (64-68)	SAMPLE TYPE (69-70)
		AVERAGE	MAXIMUM	UNITS	MINIMUM	AVERAGE	MAXIMUM			
DATE OF STORM EVENT	SAMPLE MEASUREMENT	*****	*****		*****	*****	*****		***	*****
	PERMIT REQUIREMENT	*****	*****		*****	*****	*****		*****	*****
DURATION OF - _____ HRS STORM	SAMPLE MEASUREMENT	*****		INS	*****	*****		GALE	**	*****
ELAPSED SINCE _____ DAYS LAST STORM > 0.1 INS	PERMIT REQUIREMENT	*****	ESTIMATE RAINFALL		*****	*****	ESTIMATE VOL. DLS		ONCE/ YEAR	*****
FLUORIDE, TOTAL (AS F)	SAMPLE MEASUREMENT	*****	*****		*****			MG/L		
00551 1	PERMIT REQUIREMENT	*****	*****		*****	25.0 30-DAY AVG	75.0 DAILY MAX		ONCE/ YEAR	GRAMS
EFFLUENT GROSS VALUE	SAMPLE MEASUREMENT	*****	*****		*****			MG/L		
PHOSPHORUS, TOTAL (AS P)	PERMIT REQUIREMENT	*****	*****		*****	35.0 30-DAY AVG	105.0 DAILY MAX		ONCE/ YEAR	GRAMS
00665 1	SAMPLE MEASUREMENT									
EFFLUENT GROSS VALUE	PERMIT REQUIREMENT									
	SAMPLE MEASUREMENT									
	PERMIT REQUIREMENT									
	SAMPLE MEASUREMENT									
	PERMIT REQUIREMENT									
	SAMPLE MEASUREMENT									
	PERMIT REQUIREMENT									

NAME/TITLE PRINCIPAL EXECUTIVE OFFICER	SIGNATURE OF PRINCIPAL EXECUTIVE OFFICER OR AUTHORIZED AGENT	TELEPHONE		DATE	
		AREA	NUMBER	YEAR	MO DAY

COMMENTS AND EXPLANATION OF ANY VIOLATIONS (Reference all attachments here)  
SECTOR C: CHEMICAL AND ALLIED PRODUCTS MANUFACTURERS, SUBSECTOR: AGRICULTURAL CHEMICALS  
SIC CODE: 287X

APPLICABLE ONLY TO: Discharges from the Phosphate Subcategory of the Fertilizer Manufacturing Point Source Category (see 40 CFR Part 418)

Send completed DMR to: Industrial Storm Water General Permit Coordinator, NYSDEC, Bureau of Water Permits, 625 Broadway, Albany, NY 12233-3505

Page: \_\_\_\_ of \_\_\_\_

## **APPENDIX F**

### **Additional Information for New Discharges**

## ***Appendix F - Additional Information For New Stormwater Discharges***

(See General Permit Part II.A on page 9)

Any facility with new stormwater discharges associated with industrial activity which require any other Uniform Procedures Act permit(s) (Environmental Conservation Law, 6 NYCRR Part 621) are not initially eligible for coverage under this general permit. The discharger must first complete a Short Environmental Assessment Form which can be found in Appendix C of 6 NYCRR Part 617. Upon a review of the Short Environmental Assessment Form and the information specified below, the Department may authorize the applicant to submit a Notice of Intent or Termination (NOIT) to obtain coverage under this general permit or, alternatively, require an application for an individual SPDES permit.

### **Additional Information**

1. A site map showing topography (or indicating the outline of drainage areas served by the outfall(s) for which discharge authorization and permit coverage is being sought if a topographic map is unavailable) of the facility including: each of its drainage and discharge structures; the drainage area of each stormwater outfall; paved areas and buildings within the drainage area of each stormwater outfall; areas used for outdoor storage or disposal of significant materials; structural control measure(s) to reduce pollutants in stormwater runoff; material loading and access areas; areas where pesticides, herbicides, soil conditioners and fertilizers are applied; each hazardous waste treatment, storage or disposal facility (including each area not required to have a RCRA permit which is used for accumulating hazardous waste under 40 CFR 262.34); each well where fluids from the facility are injected underground; and springs, and surface and/or groundwater bodies which will receive stormwater discharges from the facility.
2. An estimate of the area of impervious surfaces (including paved areas and building roofs) and the total area drained by each outfall and a narrative description of the following: significant materials that, in the three years prior to the submittal of this information, have been treated, stored or disposed of in a manner which will allow exposure to stormwater; methods of treatment, storage or disposal of such materials; materials management practices employed to minimize contact of these materials with stormwater runoff; materials loading and access areas; the location, manner and frequency of application of pesticides, herbicides, soil conditioners and fertilizers; the location and description of structural and non-structural control measures being used to reduce pollutants in stormwater runoff; and a description of the stormwater treatment, including the ultimate disposal of any solid or fluid wastes other than by discharge.
3. A certification that all outfalls that could contain stormwater discharges associated with industrial activity have been tested or evaluated for the presence of non-stormwater discharges which are not covered by an existing SPDES permit; tests for such non-stormwater discharges may include smoke tests, fluorometric, analysis of accurate schematics, as well as other appropriate tests. The certification shall include a description of the method used, the date of any testing, and the on-site drainage points that were directly observed during a test.
4. Existing information regarding reportable leaks or spills of toxic or hazardous pollutants at the facility that have occurred within the three years prior to the submittal of this information.
5. Estimates for the following parameters for all outfalls:
  - Any pollutant limited in an effluent limitations guideline for which the facility is subject;
  - Any pollutant listed in the facility's existing SPDES permit, if any;
  - Oil and grease, pH, BOD5, COD, TSS, total phosphorus, total Kjeldahl nitrogen, and nitrate plus nitrite nitrogen;
  - Any information on the discharge required under paragraph §122.21.21(g)(7)(iii) and (iv) of 40 CFR Part 122; and
  - The flow rate and total amount of discharge for stormwater event(s) and the method of estimation.

Other information as the State Director may reasonably require to determine whether coverage under this general permit or, alternatively, under an individual permit is acceptable.



## **APPENDIX G**

### **List of DEC Regional Offices**